

Safety Data Sheets

All

All

B&H Mechanical

07/19/2021

Safety Data Sheet Index
Binder: B&H Mechanical - All

Product Name	Manufacturer Name	Part Number	Version Date	Page
587	John Tillman Co.		08/25/2015	3
ABC DRY CHEMICAL FIRE EXTINGUISHANT	BUCKEYE FIRE EQUIPMENT COMPANY		04/01/2015	11
ABC Dry Chemical Fire Extinguishant	AMEREX CORPORATION		03/13/2018	20
ANSUL ABC Multipurpose Dry Chemical Agent - Stored Pressure System	Tyco Fire Protection Products		02/13/2019	32
FS-ONE High Performance Intumescent Firestop Sealant	Hilti Inc.		02/19/2015	41
FS-ONE High Performance Intumescent Firestop Sealant	HILTI, Inc.		01/31/2004	43



Safety Data Sheet

587

SDS Revision Date:

08/25/2015

1. Identification

1.1. Product identifier

Product Identity 587

Alternate Names 587

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name John Tillman Company
1300 W. Artesia Blvd.
Compton, CA 90220. USA

Emergency

24 hour Emergency Telephone No. 310-764-0110

Customer Service: 310-764-0110

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Eye Irrit. 2;H319 May cause eye irritation.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Warning

H319 May cause eye irritation.

[Prevention]:

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P337+313 If eye irritation persists: Get medical advice / attention.

[Storage]:



TILLMAN™
The Brand Pros Demand

Safety Data Sheet

587

SDS Revision Date:

08/25/2015

No GHS storage statements

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Fibrous glass CAS Number: 0065997-17-3	100	Eye Irrit. 2;H319	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Drink water to clear throat, blow nose to evacuate fibers.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	Exposure with the product may cause skin, eye, and respiratory tract irritation. See section 2 for further details.
Eyes	May cause eye irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Water, carbon dioxide, or dry chemical.



5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Carbon monoxide, carbon dioxide

5.3. Advice for fire-fighters

Thermal decomposition of fiber coating may produce an Irritating mixture of smoke and fumes. Fire fighters should wear full protective gear including NIOSH approved self-contained breathing apparatus.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Prevent the spread of fiberglass dust & avoid dust generation conditions. Those involved in clean up of particulates should use appropriate personal protective equipment. Vacuum clean dusts. If sweeping is necessary, use a dust suppressant.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Store and use in a manner that will prevent airborne particulates in the workplace.

Incompatible materials: Strong oxidizing agents.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0065997-17-3	Fibrous glass, glass	OSHA	15 mg/m ³ (as nuisance dust)5 mg/m ³ (respirable fraction)
		ACGIH	10 mg/m ³ (as nuisance dust)5 mg/m ³ (respirable fraction)
		NIOSH	No Established Limit



		Supplier	No Established Limit
--	--	----------	----------------------

Carcinogen Data

CAS No.	Ingredient	Source	Value
0065997-17-3	Fibrous glass, glass	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

- Respiratory** Where dust level exceeds the TLV, use NIOSH approved respirator to protect against nuisance dusts.
- Eyes** Safety glasses with side shield goggles.
- Skin** Work aprons or smocks are recommended. Wear loose fitting long sleeved clothing. NIOSH approved air supplied or self contained respirator. Protective Gloves and barrier creams if necessary.
- Engineering Controls** Local Exhaust Recommended for processing machinery where dust generation is apparent. Mechanical exhaust is acceptable where local exhaust is not feasible.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Plain Weave Heavy Weight Fiberglass Fabric
Odor	No smell
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	> 1000°F
Initial boiling point and boiling range	Not Measured
Flash Point	250°C (TOC)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapor pressure (Pa)	Not Measured
Vapor Density	Not Measured
Specific Gravity	2.5
Solubility in Water	None
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured



Safety Data Sheet

587

SDS Revision Date:

08/25/2015

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide, carbon dioxide

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Fibrous glass, glass - (65997-17-3)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable



Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Fibrous glass, glass - (65997-17-3)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

In most cases, woven fiberglass scrap can be disposed of in a sanitary landfill in accordance with Federal, State, & local regulations. Check with local authorities any questions concerning disposal.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated



14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user			
No further information			

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.		
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.		
WHMIS Classification	D2B		
US EPA Tier II Hazards	Fire: No	Sudden Release of Pressure: No	Reactive: No
	Immediate (Acute): Yes		
	Delayed (Chronic): No		

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%) :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Pennsylvania RTK Substances (>1%) :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein.



TILLMAN™
The Brand Pros Demand

Safety Data Sheet

587

SDS Revision Date:

08/25/2015

We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H319 Causes serious eye irritation.

End of Document

Common Name: ABC DRY CHEMICAL FIRE EXTINGUISHANT

Manufacturer: BUCKEYE FIRE EQUIPMENT

SDS Revision Date: 4/1/2015

SDS Format: GHS-US

Grainger Item Number(s): 2LBP1, 31CA37, 35WT05, 35WT06, 35WT07, 35WT08, 35WT09, 35WT10, 35WT11, 35WT41, 35WT42, 35WT43, 35WT44, 3GRW5, 3GRW6, 3GRW7, 3GRW8, 3GRY3, 3GRY4, 3GRY5, 3GRY6, 3GRY7, 3GRY8, 3GRZ4, 44YZ28, 44YZ29, 44YZ30, 44YZ31, 44YZ33, 44YZ35

Manufacturer Model Number(s):

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

[SECTION I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION](#)

[SECTION II. HAZARD IDENTIFICATION](#)

[SECTION III. COMPOSITION/INFORMATION ON INGREDIENTS](#)

[SECTION IV. FIRST AID MEASURES](#)

[SECTION V. FIREFIGHTING MEASURES](#)

[SECTION VI. ACCIDENTAL RELEASE MEASURES](#)

[SECTION VII. HANDLING AND STORAGE](#)

[SECTION VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION](#)

[SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES](#)

[SECTION X. STABILITY AND REACTIVITY](#)

[SECTION XI. TOXICOLOGICAL INFORMATION](#)

[SECTION XII. ECOLOGICAL INFORMATION](#)

[SECTION XIII. DISPOSAL CONSIDERATION](#)

[SECTION XIV. TRANSPORTATION INFORMATION](#)

[SECTION XV. REGULATORY INFORMATION](#)

[SECTION XVI. OTHER INFORMATION](#)

SAFETY DATA SHEET

ABC DRY CHEMICAL

SECTION I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION



PRODUCT NAME: ABC DRY CHEMICAL FIRE EXTINGUISHANT

SYNONYM: MULTI-PURPOSE DRY CHEMICAL

MANUFACTURER:

BUCKEYE FIRE EQUIPMENT COMPANY

110 KINGS ROAD

KINGS MOUNTAIN, NC 28086

TELEPHONE: 704.739.7415

WEB ADDRESS: WWW.BUCKEYEFIRE.COM

EMAIL ADDRESS: BFEC@BUCKEYEF.COM

RECOMMENDED USE: FIRE SUPPRESSION, NOT FOR HUMAN OR ANIMAL DRUG USE.

EMERGENCY:

CHEMTREC: 1.800.424.9300

REVISION DATE: 04/2015

SECTION II. HAZARD IDENTIFICATION



GHS - CLASSIFICATION:

EYE IRRITATION: CLASS 2B

SKIN IRRITATION: CLASS 3

INHALATION: CLASS 5

GHS LABEL ELEMENTS:

HAZARD SYMBOLS: EXCLAMATION MARK

SIGNAL WORD: WARNING

HAZARD STATEMENTS:

H313: MAY BE HARMFUL IN CONTACT WITH SKIN.

H320: CAUSES EYE IRRITATION

H333: MAY BE HARMFUL IF INHALED.

PRECAUTIONARY STATEMENTS:

P101:

IF MEDICAL ADVICE IS NEEDED, HAVE PRODUCT CONTAINER OR LABEL AT HAND.

P102: KEEP OUT OF REACH OF CHILDREN.

P234: KEEP IN ORIGINAL CONTAINER.

P251: PRESSURIZED CONTAINER; DO NOT PIERCE OR BURN, EVEN AFTER USE

P261: AVOID BREATHING DUST

P264: WASH HANDS AND FACE THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK, OR SMOKE WHEN USING THIS PRODUCT

P281: USE PERSONAL PROTECTIVE EQUIPMENT AS REQUIRED

P285: IN CASE OF INADEQUATE VENTILATION, WEAR RESPIRATORY PROTECTION

P301+322+331:

IF SWALLOWED, DRINK 2-3 GLASSES OF WATER AND DO NOT INDUCE VOMITING

302+352: IF ON SKIN, WASH WITH SOAP AND WATER

304+313+341:

IF INHALED, AND IF DISTRESS OCCURS, REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. SEEK MEDICAL ADVICE/ATTENTION.

305+351+338:

IF IN EYES, RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES IF PRESENT AND EASY TO DO, AND CONTINUE TO RINSE.

337+313: IF EYE IRRITATION PERSISTS, GET MEDICAL ADVICE/ATTENTION.

P401+402+403:

STORE IN ORIGINAL CONTAINER OR EXTINGUISHER IN A DRY, WELL VENTILATED PLACE.

SECTION III. COMPOSITION/INFORMATION ON INGREDIENTS



THIS PRODUCT IS A MIXTURE.

CHEMICAL NAME	WEIGHT %*	CAS #
MONOAMMONIUM PHOSPHATE	85	7722-76-1
BARIUM SULFATE	10	7727-43-7
MICA	<3	12001-26-2
SILICA	<2	7631-86-9
STANNOUS OCTOATE	<.3	301-10-0
SILICONE	<.1	63148-57-2
PIGMENT	<.1	6358-31-2

* % IS ROUNDED TO THE NEAREST APPROPRIATE NUMBER. VALUES ARE NOT TO BE CONSIDERED PRODUCT SPECIFICATIONS

SECTION IV. FIRST AID MEASURES



EYE EXPOSURE:

FLUSH EYES WITH WATER UNTIL PAIN-FREE. IF IRRITATION DEVELOPS OR PERSISTS, SEEK MEDICAL ATTENTION.

SKIN EXPOSURE:

WASH WITH PLENTY OF SOAP AND WATER. IF IRRITATION DEVELOPS OR PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION:

MOVE VICTIM TO FRESH AIR. IF IRRITATION DEVELOPS OR PERSISTS, SEEK MEDICAL ATTENTION.

INGESTION:

IF VICTIM IS CONSCIOUS AND ALERT, GIVE 2-3 GLASSES OF WATER TO DRINK. DO NOT INDUCE VOMITING. IF VOMITING OCCURS AND THE VICTIM IS CONSCIOUS, GIVE ADDITIONAL WATER TO FURTHER DILUTE THE CHEMICAL. PREVENT ASPIRATION OF SWALLOWED PRODUCT BY LAYING VICTIM ON SIDE WITH HEAD LOWER THAN THEIR WAIST. SEEK MEDICAL ATTENTION. DO NOT LEAVE VICTIM UNATTENDED.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE:

INHALATION OF THE PRODUCT MAY AGGRAVATE EXISTING CHRONIC RESPIRATORY CONDITIONS SUCH AS ASTHMA, EMPHYSEMA, OR BRONCHITIS. CONTACT WITH THE SKIN MAY AGGRAVATE AN EXISTING SKIN DISEASE. CHRONIC OVEREXPOSURE MAY CAUSE PNEUMOCONIOSIS ("DUSTY LUNG" DISEASE).

SECTION V. FIREFIGHTING MEASURES



EXTINGUISHING MEDIA:

N/A. THIS PRODUCT IS AN EXTINGUISHING AGENT. IT IS NONFLAMMABLE AND NONCOMBUSTIBLE.

SPECIAL FIREFIGHTING PROCEDURES: N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS:

THIS PRODUCT MAY DECOMPOSE IN FIRE AND RELEASE OXIDES OF CARBON, POTASSIUM, AND NITROGEN (REFER TO SECTION X).

SENSITIVITY TO MECHANICAL IMPACT OR STATIC DISCHARGE: NONE

SECTION VI. ACCIDENTAL RELEASE MEASURES



IN CASE OF ACCIDENTAL RELEASE, USE THE APPROPRIATE RESPIRATORY PROTECTION. CLEAN UP THE PRODUCT USING A VACUUM OR WET SWEEP AND SHOVEL TO MINIMIZE THE GENERATION OF DUST. BAG OR DRUM THE PRODUCT FOR DISPOSAL. IF THE PRODUCT IS USED AND/OR CONTAMINATED, USE PERSONAL PROTECTIVE EQUIPMENT AND CONTAINMENT MEANS THAT ARE APPROPRIATE FOR THE COMPOSITION OF THE MIXTURE. PRODUCT SHOULD BE PREVENTED FROM ENTERING WATERWAYS.

SECTION VII. HANDLING AND STORAGE



AVOID EYE, RESPIRATORY, AND SKIN EXPOSURE. USE THE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT WHEN HANDLING. WASH THOROUGHLY AFTER HANDLING (REFER TO SECTION VIII). PRODUCT SHOULD BE STORED IN ITS ORIGINAL CONTAINER OR EXTINGUISHER. WHEN THE PRODUCT IS CONTAINED UNDER PRESSURE (E.G., AN EXTINGUISHER), INSPECT THE CONTAINER FOR RUST OR DAMAGE THAT MAY COMPROMISE THE CONTAINER INTEGRITY. DO NOT STORE THE PRODUCT IN HIGH HUMIDITY AND DO NOT MIX WITH OTHER EXTINGUISHING AGENTS, PARTICULARLY POTASSIUM BICARBONATE BASED AGENTS.

SECTION VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION



EXPOSURE GUIDELINES:

	OSHA PEL	ACGIH TLV
MONOAMONIUM PHOSPHATE	PARTICULATES NOT OTHERWISE CLASSIFIED	PARTICULATES NOT OTHERWISE CLASSIFIED
	TOTAL DUST: 15 MG/M3	TOTAL DUST: 10 MG/M3
	RESPIRABLE FRACTION: 5 MG/M3	RESPIRABLE FRACTION: 3 MG/M3
BARIUM SULFATE	PARTICULATES NOT OTHERWISE CLASSIFIED	PARTICULATES NOT OTHERWISE CLASSIFIED
	TOTAL DUST: 15 MG/M3	TOTAL DUST: 10 MG/M3
	RESPIRABLE FRACTION: 5 MG/M3	RESPIRABLE FRACTION: 3 MG/M3
MICA	6 MG/M3	3 MG/M3

SILICA	6 MG/M3	10 MG/M3
STANNOUS OCTOATE	.1 MG/M3	.1 MG/M3
SILICONE	NOT REGULATED	NOT REGULATED
PIGMENT	NOT REGULATED	NOT REGULATED

DURING THE USE OF THIS PRODUCT ON FIRES, EXHAUST GASES AND PRODUCTS OF INCOMPLETE COMBUSTION ARE THE MAIN RESPIRATORY HAZARDS. IN THE MANUFACTURE OF THIS PRODUCT, EMPLOYERS AND EMPLOYEES MUST USE THEIR COLLECTIVE JUDGMENT IN DETERMINING THE ON-THE-JOB SETTINGS WHERE THE USE OF A DUST MASK OR RESPIRATOR IS PRUDENT. THE NEED FOR RESPIRATORY PROTECTION IS NOT LIKELY FOR SHORT-TERM USE IN WELL-VENTILATED AREAS.

RESPIRATORY PROTECTION:

USE AN N-95 DUST MASK FOR LIMITED EXPOSURES AND USE AIR-PURIFYING RESPIRATORS WITH HIGH EFFICIENCY PARTICULATE AIR FILTERS (HEPA FILTERS) FOR PROLONGED EXPOSURES.

EYE PROTECTION:

WEAR CHEMICAL GOGGLES OR FULL-FACE AIR-PURIFYING RESPIRATOR.

SKIN PROTECTION:

USE NITRILE, LATEX, OR SIMILAR GLOVES AND COVERALLS. GOOD PERSONAL HYGIENE PRACTICES ARE ESSENTIAL. AFTER HANDLING THE PRODUCT, AVOID FOOD, TOBACCO PRODUCTS, OR OTHER MEANS OF TRANSFERRING THE PRODUCT FROM HAND TO MOUTH UNTIL AFTER THOROUGHLY WASHING.

SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES



APPEARANCE AND ODOR: LIGHT YELLOW FINE POWDER THAT IS ODORLESS.

APPARENT DENSITY: 0.82

SOLUBILITY:

THE PRODUCT IS COATED WITH WATER REPELLANT SILICONE. NOT IMMEDIATELY SOLUBLE IN WATER.

PH: APPROXIMATELY 4 -5

FLASH POINT: N/A

FLAMMABILITY: N/A

VAPOR PRESSURE: N/A

BOILING POINT: N/A

EXPLOSIVE OR OXIDIZING PROPERTIES: NONE

SECTION X. STABILITY AND REACTIVITY



STABILITY: STABLE

INCOMPATIBLES:

MAGNESIUM, STRONG OXIDIZERS SUCH AS CALCIUM HYPOCHLORITE (POOL CHLORINE), STRONG ALKALIS, AND ISOCYANURIC ACIDS.

DECOMPOSITION PRODUCTS:

THIS PRODUCT MAY DECOMPOSE IN FIRE AND RELEASE CARBON MONOXIDE, CARBON DIOXIDE, AND SULFUR DIOXIDE. OXIDES OF PHOSPHOROUS AND AMMONIA HAVE BEEN REPORTED.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS REACTIONS: NONE

SECTION XI. TOXICOLOGICAL INFORMATION



ACUTE TOXICITY:

MONOAMMONIUM PHOSPHATE LD50 (RAT): >1000 MG/KG BODY WEIGHT.

TARGET ORGANS IN HUMANS:

RESPIRATORY SYSTEM, EYES, AND SKIN. THIS PRODUCT IS AN IRRITANT TO EPITHELIAL TISSUE AND MAY AGGRAVATE DERMATITIS. NO INDICATION THAT THE PRODUCT CAUSES SENSITIZATION.

CHRONIC TOXICITY:

PNEUMOCONIOSIS, OR "DUSTY LUNG" DISEASE, MAY RESULT FROM CHRONIC EXPOSURE TO ANY DUST.

REPRODUCTIVE TOXICITY:

THIS PRODUCT IS NOT KNOWN TO HAVE ANY REPRODUCTIVE EFFECTS.

SECTION XII. ECOLOGICAL INFORMATION



ECOTOXICITY:

NEGATIVE EFFECTS ARE UNKNOWN. PROVIDES NUTRIENT NITROGEN AND PHOSPHOROUS TO PLANT LIFE.

DEGRADABILITY: DEGRADES RAPIDLY IN WET OR HUMID ENVIRONMENT.

BIOACCUMULATION: UNKNOWN EXTENT.

MOBILITY IN SOIL: WATER-SOLUBLE. MAY LEECH IN TO GROUNDWATER.

SECTION XIII. DISPOSAL CONSIDERATION



THIS PRODUCT IS NOT A RCRA CHARACTERISTICALLY HAZARDOUS OR LISTED HAZARDOUS WASTE. DISPOSE OF ACCORDING TO STATE OR LOCAL LAWS, WHICH MAY BE MORE RESTRICTIVE THAN FEDERAL REGULATIONS. BE AWARE THAT PRODUCT USED ON A FIRE MAY BE ALTERED OR CONTAMINATED AND THEREBY REQUIRE DIFFERENT DISPOSAL CONSIDERATIONS.

SECTION XIV. TRANSPORTATION INFORMATION



THIS PRODUCT IS NOT DEFINED AS A HAZARDOUS MATERIAL UNDER U.S. DEPARTMENT OF TRANSPORTATION 49 CFR 172, OR BY TRANSPORT CANADA "TRANSPORTATION OF DANGEROUS GOODS" REGULATIONS.

PLEASE NOTE:

ALTHOUGH THIS MATERIAL IS NOT CONSIDERED HAZARDOUS, WHEN CONTAINED IN A STORED PRESSURE FIRE EXTINGUISHER PRESSURIZED WITH A NONFLAMMABLE GAS, THE EXTINGUISHER ITSELF IS CONSIDERED A HAZARDOUS MATERIAL BY THE U.S. DEPARTMENT OF TRANSPORTATION (USDOT) AND TRANSPORT CANADA (TC). THE PROPER SHIPPING NAME SHALL BE FIRE EXTINGUISHER AND THE UN IDENTIFICATION NUMBER IS UN 1044. THE USDOT HAZARD CLASS IS LIMITED QUANTITY WHEN PRESSURIZED TO LESS THAN 241 PSIG AND WHEN SHIPPED VIA HIGHWAY OR RAIL. USE CLASS 2.2, NON-FLAMMABLE GAS, WHEN SHIPPING VIA AIR.

SECTION XV. REGULATORY INFORMATION



INTERNATIONAL INVENTORY STATUS:

ALL INGREDIENTS ARE ON THE FOLLOWING INVENTORIES

COUNTRY	AGENCY
U.S.A.	TSCA
CANADA	DSL
EUROPE	EINECS/ELINCS
AUSTRALIA	AICS
JAPAN	MITI
SOUTH KOREA	KECL

EUROPEAN RISK AND SAFETY PHRASES:

EU CLASSIFICATION: HARMFUL

R PHRASES:

22: HARMFUL IF SWALLOWED

36/37/38: IRRITATING TO EYES, RESPIRATORY SYSTEM, AND SKIN.

S PHRASES:

26:

IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE

36: WEAR SUITABLE PROTECTIVE CLOTHING

U.S. FEDERAL REGULATORY INFORMATION:

NONE OF THE CHEMICALS IN THIS PRODUCT ARE UNDER SARA REPORTING REQUIREMENTS OR HAVE SARA THRESHOLD PLANNING QUANTITIES OR CERCLA REPORTABLE QUANTITIES, OR ARE REGULATED UNDER TSCA 8(D).

STATE REGULATORY INFORMATION:

CHEMICALS IN THIS PRODUCT ARE COVERED UNDER THE SPECIFIC STATE REGULATIONS NOTED:

ALASKA:

DESIGNATED TOXIC AND HAZARDOUS SUBSTANCES: NONE

CALIFORNIA:

PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS: NONE

FLORIDA:

SUBSTANCE LIST: MICA DUST

ILLINOIS:

TOXIC SUBSTANCE LIST: NONE

KANSAS:

SECTION 302/303 LIST: NONE

MASSACHUSETTS:

SUBSTANCE LIST: MICA DUST

MINNESOTA:

LIST OF HAZARDOUS SUBSTANCES: NONE

MISSOURI:

EMPLOYER INFORMATION/TOXIC SUBSTANCE LIST: NONE

NEW JERSEY:

RIGHT TO KNOW HAZARDOUS SUBSTANCE LIST: NONE

NORTH DAKOTA:

LIST OF HAZARDOUS CHEMICALS, REPORTABLE QUANTITIES: NONE

PENNSYLVANIA:

HAZARDOUS SUBSTANCE LIST: NONE

RHODE ISLAND:

HAZARDOUS SUBSTANCE LIST: MICA DUST

TEXAS:

HAZARDOUS SUBSTANCE LIST: NO

WEST VIRGINIA:

HAZARDOUS SUBSTANCE LIST: NONE

WISCONSIN:

TOXIC AND HAZARDOUS SUBSTANCES: NONE

CALIFORNIA PROPOSITION 65:

NO COMPONENT IS LISTED ON THE CALIFORNIA PROPOSITION 65 LIST

SECTION XVI. OTHER INFORMATION



THIS SAFETY DATA SHEET PREPARED IN ACCORDANCE WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) AND THE GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS)

HMIS RATINGS:

HEALTH

1

FLAMMABILITY

0

REACTIVITY

0

PERSONAL PROTECTIVE EQUIPMENT USE N-95 DUST MASK (SEE SECTION 8)

WHMIS (CANADIAN WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION):

D2B: MAY IRRITATE EYES, MUCOUS MEMBRANES, AND/OR SKIN

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH AS TYPICAL VALUES AND NOT AS PRODUCT SPECIFICATIONS. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE.



SAFETY DATA SHEET

Section 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: ABC Dry Chemical Fire Extinguishant
 Other Identifiers: Multi-purpose Dry Chemical
 Product Code(s): CH555, F13, F11
 Model Code(s) of Extinguishers: 402, IS 18ABC, IS35ABC, IS 45ABC, 13ABC, V25ABC, VH25ABC, V30ABC, VH30ABC, V50ABC, VS50ABC, VS75ABC, V250ABC
 Recommended Use: Fire suppression, not for human or animal drug use.
 Manufacturer: AMEREX CORPORATION
 Internet Address: www.amerex-fire.com
 Address: 7595 Gadsden Highway, P.O. Box 81 Trussville, AL 35173-0081
 Company Telephone: (205) 655-3271
 E-mail Address: info@amerex-fire.com
 Emergency Contacts: Chemtrec 1(800) 424-9300 or (703) 527-3887
 Revised: March 13, 2018

Section 2. HAZARDS IDENTIFICATION

GHS – Classification

Health	Environmental	Physical
Acute Toxicity: Category 5	None	None
Skin Corrosion/Irritation: Category 3	None	None
Skin Sensitization: NO	None	None
Eye: Category 2A	None	Warning
STOT – Category 3	None	Warning
Carcinogen: Category None	None	None

GHS – Label Symbol(s):

If Pressurized: Gas Under Pressure

GHS – Words(s): Warning

Other Hazards Not Resulting in Classification: Mica may contain small quantities of quartz (crystalline silica). Prolonged exposure to respirable crystalline silica dust at concentrations exceeding the occupational exposure limits may increase the risk of developing a disabling

lung disease known as silicosis. IARC found limited evidence for pulmonary carcinogenicity of crystalline silica in humans. In the case of normal use of this product, exposure to silica should be nil.

The attapulgite clay used in this product has a fiber length of less than 5µm; therefore, the clay is not considered to be carcinogenic in animals or humans.

GHS – Hazard Phrases

GHS Hazard	GHS Codes(s)	Code Phrase(s)
Physical	H229	*- Contents under pressure; may explode if heated.
Health	H303 315 319 335	May be harmful if swallowed Causes skin irritation Causes serious eye irritation May cause respiratory irritation
Environmental	None	
Precautionary:		
General	P101	If medical advice is needed, have product container or label at hand
Prevention	P251 261 264 280	Do not pierce or burn, even after use. Avoid breathing dust/fumes/gas/mist/vapours/spray. Wash exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	P312 321 362 302+352 304+340 305+351+338 332+313 342+311 337+313	Call a doctor if you feel unwell. Specific treatment (see Section 4. First Aid Measures) Take off contaminated clothing. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation occurs: Get medical advice/attention. If experiencing respiratory symptoms: Call a doctor. If eye irritation persists get medical advice/attention.
Storage	P410 +403	*- Protect from sunlight. Store in well-ventilated place.
Disposal	P501	Dispose of contents through a licensed disposal company. Contaminated container should be disposed of as unused product.

*- If under pressure

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	EC No.	REACH Reg. No.	CAS-No.	Weight %	Classification
Mono-ammonium phosphate	231-764-5	01-2119488166-29	7722-76-1	80-98	NA
Attapulgite clay	601-805-5	Not Available	12174-11-7	3-16	NA
Mica-potassium aluminum silicate	310-1276	Not Available	12001-26-2	1-2	NA
Silicone oil methyl hydrogen polysiloxane	613-152-3	Not Available	63148-57-2	<1	NA
Calcium carbonate	207-439-9	Not Available	1317-65-3	<1	NA
Amorphous silica precipitated synthetic zeolite	231-545-4	01-2119379499-16-0036	7631-86-9	<1	NA
Yellow 14 pigment – di-azo dye	226-789-3	Not Available	5468-75-7	<1	NA

Emergency overview:

Light yellow, fine solid powder, odorless.

Adverse health effects and symptoms:

Mild irritant to the respiratory system. Irritant to eyes, and skin. Symptoms may include coughing,

shortness of breath, and irritation of the lungs, eyes, and skin. Ingestion, although unlikely, may cause cramps, nausea and diarrhea.

Section 4. FIRST AID MEASURES

Eye Exposure:	May cause irritation. Irrigate eyes with water and repeat until pain free. Seek medical attention if irritation develops, or if vision changes occur.
Skin Exposure:	May cause skin irritation. In case of contact, wash with plenty of soap and water. Seek medical attention if irritation persists.
Inhalation:	May cause irritation, along with coughing. If respiratory irritation or distress occurs remove victim to fresh air. Seek medical attention if irritation persists.
Ingestion:	Overdose symptoms may include numbness or tingling in hands or feet, uneven heart rate, paralysis, feeling faint, chest pain or heavy feeling, pain spreading to the arm or shoulder, nausea, diarrhea, sweating, general ill feeling, or seizure (convulsions). If victim is conscious and alert, give 2-3 glasses of water to drink. If conscious, do not induce vomiting. Seek immediate medical attention. Do not leave victim unattended. To prevent aspiration of swallowed product, lay victim on side with head lower than waist.
Medical conditions possibly aggravated by exposure:	Inhalation of product may aggravate existing chronic respiratory problems such as asthma, emphysema, or bronchitis. Skin contact may aggravate existing skin disease. Chronic overexposure may cause pneumoconiosis ("dusty lung" disease).

Section 5. FIRE-FIGHTING MEASURES

Flammable Properties:	Not flammable
Flash Point:	Not determined
Suitable Extinguishing Media:	Non-combustible. Use extinguishing media suitable for surrounding conditions.
Hazardous Combustion Products:	Carbon oxides

Explosion Data:

Sensitivity to Mechanical Impact:	Not sensitive
Sensitivity to Static Discharge:	Not sensitive
Unusual fire/explosion hazards:	In a fire this material may decompose, releasing oxides of carbon, potassium and nitrogen (see Section 10).
Protective Equipment and Precautions for Firefighters:	As in any fire, wear self-contained breathing apparatus pressure-demand. NIOSH (approved or equivalent) and full protective gear.

Section 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid contact with skin, eyes, and clothing.
Personal Protective Equipment:	Minimum - safety glasses, gloves, and a dust respirator.
Emergency Procedures:	NA
Methods for Containment:	Prevent further leakage or spillage if safe to do so.
Methods for Clean Up:	Avoid dust formation; clean up released material using vacuum or wet sweep and shovel to minimize generation of dust. Bag and transfer to properly labeled containers. Ventilate area and wash spill site after material pickup is complete.
Other:	If product is contaminated, use PPE and containment appropriate to the nature of the most toxic chemical/material in the mixture.

Section 7. HANDLING AND STORAGE

Personal Precautions:	Use appropriate PPE when handling or maintaining equipment, and wash thoroughly after handling (see Section 8).
Conditions for Safe Storage:	Keep product in original container or extinguisher. Contents may be under pressure – inspect for extinguisher rust periodically to ensure container integrity.
Incompatible Products:	Do not mix with other extinguishing agents, particularly potassium bicarbonate and sodium bicarbonate. Incompatible with strong oxidizing agents and strong acids. Do not store in high humidity. Do not combine with chlorine compounds.

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	OSHA PEL	ACGIH TLV	DFG MAK *	EU BLV
Mono-ammonium phosphate	PNOC** Total dust, 15 mg/m ³ Respirable fraction, 5 mg/m ³	PNOC Total dust, 10 mg/m ³ Respirable fraction, 3 mg/m ³	PNOC Total dust, 4 mg/m ³ Respirable fraction, 1.5 mg/m ³	NA
Mica	6 mg/m ³	3 mg/m ³	-----	NA
Attapulgite clay	PNOC** Total dust, 15 mg/m ³ Respirable fraction, 5 mg/m ³	PNOC Total dust, 10 mg/m ³ Respirable fraction, 3 mg/m ³	PNOC Total dust, 4 mg/m ³ Respirable fraction, 1.5 mg/m ³	
Silicone oil	NR**	NR		
Calcium carbonate	PNOC Total dust, 15 mg/m ³ Respirable fraction, 5 mg/m ³	PNOC Total dust, 10 mg/m ³ Respirable fraction, 3 mg/m ³	-----	NA
Amorphous silica	20mppcf 80 mg/m ³ or % SiO ₂	10 mg/m ³	4 mg/m ³	NA
Yellow 14 pigment	NR	NR	NR	NA

*German regulatory limits **PNOC = Particulates not otherwise classified (ACGIH) also known as Particulates not otherwise regulated (OSHA) *** NR = Not Regulated. All values are 8 hour time weighted average concentrations.

Engineering Controls:

Showers
Eyewash stations
Ventilation systems

Personal Protective Equipment – PPE Code E:

The need for respiratory protection is not probable during short-term exposure. During production, the manufacturer should use judgement concerning the need for PPE.



Eye/Face Protection:
Skin and Body Protection:
Respiratory Protection:

Tightly fitting safety goggles
Wear protective gloves/coveralls
If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn. Use P100 respirators for limited exposure. Use air-purifying respirator (APR) with high efficiency particulate air (HEPA) filters for prolonged

exposure. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. The need for respiratory protection is not likely for short-term use in well ventilated areas.

Hygiene Measures:

Good personal hygiene practices essential, such as avoiding food, tobacco products, or other hand-to-mouth contact when handling. Wash thoroughly after handling.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Light yellow powder, finely divided odorless solid
Molecular Weight:	NH ₄ H ₂ PO ₄ : 115.03
Odor:	Odorless
Odor Threshold:	No information available
Decomposition Temperature °C:	100 - 120
Freezing Point °C:	No information available
Initial Boiling Point °C:	No information available
Physical State:	Crystalline Powder
pH:	Approximately 4.4 to 4.9
Flash Point °C:	None
Autoignition Temperature °C:	None
Boiling Point/Range °C:	No information available
Melting Point/Range °C:	NH ₄ H ₂ PO ₄ : 190
Flammability/Explosion Limits in Air °C:	Upper – None; Lower-None
Explosive Properties:	None
Oxidizing Properties:	None
Volatile Component (%vol)	Not applicable
Evaporation Rate:	No information available
Vapor Density:	No information available
Vapor Pressure:	NH ₄ H ₂ PO ₄ : 1.41 mm/Hg
Specific gravity at 25 °C:	NH ₄ H ₂ PO ₄ : 1.80
Solubility:	40.4 g/100 ml
Partition Coefficient:	NH ₄ H ₂ PO ₄ Est: -4.11
Viscosity:	No information available

NOTE: NH₄H₂PO₄ – Monoammonium Phosphate

Section 10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage and handling conditions.
Incompatibles:	Strong oxidizing agents; Strong acids; sodium hypochlorite and chlorine compounds. Protect from moisture
Conditions to Avoid:	Storage or handling near incompatibles.
Hazardous Decomposition Products:	Carbon, nitrogen, and potassium oxides. Heat of fire may release carbon monoxide.
Possibility of Hazardous Reactions:	None
Hazardous Polymerization	Does not occur

Section 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:	Inhalation, skin and eye contact.
Symptoms:	
Inhalation:	Irritation, coughing.
Eyes:	Irritation.
Skin:	Irritation.
Acute Toxicity:	Relatively non-toxic.
Chronic Toxicity:	
Short-term Exposure:	None known.
Long-term Exposure:	As with all dusts, pneumoconiosis, or "dusty lung" disease, may result from chronic exposure.

Acute Toxicity Values - Health

Chemical Name	LD50		LC50 (Inhalation)
	Oral	Dermal	
Mono-ammonium phosphate	5750 mg/kg (rat)	>7940 mg/kg (rabbit)	Not available
Mica	None	None	None
Attapulgite clay	None	None	None
Silicone oil	None	None	None
Calcium carbonate	6450 mg/kg (rat)	500 mg/24 hr (rabbit)	Not available
Amorphous silica	>5000 mg/kg (rat)	>2000 mg/kg (rabbit)	>2.2 mg/L (rat)
Yellow 14 pigment	>17000 mg/kg (rat)	>3000 mg/kg (rat)	>4448 mg/m3 (rat)

Reproductive Toxicity:	This product's ingredients are not known to have reproductive or teratogenic effects.
Target Organs and Effects (TOST):	Respiratory system (mild irritant). This product is a mild irritant to epithelial tissue, (eyes, mucous membranes, skin) and may aggravate dermatitis. No information was found indicating the product causes sensitization.

Other Toxicity Categories

Chemical Name	Germ Cell Mutagenicity	Carcinogenicity	Reproductive	TOST Single Exp	TOST Repeated Exp	Aspiration
Mono-ammonium phosphate	None	None	None	Cat 3	None	None
Attapulgate clay	None	None	None	None	None	None
Mica	None	None	None	None	None	None
Silicone oil	None	None	None	None	None	None
Calcium carbonate	None	None	None	None	None	None
Amorphous silica	None	None	None	None	None	None
Yellow 14 pigment	None	None	None	None	None	None

Section 12. ECOLOGICAL INFORMATION

Ecotoxicity:	Negative effects unknown. Provides nutrient nitrogen and phosphorus to plant life.
Persistence/Degradability:	Degrades rapidly in humid/wet environment.
Probability of rapid biodegradation:	NH ₄ H ₂ PO ₄ Est: 0.693 (Rapid); (NH ₄) ₂ SO ₄ : Est: 0.684 (Rapid)
Anaerobic biodegradation probability:	NH ₄ H ₂ PO ₄ Est: 0.398 (Slow); (NH ₄) ₂ SO ₄ : Est: 0.398 (Slow)
Bioaccumulation potential:	Low.
Bioconcentration factor:	NH ₄ H ₂ PO ₄ : 3.16 L/kg (wet weight) (Low BCF)
Bioaccumulation factor:	NH ₄ H ₂ PO ₄ : 63.04 L/kg (wet weight)
Mobility in soil:	Slow evaporation rate; water soluble, may leach to groundwater
Log Koc:	NH ₄ H ₂ PO ₄ Est: -1.25
Log Koa:	NH ₄ H ₂ PO ₄ Est: 16.72
Log Kaw:	NH ₄ H ₂ PO ₄ Est: -20.86
NOTE: NH ₄ H ₂ PO ₄ – Mono-ammonium Phosphate	

Other Adverse Ecological Effects: No other known effects at this time

Aquatic Toxicity Values – Environment – Research

Chemical Name	Acute (LC50)	Chronic (LC50)
Mono-ammonium phosphate	N/A	N/A
Mica	N/A	N/A
Attapulgate clay	N/A	N/A
Silicone oil	N/A	N/A
Calcium carbonate	N/A	N/A
Amorphous silica	N/A	N/A
Yellow 14 pigment	N/A	N/A

Aquatic Toxicity Values – Environment – Estimates

Chemical Name	Acute (LC50)	EC50
Mono-ammonium phosphate	2,91e+07 mg/L Fish 96 hr; 9.4e+06 mg/l Daphnid 48 hr;	6.70e+05 mg/L Gr. Algae 96 hr
Mica	N/A	N/A
Attapulgite clay	N/A	N/A
Silicone oil	N/A	N/A
Calcium carbonate	N/A	N/A
Amorphous silica	N/A	N/A
Yellow 14 pigment	N/A	N/A

Section 13. DISPOSAL CONSIDERATIONS

Safe Handling	Use appropriate PPE when handling, and wash thoroughly after handling (see Section 8).
Waste Disposal Considerations	Dispose in accordance with federal, state, and local regulations.
Contaminated Packaging	Dispose in accordance with federal, state, and local regulations.

NOTES:

This product is not a RCRA characteristically hazardous or listed hazardous waste. Dispose of according to state or local laws, which may be more restrictive than federal laws or regulations. Used product may be altered or contaminated, creating different disposal considerations.

Section 14. TRANSPORT INFORMATION

UN Number:	NA
UN Proper Shipping Name:	NA
Transport Hazard Class:	NA
Packing Group:	NA
Marine Pollutant?:	NO

IATA Not regulated

DOT Not regulated

NOTES:

This product is not defined as a hazardous material under U.S. Department of Transportation (DOT) 49 CFR 172, or by Transport Canada “Transportation of Dangerous Goods” regulations.

Special Precautions for Shipping:

The transportation information above covers the ABC 555 dry chemical extinguisher agent as shipped in bulk containers and not when contained in fire extinguishers or fire extinguisher systems. If shipped in a stored pressure-type fire extinguisher, and pressurized with a non-flammable, non-toxic

inert expellant gas, the fire extinguisher is considered a hazardous material by the US Department of Transportation and Transport Canada. The proper shipping name shall be FIRE EXTINGUISHER and the UN designation is UN 1044. The DOT hazard class/division is LIMITED QUANTITY when pressurized to less than 241 psig and when shipped via highway or rail. UN Class 2.2. Non-Flammable Gas, when shipping via air. Packing Group – N/A

Section 15. REGULATORY INFORMATION

International Inventory Status: All ingredients are on the following inventories

Country(ies)	Agency	Status
United States of America	TSCA	Yes
Canada	DSL	Yes
Europe	EINECS/ELINCS	Yes
Australia	AICS	Yes
Japan	MITI	Yes
South Korea	KECL	Yes

REACH Title XVII Restrictions: No information available

Chemical Name	Dangerous Substances	Organic Solvents	Harmful Substances Whose Names Are to be Indicated on Label	Pollution Release and Transfer Registry (Class II)	Pollution Release and Transfer Registry (Class I)	Poison and Deleterious Substances Control Law
Monoammonium Phosphate	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Component	ISHA – Harmful Substances Prohibited for Manufacturing, Importing, Transferring, or Supplying	ISHA – Harmful Substances Requiring Permission	Toxic Chemical Classification Listing (TCCL) – Toxic Chemicals	Toxic Release Inventory (TRI) – Group I	Toxic Release Inventory (TRI) – Group II
Monoammonium Phosphate 7722-76-1	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Attapulgitte clay 12174-11-7 (>3)	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Mica-potassium aluminum silicate 120001-26-2 (>2)	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Calcium carbonate 471-34-1	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Amorphous silica 69012-64-2	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Yellow 14 pigment 5468-75-7	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

European Risk and Safety phrases:

EU Classification:	Xn - Irritant	
R Phrases:	20	Harmful by inhalation.
	36/37/38	Irritating to eyes, respiratory system and skin.
S Phrases:	22	Do not breath dust.
	24/25	Avoid contact with skin and eyes
	26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	36	Wear suitable protective clothing.

U.S. Federal Regulatory Information:

SARA 313:

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) - This product does not contain and chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

None of the chemicals in this product are under SARA reporting requirements or have SARA threshold planning quantities (TPQs) or CERCLA reportable quantities (RQs), or are regulated under TSCA 8(d).

SARA 311/312 Hazard Categories:

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
*-Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

* - Only applicable if material is in a pressurized extinguisher.

Clean Water/Clean Air Acts:

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42) or Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61) and Section 112 of the Clean Air Act Amendments of 1990.

U.S. State Regulatory Information:

Chemicals in this product are covered under specific State regulations, as denoted below:

- Alaska** - Designated Toxic and Hazardous Substances: None
- California** – Permissible Exposure Limits for Chemical Contaminants: None
- Florida** – Substance List: Mica Dust
- Illinois** – Toxic Substance List: None
- Kansas** – Section 302/303 List: None
- Massachusetts** – Substance List: Mica Dust

Minnesota – List of Hazardous Substances: None
Missouri – Employer Information/Toxic Substance List: None
New Jersey – Right to Know Hazardous Substance List: None
North Dakota – List of Hazardous Chemicals, Reportable Quantities: None
Pennsylvania – Hazardous Substance List: None
Rhode Island – Hazardous Substance List: Mica Dust
Texas – Hazardous Substance List: No
West Virginia – Hazardous Substance List: None
Wisconsin – Toxic and Hazardous Substances: None

California Proposition 65: No component is listed on the California Proposition 65 list.

Other:

Mexico – Grade	No component listed
Canada – WHMIS Hazard Class	No component listed

Section 16. OTHER INFORMATION

This SDS conforms to requirements under U.S., U.K., Canadian, Australian, and EU regulations or standards, and conforms to the proposed 2003 ANSI Z400.1 format.

Issuing Date	17-June-2012
Revision Date	13-March-2018
Revision Notes	None

The information herein is given in good faith but no warranty, expressed or implied, is made.
 Updated by William F. Garvin, CIH.



Safety Data Sheet

This safety data sheet complies with the requirements of: 2012 OSHA Hazard Communication Standard (29CFR 1910.1200)

Product name ANSUL ABC Multipurpose Dry Chemical Agent - Stored Pressure System

1. Identification

1.1. Product Identifier

Product name ANSUL ABC Multipurpose Dry Chemical Agent - Stored Pressure System

1.2. Other means of identification

Product code 435028
UN/ID no UN1044
Synonyms None
Chemical Family No information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use No information available.
Uses advised against Consumer use.

1.4. Details of the Supplier of the Safety Data Sheet

Company Name Tyco Fire Protection Products
One Stanton Street
Marinette, WI 54143-2542
Telephone: 715-735-7411
Contact point Product Stewardship at 1-715-735-7411
E-mail address psra@tycofp.com

1.5. Emergency Telephone Number

Emergency telephone CHEMTREC 001-800-424-9300 or 001-703-527-3887

2. Hazards Identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Simple asphyxiants
Gases Under Pressure - Compressed Gas

2.2. Label Elements

Signal Word

WARNING

Hazard Statements

May displace oxygen and cause rapid suffocation
Contains gas under pressure; may explode if heated





Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 2 / 9

Precautionary Statements

Storage

Protect from sunlight. Store in a well-ventilated place.

2.3. Hazards Not Otherwise Classified (HNOC)

Not Applicable.

2.4. Other Information

3. Composition/information on Ingredients

3.1. Mixture

The following component(s) in this product are considered hazardous under applicable OSHA(USA)

Chemical name	CAS No.	weight-%
Attapulgate	12174-11-7	1 - 5
Calcium carbonate	471-34-1	1 - 5

4. First aid measures

4.1. Description of first aid measures

General Advice

Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical advice/attention.

Skin contact

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Inhalation

Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.

Ingestion

If swallowed: Call a POISON CENTER or doctor/physician if you feel unwell.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms

None known.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

Note to physicians

Keep victim warm and quiet.

5. Fire-fighting measures

5.1. Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire. Dry chemical or CO2. Water spray, fog or regular foam.



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 3 / 9

5.2. Unsuitable Extinguishing Media

None.

5.3. Specific Hazards Arising from the Chemical

Ruptured cylinders may rocket. Some may burn but none ignite readily.

5.4. Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

5.5. Protective Equipment and Precautions for Firefighters

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions Do not touch or walk through spilled material. Stop leak if you can do it without risk.

OTHER INFORMATION Ventilate the area.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental Precautions

Environmental Precautions Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for Containment If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

Methods for Cleaning Up Use personal protective equipment as required. Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Take up mechanically, placing in appropriate containers for disposal. Avoid creating dust. Clean contaminated surface thoroughly.

7. Handling and Storage

7.1. Precautions for Safe Handling

Advice on safe handling Avoid generation of dust. Do not breathe dust/fume/gas/mist/vapors/spray. Use with local exhaust ventilation. Use personal protective equipment as required. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a well-ventilated place. Keep cool. Keep container tightly closed. Guard against dust accumulation of material. Use care in handling/storage. Pressurized extinguishers



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 4 / 9

should be properly stored and secured to prevent falling or being knocked over.

Incompatible Materials Strong acids.

8. Exposure Controls/Personal Protection

8.1. Control Parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL
Attapulgit 12174-11-7	TWA: 1 mg/m ³ respirable particulate matter	-	-	-
Calcium carbonate 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	-

ACGIH (American Conference of Governmental Industrial Hygienists) OSHA (Occupational Safety and Health Administration of the US Department of Labor): NIOSH IDLH Immediately Dangerous to Life or Health

8.2. Appropriate Engineering Controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

8.3. Individual protection measures, such as personal protective equipment

Eye/Face Protection Avoid contact with eyes. Tight sealing safety goggles.

Skin and Body Protection No special precautions are needed in handling this material.

Respiratory Protection In case of insufficient ventilation, wear suitable respiratory equipment.

Ventilation Use local exhaust or general dilution ventilation to control exposure with applicable limits

8.4. General hygiene considerations

Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical State	powder	Color	Yellow
Odor	odorless		
Odor Threshold	No data available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point/freezing point	No data available	
Boiling point / boiling range	No data available	
Flash Point	No data available	
Evaporation Rate	No data available	
Flammability (solid, gas)	No data available	
Flammability limit in air		
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 5 / 9

Vapor Pressure	No data available
Vapor Density	No data available
Specific gravity	No data available
Water Solubility	No data available
Solubility in Other Solvents	No data available
Partition coefficient	No data available
Autoignition Temperature	No data available
Decomposition Temperature	No data available
Kinematic viscosity	No data available

10. Stability and Reactivity

10.1. Chemical Stability

Stable under recommended storage conditions.

10.2. Reactivity

No data available

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

Hazardous Polymerization	Hazardous polymerization does not occur.
---------------------------------	--

10.4. Conditions to Avoid

None known based on information supplied.

10.5. Incompatible Materials

Strong acids.

10.6. Hazardous decomposition products

Carbon oxides. Nitrogen oxides (NO_x).

11. Toxicological Information

11.1. Information on Likely Routes of Exposure

Product information

Inhalation	May cause irritation of respiratory tract.
Eye Contact	May cause irritation.
Skin contact	May cause irritation.
Ingestion	Ingestion may cause irritation to mucous membranes.

Component Information

Acute Toxicity



Product code 435028

/ Product name ANSUL ABC /
 Multipurpose Dry Chemical Agent -
 Stored Pressure System

PAGE 6 / 9

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Calcium carbonate 471-34-1	= 6450 mg/kg (Rat)	-	-

11.2. Information on Toxicological Effects

Symptoms No information available.

11.3. Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Attapulgite (palygorskite fibers) is a hydrated magnesium aluminum silicate. Long palygorskite (attapulgite) fibers (>5 micrometers) are possibly carcinogenic to humans (Group 2B). Short palygorskite (attapulgite) fibers (<5 micrometers) cannot be classified as to their carcinogenicity to humans (Group 3). The attapulgite present in this product contains fibers 0.5-2.5 um range, so would be considered by IARC as Group 3. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product.

Chemical name	ACGIH	IARC	NTP	OSHA
Attapulgite 12174-11-7	-	Group 3	-	X

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity No information available.
STOT - Single Exposure No information available.
STOT - Repeated Exposure No information available.
Target organ effects Eyes, Respiratory System, Skin.
Aspiration Hazard No information available.

11.4. Numerical Measures of Toxicity - Product information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 8156 mg/kg

12. Ecological Information

12.1. Ecotoxicity

Not classified.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Ammonium sulfate, technical 7783-20-2	-	LC50 96 h 460 - 1000 mg/L Leuciscus idus static; LC50 96 h 123 - 128 mg/L Poecilia reticulata semi-static; LC50 96 h = 126 mg/L Poecilia reticulata; LC50 96 h > 100 mg/L Pimephales promelas; LC50 96 h 32.2 - 41.9 mg/L Oncorhynchus mykiss flow-through; LC50 96 h 5.2 - 8.2 mg/L Oncorhynchus mykiss static; LC50 96 h = 18 mg/L Cyprinus carpio; LC50 96 h = 480 mg/L Brachydanio rerio flow-through; LC50 96 h = 420 mg/L Brachydanio rerio semi-static; LC50 96 h = 250 mg/L Brachydanio rerio	LC50 48 h = 14 mg/L Daphnia magna; EC50 24 h = 423 mg/L Daphnia magna
Silicic Acid/silica gel, Amorphous	EC50 (72h) = 440 mg/L	LC50 (96h) static = 5000 mg/L	EC50 (48h) = 7600 mg/L



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 7 / 9

7631-86-9	Pseudokirchneriella subcapitata	Brachydanio rerio	Ceriodaphnia dubia
-----------	---------------------------------	-------------------	--------------------

12.2. Persistence and Degradability

No information available.

12.3. Bioaccumulation

No information available.

12.4. Other Adverse Effects

No information available

13. Disposal Considerations

13.1. Waste Treatment Methods

Disposal of wastes

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Do not reuse container. Pressurized container: Do not pierce or burn, even after use.

14. Transport Information

DOT

UN/ID no	UN1044
Proper Shipping Name	Fire extinguishers
Description	UN1044, Fire extinguishers, 2.2
Hazard class	2.2
Special Provisions	18, 110
Emergency Response Guide Number	126

TDG

UN/ID no	UN1044
Description	UN1044, Fire extinguishers, 2.2
Proper Shipping Name	Fire extinguishers
Hazard class	2.2

MEX

UN/ID no	UN1044
Description	UN1044, Fire extinguishers, 2.2
Proper Shipping Name	Fire extinguishers
Hazard class	2.2

ICAO (air)

UN/ID no	UN1044
Description	UN1044, Fire extinguishers, 2.2



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 8 / 9

Proper Shipping Name Fire extinguishers
Hazard class 2.2
Special Provisions A19

IATA

UN/ID no UN1044
Description UN1044, Fire extinguishers, 2.2
Proper Shipping Name Fire extinguishers
Hazard class 2.2
ERG Code 2L
Special Provisions A19

IMDG

UN/ID no UN1044
Description UN1044, Fire extinguishers, 2.2
Proper Shipping Name Fire extinguishers
Hazard class 2.2
EmS-No F-C, S-V
Special Provisions 225

15. Regulatory Information

15.1. International Inventories

TSCA Complies
DSL/NDSL Complies
ENCS Does not comply
IECSC Complies
KECL Does not comply
PICCS Complies
AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

15.2. US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Ammonium dihydrogen phosphate - 7722-76-1	1.0
Ammonium sulfate, technical - 7783-20-2	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard No
Chronic health hazard No
Fire Hazard No
Sudden Release of Pressure Hazard Yes
Reactive Hazard No



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 9 / 9

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

15.3. US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Attapulgitite - 12174-11-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Silicic Acid/silica gel, Amorphous 7631-86-9	-	X	X
Magnesium carbonate 546-93-0	X	X	-

16. Other information, including date of preparation of the last revision

NFPA	Health Hazards 0	Flammability 0	Instability 0	Physical and chemical properties -
HMIS	Health Hazards 0	Flammability 0	Physical Hazards 3	Personal Protection X

Revision date 13-Feb-2019

Revision note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet


MATERIAL SAFETY DATA SHEET

Product identifier: FS-ONE High Performance Intumescent Firestop Sealant
Product use: Impedes the passage of fire, smoke and water through fire-rated walls and floors .
Supplier: Hilti (Canada) Corporation, 2360 Meadowpine Blvd., Mississauga, Ontario L5N 6S2
Originator: Hilti, Inc., P. O. Box 21148, Tulsa, Oklahoma, USA 74121
Emergency number: Chem-Trec: 1 800 424 9300

INGREDIENTS INFORMATION

Ingredient	CAS Number	% (wt.)	LC ₅₀ , (rat)	LD ₅₀ (rat)	TLV	STEL
Polyacrylate dispersion	Mixture	30 - 40	N/Av	N/Av	N/Av	N/Av
Calcium carbonate	01317-65-3	15 - 20	N/Av	N/Av	10 mg/m ³	N/Av
Zinc borate	1332-07-6	10 - 15	N/Av	N/Av	N/Av	N/Av
Talc	14807-96-6	05 - 10	N/Av	N/Av	2 mg/m ³	N/Av
Ethylene glycol	00107-21-1	01 - 05	10,876 mg/kg	4,700 mg/kg	100 mg/m ³	N/Av
Ferric oxide	01309-37-1	01 - 05	N/Av	N/Av	5 mg/m ³	N/Av

PHYSICAL PROPERTIES

Appearance / Physical state:	Red paste.	Odour:	Odourless.
Specific gravity (at 20°C):	1.5	VOC Content:	75.0 g/L
Vapour pressure (at 20°C):	23 mbar	Vapour density:	Not applicable.
Evaporation rate:	Not determined.	Boiling point:	Not determined.
Freezing point:	Not determined.	pH:	Not determined.
Coefficient of H2O / oil distrib:	Not determined.	Solubility in water:	Soluble.

FIRE AND EXPLOSION DATA

Flash point / Method:	Nonflammable.	Flammable limits:	Not applicable.
Conditions of flammability:	Not applicable.	Auto-ignition temperature:	Not applicable.
Means of extinction:	As appropriate for surrounding fire (e.g. Water, CO ₂ , Dry Chemical, Foam).		
Special fire fighting procedures:	None known. A NIOSH-approved self-contained breathing apparatus (SCBA) should be worn when fighting fires involving chemicals.		
Hazardous combustion products:	Thermal decomposition products such as oxides of carbon and nitrogen can be produced under fire conditions. See below.		
Sensitivity to mechanical impact / static discharge:	Not susceptible to mechanical impact or to a static discharge.		

REACTIVITY DATA

Stability:	Stable.	Conditions of reactivity:	None known.
Incompatible materials:	Strong acids, peroxides and oxidizing agents.		
Hazardous decomposition products:	None known. Thermal decomposition can yield CO and CO ² .		

TOXICOLOGICAL PROPERTIES

Routes of exposure:	<input checked="" type="checkbox"/> Skin contact <input type="checkbox"/> Skin absorption <input checked="" type="checkbox"/> Eye contact <input type="checkbox"/> Inhalation <input type="checkbox"/> Ingestion		
Acute effects of exposure:	Eyes: Can cause irritation or watering but injury is unlikely. Skin: Prolonged or repeated contact can cause irritation. Inhalation: No effects expected. Ingestion: Not a likely route of exposure. Considered to have a low acute oral toxicity.		
Chronic effects of exposure:	None known.		
Synergistic materials:	None known.		

FIRST AID MEASURES

Eyes:	Flush with plenty of water. Contact a physician if symptoms occur.
Skin:	Wash with soap and water. Seek medical attention if any effects persist.
Inhalation:	No ill effects expected. Should discomfort occur, move to fresh air.
Ingestion:	Do not induce vomiting unless directed by a Physician. Contact a physician immediately.
Other:	Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure

PREVENTATIVE MEASURES

Engineering controls:	General (natural or mechanically induced fresh air movements).
Eye protection:	Safety glasses with side shields are recommended.
Skin protection:	Impermeable gloves recommended.
Respiratory protection:	None normally required.
Other:	No additional measures are normally required.
Handling procedures and equipment:	For industrial use only. Keep out of reach of children. Keep container closed when not in use. Do not get into the eyes. Avoid prolonged or repeated contact with the skin. Practice good hygiene; i.e., wash after using and before eating or smoking.
Storage requirements:	Store in a cool dry area. Keep from freezing. Store between 5° and 25° C.
Spill, leak or release:	Immediately wipe away spilled material before it hardens. Place in a container for proper disposal in accordance with all applicable local, state, or federal requirements.
Waste disposal:	Consult with regulatory agencies or your corporate personnel for disposal methods that comply with local, provincial, and federal safety, health and environmental regulations.
Special shipping instructions:	Avoid temperature extremes. Keep from freezing.

REGULATORY INFORMATION

WHMIS classification:	D2A, D2B
HMIS codes:	Health 1, Flammability 0, Reactivity 0, PPE A
TDG shipping name:	Not regulated.

PREPARATION INFORMATION / CONTACTS

Prepared by:	Hilti, Inc., Tulsa, OK USA	Date of Preparation:	February 19, 2015	Emergency phone number:	1 800 424 9300
Customer Service:	Hilti (Canada) Corporation, Mississauga, Ontario; 1 800 363 4458				
Health / Safety contacts:	Hilti, Inc., Tulsa, OK USA; 1 800 879 6000, Jerry Metcalf (x71003704)				
Abbreviations used:	N/E = None Established. N/A = Not Applicable. N/Av = Not Available. R = as "respirable fraction". IARC : International Agency for Research on Cancer. HMIS : Hazardous Materials Identification System				

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.

MATERIAL SAFETY DATA SHEET

Product name: FS-ONE High Performance Intumescent Firestop Sealant
Description: One-part acrylic-based sealant
Supplier: Hilti, Inc. P.O. Box 21148, Tulsa, OK 74121
Emergency # (Chem-Trec.): 1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)

INGREDIENTS AND EXPOSURE LIMITS

Ingredients:	CAS Number:	PEL:	TLV:	STEL:
Polyacrylate dispersion	Mixture	NE	NE	NE
Calcium carbonate	001317-65-3	5 mg/m ³ (T)	10 mg/m ³ (T)	NE
Zinc borate	138265-88-0	NE	NE	NE
Ammonium polyphosphate	068333-79-9	NE	NE	NE
Talc	014807-96-6	20 mppcf	2 mg/m ³	NE
Expandable graphite	012777-87-6	5 mg/m ³ (T)	2 mg/m ³ (T)	NE
Ethylene glycol	000107-21-1	NE	C:100 mg/m ³ (A)	NE
Polybutene	009003-29-6	NE	NE	NE
Iron oxide	001309-37-1	10 mg/m ³	5 mg/m ³	NE
Glass filament	065997-17-3	NE	5 mg/m ³ (T)	NE
Silicon dioxide	014808-60-7	0.05 mg/m ³ (T)	0.1 mg/m ³ (T)	NE
Water	007732-18-5	NE	NE	NE

Abbreviations: PEL = OSHA Permissible Exposure Limit. TLV = ACGIH Threshold Limit Value. C = Ceiling. STEL = Short Term Exposure Limit. NE = None Established. NA = Not Applicable. (T) indicates "as total dust". (R) indicates "as respirable fraction". (A) indicates "as an aerosol". mppcf = million particles per cubic foot.

PHYSICAL DATA

Appearance:	Red paste.	Odor:	Odorless.
Vapor Density: (air = 1)	Not determined.	Vapor Pressure:	23mbar @ 20C / 68F
Boiling Point:	Not applicable.	VOC Content:	75.0 g/L.
Evaporation Rate:	Not applicable.	Solubility in Water:	Soluble.
Specific Gravity:	1.5	pH:	Not determined.

FIRE AND EXPLOSION HAZARD DATA

Flash Point:	Non-flammable.	Flammable Limits:	Not applicable.
Extinguishing Media:	Not applicable. Use extinguishing media as appropriate for surrounding fire.		
Special Fire Fighting Procedures:	None known. Use a self-contained breathing apparatus when fighting fires involving chemicals.		
Unusual Fire and Explosion Hazards:	None known. Thermal decomposition products can be formed such as oxides of carbon, sulfur and phosphorous.		

REACTIVITY DATA

Stability:	Stable.	Hazardous Polymerization:	Will not occur.
Incompatibility:	Strong acids, peroxides, and oxidizing agents.		
Decomposition Products:	Thermal decomposition can yield CO and CO ₂ .		
Conditions to Avoid:	None known.		

HEALTH HAZARD DATA

Known Hazards:	None known.
Signs and Symptoms of Exposure:	Possibly irritating upon contact with the eyes or upon repeated contact with the skin.
Medical Conditions Aggravated by Exposure:	Eye and skin conditions.
Routes of Exposure:	Dermal.

Carcinogenicity:	IARC classifies crystalline silica (quartz sand) as Group I based upon evidence among workers in industries where there has been long-term and chronic exposure (via inhalation) to silica dust; e.g. mining, quarry, stone crushing, refractory brick and pottery workers. This product does not pose a dust hazard; therefore, this classification is not relevant. Based upon the nature and intended use of this product, it does not pose an increased cancer risk to workers.
EMERGENCY AND FIRST AID PROCEDURES	

Eyes:	Immediately flush with plenty of water. Call a physician if symptoms occur.
Skin:	Immediately wipe off material and wash with soap and water. Material can adhere to the skin. If material has adhered to the skin, use an abrasive containing hand cleaner. If material does not come off, buff with a pumice stone.
Inhalation:	Move victim to fresh air if discomfort develops. Call a physician if symptoms persist.
Ingestion:	Seek medical attention. Do not induce vomiting unless directed by a physician. If a large quantity was ingested, give 1 to 2 glasses of water to dilute. <u>Never</u> give anything by mouth to an unconscious person.
Other:	Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure.

CONTROL MEASURES AND PERSONAL PROTECTIVE EQUIPMENT

Ventilation:	General (natural or mechanically induced fresh air movements).
Eye Protection:	Not required, however, safety glasses should be worn in most industrial settings.
Skin Protection:	Avoid skin contact. Cloth gloves are suitable for hand protection.
Respiratory Protection:	None normally required. Where ventilation is inadequate to control vapors, use a NIOSH-approved respirator with organic vapor cartridges. Never enter a confined space without an appropriate air-supplied respirator.

PRECAUTIONS FOR SAFE HANDLING AND USE

Handling and Storing Precautions:	Store in a cool, dry area preferably between 40° and 77° F. Keep from freezing. Do not store in direct sunlight. Avoid contact with the eyes or skin. Practice good hygiene; i.e. always wash thoroughly after handling and before eating or smoking. For industrial use only. Keep out of reach of children. Follow label/use instructions.
Spill Procedures:	Immediately wipe away spilled material before it hardens. Place in a container for proper disposal in accordance with all applicable local, state, or federal requirements.

REGULATORY INFORMATION

Hazard Communication:	This MSDS has been prepared in accordance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.
HMIS Codes:	Health 1, Flammability 0, Reactivity 0, PPE B
DOT Shipping Name:	Not regulated.
IATA / ICAO Shipping Name:	Not regulated.
TSCA Inventory Status:	Chemical components listed on TSCA inventory.
SARA Title III, Section 313:	This product contains < 3% ethylene glycol (CAS 107-21-1) and < 15% zinc borate (re: zinc compounds) which are subject to reporting under Section 313 of SARA Title III (40 CFR Part 372).
EPA Waste Code(s):	Not regulated by EPA as a hazardous waste.
Waste Disposal Methods:	Consult with regulatory agencies or your corporate personnel for disposal methods that comply with local, state, and federal safety, health and environmental regulations.

CONTACTS

Customer Service:	1 800 879 8000	Technical Service:	1 800 879 8000
Health / Safety:	1 800 879 6000	Jerry Metcalf	(x6704)
Emergency # (Chem-Trec):	1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)		

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.