

Safety Data Sheets

All

All

IPL - Eagle Valley

01/11/2022

Safety Data Sheet Index
Binder: IPL - Eagle Valley - All

Product Name	Manufacturer Name	Part Number	Version Date	Page
2-26 Multi-Purpose Precision Lubricant	CRC Industries, Inc.	02004	04/11/2016	4
587	John Tillman Co.		08/25/2015	13
ABC Dry Chemical Fire Extinguishant	Buckeye Fire Equipment Company		08/05/2019	21
ABC DRY CHEMICAL FIRE EXTINGUISHANT	BUCKEYE FIRE EQUIPMENT COMPANY		04/01/2015	26
ABC Dry Chemical Fire Extinguishant	AMEREX CORPORATION	CH555, F13, F11	03/13/2018	35
AEROKROIL	Kano Laboratories, Inc.		07/01/2020	47
AEROKROIL	Kano Laboratories, Inc.		11/10/2020	53
ANSUL ABC Multipurpose Dry Chemical Agent - Stored Pressure System	Tyco Fire Protection Products		02/13/2019	59
General Purpose Thred Gard	Federal Process Corporation		03/23/2018	68
General Purpose Thred Gard.	Federal Process Corporation	TG04, TG08, TG16	03/23/2018	76
Industrial WORK DAY Enamel Spray Paint Flat White	Krylon Products Group	A04422007	11/27/2019	84
KRYLON Industrial QUIK-MARK Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Orange	Krylon Products Group	A03700004	06/04/2021	102
KRYLON Industrial QUIK-MARK Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Orange	Krylon Products Group	A03700004	06/04/2021	119
KRYLON Industrial QUIK-MARK Water-Based Inverted Marking Paint (Fluorescent), Fluorescent Alert Orange	THE SHERWIN-WILLIAMS COMPANY- KRYLON Products Group		10/13/2020	136
LOCTITE LB 8504 SYNTHETIC PETROLEUM ANTI-SEIZE known as Loctite Graphite-50 Synthet	Henkel Corporation	51084	04/02/2018	152
SCRUBS Hand Cleaner Towels	ITW PRO BRANDS		06/03/2019	158
SCRUBS Hand Cleaner Towels	ITW Pro Brands		06/03/2019	165
SCRUBS In-A-Bucket	ITW Pro Brands	42201, 42210, 42230, 42232, 42256, 42260, 42272, 42274, 4228	03/05/2021	172

Product Name	Manufacturer Name	Part Number	Version Date	Page
WD-40 Aerosol	WD-40 Company		03/05/2019	180



SAFETY DATA SHEET

1. Identification

Product identifier	2-26® Multi-Purpose Precision Lubricant
Other means of identification	
Product code	02004
Recommended use	Multi-purpose lubricant
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufactured or sold by:	
Company name	CRC Industries, Inc.
Address	885 Louis Dr. Warminster, PA 18974 US
Telephone	
General Information	215-674-4300
Technical Assistance	800-521-3168
Customer Service	800-272-4620
24-Hour Emergency (CHEMTREC)	800-424-9300 (US) 703-527-3887 (International)
Website	www.crcindustries.com

2. Hazard(s) identification

Physical hazards	Flammable aerosols Gases under pressure	Category 1 Compressed gas
Health hazards	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Toxic to aquatic life.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid release to the environment.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.
Storage	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated light		64742-47-8	60 - 70
Light mineral oil		8042-47-5	10 - 20
n-Butyl stearate		123-95-5	3 - 5
carbon dioxide		124-38-9	1 - 3
Petrolatum		8009-03-8	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Rinse skin with water/shower. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. Aspiration may cause pulmonary edema and pneumonitis. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
Light mineral oil (CAS 8042-47-5)	PEL	5000 ppm	
Petrolatum (CAS 8009-03-8)	PEL	5 mg/m3	Mist.
		5 mg/m3	Mist.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
Light mineral oil (CAS 8042-47-5)	TWA	5000 ppm	
n-Butyl stearate (CAS 123-95-5)	TWA	5 mg/m3	Inhalable fraction.
Petrolatum (CAS 8009-03-8)	TWA	10 mg/m3	
		5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
Light mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as: Nitrile. Neoprene.
Other	Wear suitable protective clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	Amber.
Odor	Mild petroleum.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-56.2 °F (-49 °C) estimated
Initial boiling point and boiling range	Not available.
Flash point	200 °F (93.3 °C) Tag Closed Cup
Evaporation rate	Slow.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.6 % estimated
Flammability limit - upper (%)	5.5 % estimated
Vapor pressure	1557.7 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.84 estimated
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	392 °F (200 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	88.4 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Product	Species	Test Results
2-26® Multi-Purpose Precision Lubricant		
Acute		
Dermal		
LD50	Rabbit	2475 mg/kg estimated
Inhalation		
LC50	Rat	58740 ppm, 4 hours estimated
Oral		
LD50	Rat	6263 mg/kg estimated

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Light mineral oil (CAS 8042-47-5) 3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.

12. Ecological information

Ecotoxicity Toxic to aquatic life.

Components	Species	Test Results
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)
		2.2 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products	The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not puncture, incinerate or crush. Contents under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
Hazardous waste code	Not regulated.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, LIMITED QUANTITY
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not applicable.

Environmental hazards

Marine pollutant No.
EmS F-D, S-U
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.
This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

Food and Drug Administration (FDA)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes

Hazard categories Delayed Hazard - No

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Petrolatum (CAS 8009-03-8)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

carbon dioxide (CAS 124-38-9)

Light mineral oil (CAS 8042-47-5)

US. New Jersey Worker and Community Right-to-Know Act

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

carbon dioxide (CAS 124-38-9)

US. Pennsylvania Worker and Community Right-to-Know Law

carbon dioxide (CAS 124-38-9)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Light mineral oil (CAS 8042-47-5)

US. Rhode Island RTK

None.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations**EPA****VOC content (40 CFR 51.100(s))** 97.3 %**Consumer products (40 CFR 59, Subpt. C)** Not regulated**State****Consumer products** This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50 states.**VOC content (CA)** 0 %**VOC content (OTC)** 0 %**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-12-2014
Revision date	04-11-2016
Prepared by	Allison Cho
Version #	04
Further information	CRC # 591B-C
HMIS® ratings	Health: 1 Flammability: 3 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 1 Flammability: 3 Instability: 0

NFPA ratings

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.



Safety Data Sheet

587

SDS Revision Date:

08/25/2015

1. Identification

1.1. Product identifier

Product Identity 587

Alternate Names 587

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name John Tillman Company
1300 W. Artesia Blvd.
Compton, CA 90220. USA

Emergency

24 hour Emergency Telephone No. 310-764-0110

Customer Service: 310-764-0110

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Eye Irrit. 2;H319 May cause eye irritation.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Warning

H319 May cause eye irritation.

[Prevention]:

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P337+313 If eye irritation persists: Get medical advice / attention.

[Storage]:



No GHS storage statements

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Fibrous glass CAS Number: 0065997-17-3	100	Eye Irrit. 2;H319	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

- General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** Drink water to clear throat, blow nose to evacuate fibers.
- Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Overview** Exposure with the product may cause skin, eye, and respiratory tract irritation. See section 2 for further details.
- Eyes** May cause eye irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Water, carbon dioxide, or dry chemical.



5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Carbon monoxide, carbon dioxide

5.3. Advice for fire-fighters

Thermal decomposition of fiber coating may produce an Irritating mixture of smoke and fumes. Fire fighters should wear full protective gear including NIOSH approved self-contained breathing apparatus.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Prevent the spread of fiberglass dust & avoid dust generation conditions. Those involved in clean up of particulates should use appropriate personal protective equipment. Vacuum clean dusts. If sweeping is necessary, use a dust suppressant.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Store and use in a manner that will prevent airborne particulates in the workplace.

Incompatible materials: Strong oxidizing agents.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0065997-17-3	Fibrous glass, glass	OSHA	15 mg/m3 (as nuisance dust)5 mg/m3 (respirable fraction)
		ACGIH	10 mg/m3 (as nuisance dust)5 mg/m3 (respirable fraction)
		NIOSH	No Established Limit



		Supplier	No Established Limit
--	--	----------	----------------------

Carcinogen Data

CAS No.	Ingredient	Source	Value
0065997-17-3	Fibrous glass, glass	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

- Respiratory** Where dust level exceeds the TLV, use NIOSH approved respirator to protect against nuisance dusts.
- Eyes** Safety glasses with side shield goggles.
- Skin** Work aprons or smocks are recommended. Wear loose fitting long sleeved clothing. NIOSH approved air supplied or self contained respirator. Protective Gloves and barrier creams if necessary.
- Engineering Controls** Local Exhaust Recommended for processing machinery where dust generation is apparent. Mechanical exhaust is acceptable where local exhaust is not feasible.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Plain Weave Heavy Weight Fiberglass Fabric
Odor	No smell
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	> 1000°F
Initial boiling point and boiling range	Not Measured
Flash Point	250°C (TOC)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapor pressure (Pa)	Not Measured
Vapor Density	Not Measured
Specific Gravity	2.5
Solubility in Water	None
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured



Safety Data Sheet

587

SDS Revision Date:

08/25/2015

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide, carbon dioxide

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Fibrous glass, glass - (65997-17-3)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable



Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Fibrous glass, glass - (65997-17-3)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

In most cases, woven fiberglass scrap can be disposed of in a sanitary landfill in accordance with Federal, State, & local regulations. Check with local authorities any questions concerning disposal.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated



14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user			
No further information			

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.		
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.		
WHMIS Classification	D2B		
US EPA Tier II Hazards	Fire: No	Sudden Release of Pressure: No	Reactive: No
		Immediate (Acute): Yes	Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%) :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Pennsylvania RTK Substances (>1%) :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein.



TILLMAN™
The Brand Pros Demand

Safety Data Sheet

587

SDS Revision Date:

08/25/2015

We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H319 Causes serious eye irritation.

End of Document

SAFETY DATA SHEET

ABC DRY CHEMICAL

SECTION I. Chemical Product and Company Identification

Product Name: ABC Dry Chemical Fire Extinguishant
(Fire Extinguishing Agent, Non-pressurized and Pressurized)
Synonym: Multi-Purpose Dry Chemical
Manufacturer: Buckeye Fire Equipment Company
PO Box 428
Kings Mountain, NC 28086
Telephone: 704.739.7415
Web Address: www.buckeyefire.com
Email Address: bfec@buckeyef.com
Recommended Use: Fire suppression, not for human or animal drug use.
Emergency: CHEMTREC 1.800.424.9300
Revision Date: 08/05//2019

SECTION II. Hazard Identification

Note: This SDS covers both pressurized and non-pressurized containers of the product.

GHS – Classification (Pressurized):

Hazard Classification: Gas Under Pressure-Compressed Gas

GHS Label Elements:



Hazard Symbols:

Signal Word: WARNING

Hazard Statements: Contents Under Pressure: may explode if heated

Precautionary Statements: P251 Pressurized container; do not pierce or burn, even after use.

GHS – Classification (Non-pressurized):

Eye Irritation: Category 2B

Skin Irritation: Category 5

Acute Toxicity-Inhalation: Category 5

GHS Label Elements:



Hazard Symbols:

Signal Word: WARNING

Hazard Statements:

H313 May be harmful in contact with skin.

H320 Causes eye irritation

H333 May be harmful if inhaled.

Precautionary Statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P234 Keep in original container.

P251 Pressurized container; do not pierce or burn, even after use

P261 Avoid breathing dust

P264 Wash hands and face thoroughly after handling

P270 Do not eat, drink, or smoke when using this product

P281 Use personal protective equipment as required

SAFETY DATA SHEET ABC DRY CHEMICAL

P285	In case of inadequate ventilation, wear respiratory protection
P301+322+331	If swallowed, drink 2-3 glasses of water and do not induce vomiting
302+352	If on skin, wash with soap and water
304+313+341	If inhaled, and if distress occurs, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical advice/attention.
305+351+338	If in eyes, rinse cautiously with water for several minutes. Remove contact lenses if present and east to do and continue to rinse.
337+313	If eye irritation persists, get medical advice/attention.
P401+402+403	Store in original container or extinguisher in a dry, well ventilated place.

SECTION III. Composition/Information on Ingredients

This product is a mixture.

Chemical Name	Weight %*	CAS #
Monoammonium phosphate	85	7722-76-1
Barium Sulfate	8	7727-43-7
Mica	< 3	12001-26-2
Amorphous Silica (non-crystalline)	< 3	112926-00-8 (7631-86-9)
Stannous octoate	< .3	301-10-0
Silicone	< .1	63148-57-2
Pigment	< .1	6358-31-2

Note: Pressurized product uses nitrogen as the expellant 7727-37-9

* % is rounded to the nearest appropriate number. Values are not to be considered product specifications

SECTION IV. First Aid Measures

Eye Exposure- Flush eyes with water until pain-free. If irritation develops or persists, seek medical attention.

Skin Exposure- Wash with plenty of soap and water. If irritation develops or persists, seek medical attention.

Inhalation- Move victim to fresh air. If irritation develops or persists, seek medical attention.

Ingestion- If victim is conscious and alert, give 2-3 glasses of water to drink. Do not induce vomiting. If vomiting occurs and the victim is conscious, give additional water to further dilute the chemical. Prevent aspiration of swallowed product by laying victim on side with head lower than their waist. Seek medical attention. Do not leave victim unattended.

Medical Conditions Possibly Aggravated by Exposure- Inhalation of the product may aggravate existing chronic respiratory conditions such as asthma, emphysema, or bronchitis. Contact with the skin may aggravate an existing skin disease. Chronic overexposure may cause pneumoconiosis ("Dusty Lung" disease).

SECTION V. Firefighting Measures

Extinguishing Media: N/A. This product is an extinguishing agent. It is nonflammable and noncombustible.

Special Firefighting Procedures: N/A

Unusual Fire and Explosion Hazards: This product may decompose in fire and release oxides of carbon, potassium, and nitrogen (Refer to Section X).

Sensitivity to Mechanical Impact or Static Discharge: None

SECTION VI. Accidental Release Measures

In case of accidental release, use the appropriate respiratory protection. Clean up the product using a vacuum or wet sweep and shovel to minimize the generation of dust. Bag or drum the product for disposal. If the product is used and/or contaminated, use personal protective equipment and containment means that are appropriate for the composition of the mixture. Product should be prevented from entering waterways.

SAFETY DATA SHEET

ABC DRY CHEMICAL

SECTION VII. Handling and Storage

Avoid eye, respiratory, and skin exposure. Use the appropriate personal protective equipment when handling. Wash thoroughly after handling (Refer to Section VIII). Product should be stored in its original container or extinguisher. When the product is contained under pressure (e.g., an extinguisher), inspect the container for rust or damage that may compromise the container integrity. Do not store the product in high humidity and do not mix with other extinguishing agents, particularly potassium bicarbonate-based agents.

SECTION VIII. Exposure Controls and Personal Protection

Exposure Guidelines:

	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Monoammonium phosphate	Particulates Not Otherwise Classified Total Dust- 15 mg/m ³ Respirable Fraction- 5 mg/m ³	Particulates Not Otherwise Classified Total Dust- 10 mg/m ³ Respirable Fraction- 3 mg/m ³
Barium sulfate	Particulates Not Otherwise Classified Total Dust- 15 mg/m ³ Respirable Fraction- 5 mg/m ³	Particulates Not Otherwise Classified Total Dust- 10 mg/m ³ Respirable Fraction- 3 mg/m ³
Mica	6 mg/m ³	3 mg/m ³
Amorphous Silica	6 mg/m ³	10 mg/m ³
Stannous octoate	.1 mg/m ³	.1 mg/m ³
Silicone	Not Regulated	Not Regulated
Pigment	Not Regulated	Not Regulated

During the use of this product on fires, exhaust gases and products of incomplete combustion are the main respiratory hazards. In the manufacture of this product, employers and employees must use their collective judgment in determining the on-the-job settings where the use of a dust mask or respirator is prudent. The need for respiratory protection is not likely for short-term use in well-ventilated areas.

Respiratory Protection: Use an N-95 dust mask for limited exposures and use air-purifying respirators with high efficiency particulate air filters (HEPA filters) for prolonged exposures.

Eye Protection: Wear chemical goggles or full-face air-purifying respirator.

Skin Protection: Use nitrile, latex, or similar gloves and coveralls. Good personal hygiene practices are essential. After handling the product, avoid food, tobacco products, or other means of transferring the product from hand to mouth until after thoroughly washing.

SECTION IX. Physical and Chemical Properties

Chemical Agent

Appearance and Odor: Light yellow fine powder that is odorless.

Apparent Density: 0.82

Solubility: The product is coated with water repellent silicone. Not immediately soluble in water.

pH: Approximately 4 -5

Flash Point: N/A

Flammability: N/A

Vapor Pressure: N/A

Boiling Point: N/A

Explosive or Oxidizing Properties: None

Expellant- Nitrogen

Appearance and Odor: Colorless and odorless.

Specific Gravity: 0.075 lb./ft³@ 70°F as vapor

Solubility: N/A

pH: N/A

Flash Point: Nonflammable

Flammability: Nonflammable

Vapor Pressure: N/A

Boiling Point: -321°F

Explosive or Oxidizing Properties: None

SAFETY DATA SHEET

ABC DRY CHEMICAL

SECTION X. Stability and Reactivity

Reactivity: Pressurized containers may rupture or explode if exposed to high heat

Stability: Stable

Incompatibles: Magnesium, strong oxidizers such as calcium hypochlorite (pool chlorine), strong alkalis, and isocyanic acids.

Decomposition Products: This product may decompose in fire and release carbon monoxide, carbon dioxide, and sulfur dioxide. Oxides of phosphorous and ammonia have been reported.

Hazardous Polymerization: Will not occur

Hazardous Reactions: None

SECTION XI. Toxicological Information

Acute Toxicity: Monoammonium phosphate LD50 (rat): > 1000mg/kg body weight.

Target organs in humans: respiratory system, eyes, and skin. This product is an irritant to epithelial tissue and may aggravate dermatitis. No indication that the product causes sensitization.

Chronic Toxicity: Pneumoconiosis, or “Dusty Lung” disease, may result from chronic exposure to any dust.

Reproductive Toxicity: This product is not known to have any reproductive effects.

Nitrogen: Simple asphyxiant. Exposure at high concentrations can cause suffocation by reducing the available oxygen.

SECTION XII. Ecological Information

Ecotoxicity: Negative effects are unknown. Provides nutrient nitrogen and phosphorous to plant life.

Degradability: Degrades rapidly in wet or humid environment.

Bioaccumulation: Unknown extent.

Mobility in Soil: Water-soluble. May leech into groundwater.

SECTION XIII. Disposal Consideration

This product is not a RCRA characteristically hazardous or listed hazardous waste. Dispose of according to state or local laws, which may be more restrictive than federal regulations. Be aware that product used on a fire may be altered or contaminated and thereby require different disposal considerations.

SECTION XIV. Transportation Information

This product is not defined as a hazardous material under U.S. Department of Transportation 49 CFR 172, or by Transport Canada “Transportation of Dangerous Goods” regulations.

Please Note: Although this material is not considered hazardous, when contained in a stored pressure fire extinguisher pressurized with a nonflammable gas, the extinguisher itself is considered a hazardous material by the U.S. Department of Transportation (USDOT) and Transport Canada (TC). The proper shipping name shall be Fire Extinguisher and the UN Identification Number is UN 1044. The USDOT hazard class is Limited Quantity when pressurized to less than 241 psig and when shipped via highway or rail. For shipment by Air or Water consult the current IATA or IMDG Regulations respectively.

SAFETY DATA SHEET

ABC DRY CHEMICAL

SECTION XV. Regulatory Information

International Inventory Status: All ingredients are on the following inventories

<u>Country</u>	<u>Agency</u>	<u>Country</u>	<u>Agency</u>
U.S.A.	TSCA	Australia	AICS
Canada	DSL	Japan	MITI
Europe	EINECS/ELINCS	South Korea	KECL

European Risk and Safety Phrases:

EU Classification-		Harmful
R Phrases-	22 36/37/38	Harmful if swallowed Irritating to eyes, respiratory system, and skin.
S Phrases-	26 36	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice Wear suitable protective clothing

U.S. Federal Regulatory Information:

Non-pressurized; None of the chemicals in this product are under SARA reporting requirements or have SARA Threshold Planning Quantities or CERCLA Reportable Quantities or are regulated under TSCA 8(d).
Pressurized: SARA Title III Section 311/312 Categorization is Pressure Hazard

State Regulatory Information:

Chemicals in this product are covered under the specific State regulations noted:

Alaska	Designated Toxic and Hazardous Substances- None		
California	Permissible Exposure Limits for Chemical Contaminants- None		
Florida	Substance list- Mica dust	Pennsylvania	Hazardous Substance List- None
Illinois	Toxic Substance List- No	Rhode Island	Hazardous Substance List- Mica dust
Kansas	Section 302/303 List- None	Texas	Hazardous Substance List- No
Massachusetts	Substance list- Mica dust	West Virginia	Hazardous Substance List- None
Minnesota	List of Hazardous Substances- None	Wisconsin	Toxic and Hazardous Substances- None
Missouri	Employer Information/Toxic Substance List- None		
New Jersey	Right to Know Hazardous Substance List- None		
North Dakota	List of Hazardous Chemicals, Reportable Quantities- None		

California Proposition 65- No component is listed on the California Proposition 65 List

SECTION XVI. Other Information

This Safety Data Sheet prepared in accordance with OSHA's Hazard Communication Standard (29 CFR 1910.1200) and the Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HMIS RATINGS:

Health 1
Flammability 0
Reactivity 0
Personal Protective Equipment: use N-95 dust mask (See Section 8)

WHMIS (Canadian Workplace Hazardous Materials Identification)

D2B- May irritate eyes, mucous membranes, and/or skin

Revised on 7/24/19: Page 1, Section II GHS-classification (Non-pressurized) changed (Class) to (Category) Skin Irritation: Class 3 to Category 5, and Inhalations from Class 5 to Category 5. Revised 8/5/19 (Section II) to add "Acute Toxicity" to Inhalation: Category 5

The information contained herein is given in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made.

Common Name: ABC DRY CHEMICAL FIRE EXTINGUISHANT

Manufacturer: BUCKEYE FIRE EQUIPMENT

SDS Revision Date: 4/1/2015

SDS Format: GHS-US

Grainger Item Number(s): 2LBP1, 31CA37, 35WT05, 35WT06, 35WT07, 35WT08, 35WT09, 35WT10, 35WT11, 35WT41, 35WT42, 35WT43, 35WT44, 3GRW5, 3GRW6, 3GRW7, 3GRW8, 3GRY3, 3GRY4, 3GRY5, 3GRY6, 3GRY7, 3GRY8, 3GRZ4, 44YZ28, 44YZ29, 44YZ30, 44YZ31, 44YZ33, 44YZ35

Manufacturer Model Number(s):

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

[SECTION I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION](#)

[SECTION II. HAZARD IDENTIFICATION](#)

[SECTION III. COMPOSITION/INFORMATION ON INGREDIENTS](#)

[SECTION IV. FIRST AID MEASURES](#)

[SECTION V. FIREFIGHTING MEASURES](#)

[SECTION VI. ACCIDENTAL RELEASE MEASURES](#)

[SECTION VII. HANDLING AND STORAGE](#)

[SECTION VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION](#)

[SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES](#)

[SECTION X. STABILITY AND REACTIVITY](#)

[SECTION XI. TOXICOLOGICAL INFORMATION](#)

[SECTION XII. ECOLOGICAL INFORMATION](#)

[SECTION XIII. DISPOSAL CONSIDERATION](#)

[SECTION XIV. TRANSPORTATION INFORMATION](#)

[SECTION XV. REGULATORY INFORMATION](#)

[SECTION XVI. OTHER INFORMATION](#)

SAFETY DATA SHEET

ABC DRY CHEMICAL

SECTION I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION



PRODUCT NAME: ABC DRY CHEMICAL FIRE EXTINGUISHANT

SYNONYM: MULTI-PURPOSE DRY CHEMICAL

MANUFACTURER:

BUCKEYE FIRE EQUIPMENT COMPANY

110 KINGS ROAD

KINGS MOUNTAIN, NC 28086

TELEPHONE: 704.739.7415

WEB ADDRESS: WWW.BUCKEYEFIRE.COM

EMAIL ADDRESS: BFEC@BUCKEYEF.COM

RECOMMENDED USE: FIRE SUPPRESSION, NOT FOR HUMAN OR ANIMAL DRUG USE.

EMERGENCY:

CHEMTREC: 1.800.424.9300

REVISION DATE: 04/2015

SECTION II. HAZARD IDENTIFICATION



GHS - CLASSIFICATION:

EYE IRRITATION: CLASS 2B

SKIN IRRITATION: CLASS 3

INHALATION: CLASS 5

GHS LABEL ELEMENTS:

HAZARD SYMBOLS: EXCLAMATION MARK

SIGNAL WORD: WARNING

HAZARD STATEMENTS:

H313: MAY BE HARMFUL IN CONTACT WITH SKIN.

H320: CAUSES EYE IRRITATION

H333: MAY BE HARMFUL IF INHALED.

PRECAUTIONARY STATEMENTS:

P101:

IF MEDICAL ADVICE IS NEEDED, HAVE PRODUCT CONTAINER OR LABEL AT HAND.

P102: KEEP OUT OF REACH OF CHILDREN.

P234: KEEP IN ORIGINAL CONTAINER.

P251: PRESSURIZED CONTAINER; DO NOT PIERCE OR BURN, EVEN AFTER USE

P261: AVOID BREATHING DUST

P264: WASH HANDS AND FACE THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK, OR SMOKE WHEN USING THIS PRODUCT

P281: USE PERSONAL PROTECTIVE EQUIPMENT AS REQUIRED

P285: IN CASE OF INADEQUATE VENTILATION, WEAR RESPIRATORY PROTECTION

P301+322+331:

IF SWALLOWED, DRINK 2-3 GLASSES OF WATER AND DO NOT INDUCE VOMITING

302+352: IF ON SKIN, WASH WITH SOAP AND WATER

304+313+341:

IF INHALED, AND IF DISTRESS OCCURS, REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. SEEK MEDICAL ADVICE/ATTENTION.

305+351+338:

IF IN EYES, RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES IF PRESENT AND EASY TO DO, AND CONTINUE TO RINSE.

337+313: IF EYE IRRITATION PERSISTS, GET MEDICAL ADVICE/ATTENTION.

P401+402+403:

STORE IN ORIGINAL CONTAINER OR EXTINGUISHER IN A DRY, WELL VENTILATED PLACE.

SECTION III. COMPOSITION/INFORMATION ON INGREDIENTS



THIS PRODUCT IS A MIXTURE.

CHEMICAL NAME	WEIGHT %*	CAS #
MONOAMMONIUM PHOSPHATE	85	7722-76-1
BARIUM SULFATE	10	7727-43-7
MICA	<3	12001-26-2
SILICA	<2	7631-86-9
STANNOUS OCTOATE	<.3	301-10-0
SILICONE	<.1	63148-57-2
PIGMENT	<.1	6358-31-2

* % IS ROUNDED TO THE NEAREST APPROPRIATE NUMBER. VALUES ARE NOT TO BE CONSIDERED PRODUCT SPECIFICATIONS

SECTION IV. FIRST AID MEASURES



EYE EXPOSURE:

FLUSH EYES WITH WATER UNTIL PAIN-FREE. IF IRRITATION DEVELOPS OR PERSISTS, SEEK MEDICAL ATTENTION.

SKIN EXPOSURE:

WASH WITH PLENTY OF SOAP AND WATER. IF IRRITATION DEVELOPS OR PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION:

MOVE VICTIM TO FRESH AIR. IF IRRITATION DEVELOPS OR PERSISTS, SEEK MEDICAL ATTENTION.

INGESTION:

IF VICTIM IS CONSCIOUS AND ALERT, GIVE 2-3 GLASSES OF WATER TO DRINK. DO NOT INDUCE VOMITING. IF VOMITING OCCURS AND THE VICTIM IS CONSCIOUS, GIVE ADDITIONAL WATER TO FURTHER DILUTE THE CHEMICAL. PREVENT ASPIRATION OF SWALLOWED PRODUCT BY LAYING VICTIM ON SIDE WITH HEAD LOWER THAN THEIR WAIST. SEEK MEDICAL ATTENTION. DO NOT LEAVE VICTIM UNATTENDED.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE:

INHALATION OF THE PRODUCT MAY AGGRAVATE EXISTING CHRONIC RESPIRATORY CONDITIONS SUCH AS ASTHMA, EMPHYSEMA, OR BRONCHITIS. CONTACT WITH THE SKIN MAY AGGRAVATE AN EXISTING SKIN DISEASE. CHRONIC OVEREXPOSURE MAY CAUSE PNEUMOCONIOSIS ("DUSTY LUNG" DISEASE).

SECTION V. FIREFIGHTING MEASURES



EXTINGUISHING MEDIA:

N/A. THIS PRODUCT IS AN EXTINGUISHING AGENT. IT IS NONFLAMMABLE AND NONCOMBUSTIBLE.

SPECIAL FIREFIGHTING PROCEDURES: N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS:

THIS PRODUCT MAY DECOMPOSE IN FIRE AND RELEASE OXIDES OF CARBON, POTASSIUM, AND NITROGEN (REFER TO SECTION X).

SENSITIVITY TO MECHANICAL IMPACT OR STATIC DISCHARGE: NONE

SECTION VI. ACCIDENTAL RELEASE MEASURES



IN CASE OF ACCIDENTAL RELEASE, USE THE APPROPRIATE RESPIRATORY PROTECTION. CLEAN UP THE PRODUCT USING A VACUUM OR WET SWEEP AND SHOVEL TO MINIMIZE THE GENERATION OF DUST. BAG OR DRUM THE PRODUCT FOR DISPOSAL. IF THE PRODUCT IS USED AND/OR CONTAMINATED, USE PERSONAL PROTECTIVE EQUIPMENT AND CONTAINMENT MEANS THAT ARE APPROPRIATE FOR THE COMPOSITION OF THE MIXTURE. PRODUCT SHOULD BE PREVENTED FROM ENTERING WATERWAYS.

SECTION VII. HANDLING AND STORAGE



AVOID EYE, RESPIRATORY, AND SKIN EXPOSURE. USE THE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT WHEN HANDLING. WASH THOROUGHLY AFTER HANDLING (REFER TO SECTION VIII). PRODUCT SHOULD BE STORED IN ITS ORIGINAL CONTAINER OR EXTINGUISHER. WHEN THE PRODUCT IS CONTAINED UNDER PRESSURE (E.G., AN EXTINGUISHER), INSPECT THE CONTAINER FOR RUST OR DAMAGE THAT MAY COMPROMISE THE CONTAINER INTEGRITY. DO NOT STORE THE PRODUCT IN HIGH HUMIDITY AND DO NOT MIX WITH OTHER EXTINGUISHING AGENTS, PARTICULARLY POTASSIUM BICARBONATE BASED AGENTS.

SECTION VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION



EXPOSURE GUIDELINES:

	OSHA PEL	ACGIH TLV
MONOAMONIUM PHOSPHATE	PARTICULATES NOT OTHERWISE CLASSIFIED	PARTICULATES NOT OTHERWISE CLASSIFIED
	TOTAL DUST: 15 MG/M3	TOTAL DUST: 10 MG/M3
	RESPIRABLE FRACTION: 5 MG/M3	RESPIRABLE FRACTION: 3 MG/M3
BARIUM SULFATE	PARTICULATES NOT OTHERWISE CLASSIFIED	PARTICULATES NOT OTHERWISE CLASSIFIED
	TOTAL DUST: 15 MG/M3	TOTAL DUST: 10 MG/M3
	RESPIRABLE FRACTION: 5 MG/M3	RESPIRABLE FRACTION: 3 MG/M3
MICA	6 MG/M3	3 MG/M3

SILICA	6 MG/M3	10 MG/M3
STANNOUS OCTOATE	.1 MG/M3	.1 MG/M3
SILICONE	NOT REGULATED	NOT REGULATED
PIGMENT	NOT REGULATED	NOT REGULATED

DURING THE USE OF THIS PRODUCT ON FIRES, EXHAUST GASES AND PRODUCTS OF INCOMPLETE COMBUSTION ARE THE MAIN RESPIRATORY HAZARDS. IN THE MANUFACTURE OF THIS PRODUCT, EMPLOYERS AND EMPLOYEES MUST USE THEIR COLLECTIVE JUDGMENT IN DETERMINING THE ON-THE-JOB SETTINGS WHERE THE USE OF A DUST MASK OR RESPIRATOR IS PRUDENT. THE NEED FOR RESPIRATORY PROTECTION IS NOT LIKELY FOR SHORT-TERM USE IN WELL-VENTILATED AREAS.

RESPIRATORY PROTECTION:

USE AN N-95 DUST MASK FOR LIMITED EXPOSURES AND USE AIR-PURIFYING RESPIRATORS WITH HIGH EFFICIENCY PARTICULATE AIR FILTERS (HEPA FILTERS) FOR PROLONGED EXPOSURES.

EYE PROTECTION:

WEAR CHEMICAL GOGGLES OR FULL-FACE AIR-PURIFYING RESPIRATOR.

SKIN PROTECTION:

USE NITRILE, LATEX, OR SIMILAR GLOVES AND COVERALLS. GOOD PERSONAL HYGIENE PRACTICES ARE ESSENTIAL. AFTER HANDLING THE PRODUCT, AVOID FOOD, TOBACCO PRODUCTS, OR OTHER MEANS OF TRANSFERRING THE PRODUCT FROM HAND TO MOUTH UNTIL AFTER THOROUGHLY WASHING.

SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES



APPEARANCE AND ODOR: LIGHT YELLOW FINE POWDER THAT IS ODORLESS.

APPARENT DENSITY: 0.82

SOLUBILITY:

THE PRODUCT IS COATED WITH WATER REPELLANT SILICONE. NOT IMMEDIATELY SOLUBLE IN WATER.

PH: APPROXIMATELY 4 -5

FLASH POINT: N/A

FLAMMABILITY: N/A

VAPOR PRESSURE: N/A

BOILING POINT: N/A

EXPLOSIVE OR OXIDIZING PROPERTIES: NONE

SECTION X. STABILITY AND REACTIVITY



STABILITY: STABLE

INCOMPATIBLES:

MAGNESIUM, STRONG OXIDIZERS SUCH AS CALCIUM HYPOCHLORITE (POOL CHLORINE), STRONG ALKALIS, AND ISOCYANURIC ACIDS.

DECOMPOSITION PRODUCTS:

THIS PRODUCT MAY DECOMPOSE IN FIRE AND RELEASE CARBON MONOXIDE, CARBON DIOXIDE, AND SULFUR DIOXIDE. OXIDES OF PHOSPHOROUS AND AMMONIA HAVE BEEN REPORTED.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS REACTIONS: NONE

SECTION XI. TOXICOLOGICAL INFORMATION



ACUTE TOXICITY:

MONOAMMONIUM PHOSPHATE LD50 (RAT): >1000 MG/KG BODY WEIGHT.

TARGET ORGANS IN HUMANS:

RESPIRATORY SYSTEM, EYES, AND SKIN. THIS PRODUCT IS AN IRRITANT TO EPITHELIAL TISSUE AND MAY AGGRAVATE DERMATITIS. NO INDICATION THAT THE PRODUCT CAUSES SENSITIZATION.

CHRONIC TOXICITY:

PNEUMOCONIOSIS, OR "DUSTY LUNG" DISEASE, MAY RESULT FROM CHRONIC EXPOSURE TO ANY DUST.

REPRODUCTIVE TOXICITY:

THIS PRODUCT IS NOT KNOWN TO HAVE ANY REPRODUCTIVE EFFECTS.

SECTION XII. ECOLOGICAL INFORMATION



ECOTOXICITY:

NEGATIVE EFFECTS ARE UNKNOWN. PROVIDES NUTRIENT NITROGEN AND PHOSPHOROUS TO PLANT LIFE.

DEGRADABILITY: DEGRADES RAPIDLY IN WET OR HUMID ENVIRONMENT.

BIOACCUMULATION: UNKNOWN EXTENT.

MOBILITY IN SOIL: WATER-SOLUBLE. MAY LEECH IN TO GROUNDWATER.

SECTION XIII. DISPOSAL CONSIDERATION



THIS PRODUCT IS NOT A RCRA CHARACTERISTICALLY HAZARDOUS OR LISTED HAZARDOUS WASTE. DISPOSE OF ACCORDING TO STATE OR LOCAL LAWS, WHICH MAY BE MORE RESTRICTIVE THAN FEDERAL REGULATIONS. BE AWARE THAT PRODUCT USED ON A FIRE MAY BE ALTERED OR CONTAMINATED AND THEREBY REQUIRE DIFFERENT DISPOSAL CONSIDERATIONS.

SECTION XIV. TRANSPORTATION INFORMATION



THIS PRODUCT IS NOT DEFINED AS A HAZARDOUS MATERIAL UNDER U.S. DEPARTMENT OF TRANSPORTATION 49 CFR 172, OR BY TRANSPORT CANADA "TRANSPORTATION OF DANGEROUS GOODS" REGULATIONS.

PLEASE NOTE:

ALTHOUGH THIS MATERIAL IS NOT CONSIDERED HAZARDOUS, WHEN CONTAINED IN A STORED PRESSURE FIRE EXTINGUISHER PRESSURIZED WITH A NONFLAMMABLE GAS, THE EXTINGUISHER ITSELF IS CONSIDERED A HAZARDOUS MATERIAL BY THE U.S. DEPARTMENT OF TRANSPORTATION (USDOT) AND TRANSPORT CANADA (TC). THE PROPER SHIPPING NAME SHALL BE FIRE EXTINGUISHER AND THE UN IDENTIFICATION NUMBER IS UN 1044. THE USDOT HAZARD CLASS IS LIMITED QUANTITY WHEN PRESSURIZED TO LESS THAN 241 PSIG AND WHEN SHIPPED VIA HIGHWAY OR RAIL. USE CLASS 2.2, NON-FLAMMABLE GAS, WHEN SHIPPING VIA AIR.

SECTION XV. REGULATORY INFORMATION



INTERNATIONAL INVENTORY STATUS:

ALL INGREDIENTS ARE ON THE FOLLOWING INVENTORIES

COUNTRY	AGENCY
U.S.A.	TSCA
CANADA	DSL
EUROPE	EINECS/ELINCS
AUSTRALIA	AICS
JAPAN	MITI
SOUTH KOREA	KECL

EUROPEAN RISK AND SAFETY PHRASES:

EU CLASSIFICATION: HARMFUL

R PHRASES:

22: HARMFUL IF SWALLOWED

36/37/38: IRRITATING TO EYES, RESPIRATORY SYSTEM, AND SKIN.

S PHRASES:

26:

IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE

36: WEAR SUITABLE PROTECTIVE CLOTHING

U.S. FEDERAL REGULATORY INFORMATION:

NONE OF THE CHEMICALS IN THIS PRODUCT ARE UNDER SARA REPORTING REQUIREMENTS OR HAVE SARA THRESHOLD PLANNING QUANTITIES OR CERCLA REPORTABLE QUANTITIES, OR ARE REGULATED UNDER TSCA 8(D).

STATE REGULATORY INFORMATION:

CHEMICALS IN THIS PRODUCT ARE COVERED UNDER THE SPECIFIC STATE REGULATIONS NOTED:

ALASKA:

DESIGNATED TOXIC AND HAZARDOUS SUBSTANCES: NONE

CALIFORNIA:

PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS: NONE

FLORIDA:

SUBSTANCE LIST: MICA DUST

ILLINOIS:

TOXIC SUBSTANCE LIST: NONE

KANSAS:

SECTION 302/303 LIST: NONE

MASSACHUSETTS:

SUBSTANCE LIST: MICA DUST

MINNESOTA:

LIST OF HAZARDOUS SUBSTANCES: NONE

MISSOURI:

EMPLOYER INFORMATION/TOXIC SUBSTANCE LIST: NONE

NEW JERSEY:

RIGHT TO KNOW HAZARDOUS SUBSTANCE LIST: NONE

NORTH DAKOTA:

LIST OF HAZARDOUS CHEMICALS, REPORTABLE QUANTITIES: NONE

PENNSYLVANIA:

HAZARDOUS SUBSTANCE LIST: NONE

RHODE ISLAND:

HAZARDOUS SUBSTANCE LIST: MICA DUST

TEXAS:

HAZARDOUS SUBSTANCE LIST: NO

WEST VIRGINIA:

HAZARDOUS SUBSTANCE LIST: NONE

WISCONSIN:

TOXIC AND HAZARDOUS SUBSTANCES: NONE

CALIFORNIA PROPOSITION 65:

NO COMPONENT IS LISTED ON THE CALIFORNIA PROPOSITION 65 LIST

SECTION XVI. OTHER INFORMATION



THIS SAFETY DATA SHEET PREPARED IN ACCORDANCE WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) AND THE GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS)

HMIS RATINGS:

HEALTH

1

FLAMMABILITY

0

REACTIVITY

0

PERSONAL PROTECTIVE EQUIPMENT USE N-95 DUST MASK (SEE SECTION 8)

WHMIS (CANADIAN WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION):

D2B: MAY IRRITATE EYES, MUCOUS MEMBRANES, AND/OR SKIN

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH AS TYPICAL VALUES AND NOT AS PRODUCT SPECIFICATIONS. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE.



SAFETY DATA SHEET

Section 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: ABC Dry Chemical Fire Extinguishant
 Other Identifiers: Multi-purpose Dry Chemical
 Product Code(s): CH555, F13, F11
 Model Code(s) of Extinguishers: 402, IS 18ABC, IS35ABC, IS 45ABC, 13ABC, V25ABC, VH25ABC, V30ABC, VH30ABC, V50ABC, VS50ABC, VS75ABC, V250ABC
 Recommended Use: Fire suppression, not for human or animal drug use.
 Manufacturer: AMEREX CORPORATION
 Internet Address: www.amerex-fire.com
 Address: 7595 Gadsden Highway, P.O. Box 81 Trussville, AL 35173-0081
 Company Telephone: (205) 655-3271
 E-mail Address: info@amerex-fire.com
 Emergency Contacts: Chemtrec 1(800) 424-9300 or (703) 527-3887
 Revised: March 13, 2018

Section 2. HAZARDS IDENTIFICATION

GHS – Classification

Health	Environmental	Physical
Acute Toxicity: Category 5	None	None
Skin Corrosion/Irritation: Category 3	None	None
Skin Sensitization: NO	None	None
Eye: Category 2A	None	Warning
STOT – Category 3	None	Warning
Carcinogen: Category None	None	None

GHS – Label Symbol(s):

If Pressurized: Gas Under Pressure

GHS – Words(s): Warning

Other Hazards Not Resulting in Classification: Mica may contain small quantities of quartz (crystalline silica). Prolonged exposure to respirable crystalline silica dust at concentrations exceeding the occupational exposure limits may increase the risk of developing a disabling

lung disease known as silicosis. IARC found limited evidence for pulmonary carcinogenicity of crystalline silica in humans. In the case of normal use of this product, exposure to silica should be nil.

The attapulgite clay used in this product has a fiber length of less than 5µm; therefore, the clay is not considered to be carcinogenic in animals or humans.

GHS – Hazard Phrases

GHS Hazard	GHS Codes(s)	Code Phrase(s)
Physical	H229	*- Contents under pressure; may explode if heated.
Health	H303 315 319 335	May be harmful if swallowed Causes skin irritation Causes serious eye irritation May cause respiratory irritation
Environmental	None	
Precautionary:		
General	P101	If medical advice is needed, have product container or label at hand
Prevention	P251 261 264 280	Do not pierce or burn, even after use. Avoid breathing dust/fumes/gas/mist/vapours/spray. Wash exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	P312 321 362 302+352 304+340 305+351+338 332+313 342+311 337+313	Call a doctor if you feel unwell. Specific treatment (see Section 4. First Aid Measures) Take off contaminated clothing. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation occurs: Get medical advice/attention. If experiencing respiratory symptoms: Call a doctor. If eye irritation persists get medical advice/attention.
Storage	P410 +403	*- Protect from sunlight. Store in well-ventilated place.
Disposal	P501	Dispose of contents through a licensed disposal company. Contaminated container should be disposed of as unused product.

*- If under pressure

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	EC No.	REACH Reg. No.	CAS-No.	Weight %	Classification
Mono-ammonium phosphate	231-764-5	01-2119488166-29	7722-76-1	80-98	NA
Attapulgite clay	601-805-5	Not Available	12174-11-7	3-16	NA
Mica-potassium aluminum silicate	310-1276	Not Available	12001-26-2	1-2	NA
Silicone oil methyl hydrogen polysiloxane	613-152-3	Not Available	63148-57-2	<1	NA
Calcium carbonate	207-439-9	Not Available	1317-65-3	<1	NA
Amorphous silica precipitated synthetic zeolite	231-545-4	01-2119379499-16-0036	7631-86-9	<1	NA
Yellow 14 pigment – di-azo dye	226-789-3	Not Available	5468-75-7	<1	NA

Emergency overview:

Light yellow, fine solid powder, odorless.

Adverse health effects and symptoms:

Mild irritant to the respiratory system. Irritant to eyes, and skin. Symptoms may include coughing,

shortness of breath, and irritation of the lungs, eyes, and skin. Ingestion, although unlikely, may cause cramps, nausea and diarrhea.

Section 4. FIRST AID MEASURES

Eye Exposure:	May cause irritation. Irrigate eyes with water and repeat until pain free. Seek medical attention if irritation develops, or if vision changes occur.
Skin Exposure:	May cause skin irritation. In case of contact, wash with plenty of soap and water. Seek medical attention if irritation persists.
Inhalation:	May cause irritation, along with coughing. If respiratory irritation or distress occurs remove victim to fresh air. Seek medical attention if irritation persists.
Ingestion:	Overdose symptoms may include numbness or tingling in hands or feet, uneven heart rate, paralysis, feeling faint, chest pain or heavy feeling, pain spreading to the arm or shoulder, nausea, diarrhea, sweating, general ill feeling, or seizure (convulsions). If victim is conscious and alert, give 2-3 glasses of water to drink. If conscious, do not induce vomiting. Seek immediate medical attention. Do not leave victim unattended. To prevent aspiration of swallowed product, lay victim on side with head lower than waist.
Medical conditions possibly aggravated by exposure:	Inhalation of product may aggravate existing chronic respiratory problems such as asthma, emphysema, or bronchitis. Skin contact may aggravate existing skin disease. Chronic overexposure may cause pneumoconiosis ("dusty lung" disease).

Section 5. FIRE-FIGHTING MEASURES

Flammable Properties:	Not flammable
Flash Point:	Not determined
Suitable Extinguishing Media:	Non-combustible. Use extinguishing media suitable for surrounding conditions.
Hazardous Combustion Products:	Carbon oxides

Explosion Data:

Sensitivity to Mechanical Impact:	Not sensitive
Sensitivity to Static Discharge:	Not sensitive
Unusual fire/explosion hazards:	In a fire this material may decompose, releasing oxides of carbon, potassium and nitrogen (see Section 10).
Protective Equipment and Precautions for Firefighters:	As in any fire, wear self-contained breathing apparatus pressure-demand. NIOSH (approved or equivalent) and full protective gear.

Section 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid contact with skin, eyes, and clothing.
Personal Protective Equipment:	Minimum - safety glasses, gloves, and a dust respirator.
Emergency Procedures:	NA
Methods for Containment:	Prevent further leakage or spillage if safe to do so.
Methods for Clean Up:	Avoid dust formation; clean up released material using vacuum or wet sweep and shovel to minimize generation of dust. Bag and transfer to properly labeled containers. Ventilate area and wash spill site after material pickup is complete.
Other:	If product is contaminated, use PPE and containment appropriate to the nature of the most toxic chemical/material in the mixture.

Section 7. HANDLING AND STORAGE

Personal Precautions:	Use appropriate PPE when handling or maintaining equipment, and wash thoroughly after handling (see Section 8).
Conditions for Safe Storage:	Keep product in original container or extinguisher. Contents may be under pressure – inspect for extinguisher rust periodically to ensure container integrity.
Incompatible Products:	Do not mix with other extinguishing agents, particularly potassium bicarbonate and sodium bicarbonate. Incompatible with strong oxidizing agents and strong acids. Do not store in high humidity. Do not combine with chlorine compounds.

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	OSHA PEL	ACGIH TLV	DFG MAK *	EU BLV
Mono-ammonium phosphate	PNOC** Total dust, 15 mg/m ³ Respirable fraction, 5 mg/m ³	PNOC Total dust, 10 mg/m ³ Respirable fraction, 3 mg/m ³	PNOC Total dust, 4 mg/m ³ Respirable fraction, 1.5 mg/m ³	NA
Mica	6 mg/m ³	3 mg/m ³	-----	NA
Attapulgite clay	PNOC** Total dust, 15 mg/m ³ Respirable fraction, 5 mg/m ³	PNOC Total dust, 10 mg/m ³ Respirable fraction, 3 mg/m ³	PNOC Total dust, 4 mg/m ³ Respirable fraction, 1.5 mg/m ³	
Silicone oil	NR**	NR		
Calcium carbonate	PNOC Total dust, 15 mg/m ³ Respirable fraction, 5 mg/m ³	PNOC Total dust, 10 mg/m ³ Respirable fraction, 3 mg/m ³	-----	NA
Amorphous silica	20mppcf 80 mg/m ³ or % SiO ₂	10 mg/m ³	4 mg/m ³	NA
Yellow 14 pigment	NR	NR	NR	NA

*German regulatory limits **PNOC = Particulates not otherwise classified (ACGIH) also known as Particulates not otherwise regulated (OSHA) *** NR = Not Regulated. All values are 8 hour time weighted average concentrations.

Engineering Controls:

Showers
Eyewash stations
Ventilation systems

Personal Protective Equipment – PPE Code E:

The need for respiratory protection is not probable during short-term exposure. During production, the manufacturer should use judgement concerning the need for PPE.



Eye/Face Protection:
Skin and Body Protection:
Respiratory Protection:

Tightly fitting safety goggles
Wear protective gloves/coveralls
If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn. Use P100 respirators for limited exposure. Use air-purifying respirator (APR) with high efficiency particulate air (HEPA) filters for prolonged

exposure. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. The need for respiratory protection is not likely for short-term use in well ventilated areas.

Hygiene Measures:

Good personal hygiene practices essential, such as avoiding food, tobacco products, or other hand-to-mouth contact when handling. Wash thoroughly after handling.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Light yellow powder, finely divided odorless solid
Molecular Weight:	NH ₄ H ₂ PO ₄ : 115.03
Odor:	Odorless
Odor Threshold:	No information available
Decomposition Temperature °C:	100 - 120
Freezing Point °C:	No information available
Initial Boiling Point °C:	No information available
Physical State:	Crystalline Powder
pH:	Approximately 4.4 to 4.9
Flash Point °C:	None
Autoignition Temperature °C:	None
Boiling Point/Range °C:	No information available
Melting Point/Range °C:	NH ₄ H ₂ PO ₄ : 190
Flammability/Explosion Limits in Air °C:	Upper – None; Lower-None
Explosive Properties:	None
Oxidizing Properties:	None
Volatile Component (%vol)	Not applicable
Evaporation Rate:	No information available
Vapor Density:	No information available
Vapor Pressure:	NH ₄ H ₂ PO ₄ : 1.41 mm/Hg
Specific gravity at 25 °C:	NH ₄ H ₂ PO ₄ : 1.80
Solubility:	40.4 g/100 ml
Partition Coefficient:	NH ₄ H ₂ PO ₄ Est: -4.11
Viscosity:	No information available

NOTE: NH₄H₂PO₄ – Monoammonium Phosphate

Section 10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage and handling conditions.
Incompatibles:	Strong oxidizing agents; Strong acids; sodium hypochlorite and chlorine compounds. Protect from moisture
Conditions to Avoid:	Storage or handling near incompatibles.
Hazardous Decomposition Products:	Carbon, nitrogen, and potassium oxides. Heat of fire may release carbon monoxide.
Possibility of Hazardous Reactions:	None
Hazardous Polymerization	Does not occur

Section 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:	Inhalation, skin and eye contact.
Symptoms:	
Inhalation:	Irritation, coughing.
Eyes:	Irritation.
Skin:	Irritation.
Acute Toxicity:	Relatively non-toxic.
Chronic Toxicity:	
Short-term Exposure:	None known.
Long-term Exposure:	As with all dusts, pneumoconiosis, or "dusty lung" disease, may result from chronic exposure.

Acute Toxicity Values - Health

Chemical Name	LD50		LC50 (Inhalation)
	Oral	Dermal	
Mono-ammonium phosphate	5750 mg/kg (rat)	>7940 mg/kg (rabbit)	Not available
Mica	None	None	None
Attapulgite clay	None	None	None
Silicone oil	None	None	None
Calcium carbonate	6450 mg/kg (rat)	500 mg/24 hr (rabbit)	Not available
Amorphous silica	>5000 mg/kg (rat)	>2000 mg/kg (rabbit)	>2.2 mg/L (rat)
Yellow 14 pigment	>17000 mg/kg (rat)	>3000 mg/kg (rat)	>4448 mg/m3 (rat)

Reproductive Toxicity:	This product's ingredients are not known to have reproductive or teratogenic effects.
Target Organs and Effects (TOST):	Respiratory system (mild irritant). This product is a mild irritant to epithelial tissue, (eyes, mucous membranes, skin) and may aggravate dermatitis. No information was found indicating the product causes sensitization.

Other Toxicity Categories

Chemical Name	Germ Cell Mutagenicity	Carcinogenicity	Reproductive	TOST Single Exp	TOST Repeated Exp	Aspiration
Mono-ammonium phosphate	None	None	None	Cat 3	None	None
Attapulgite clay	None	None	None	None	None	None
Mica	None	None	None	None	None	None
Silicone oil	None	None	None	None	None	None
Calcium carbonate	None	None	None	None	None	None
Amorphous silica	None	None	None	None	None	None
Yellow 14 pigment	None	None	None	None	None	None

Section 12. ECOLOGICAL INFORMATION

Ecotoxicity:	Negative effects unknown. Provides nutrient nitrogen and phosphorus to plant life.
Persistence/Degradability:	Degrades rapidly in humid/wet environment.
Probability of rapid biodegradation:	NH ₄ H ₂ PO ₄ Est: 0.693 (Rapid); (NH ₄) ₂ SO ₄ : Est: 0.684 (Rapid)
Anaerobic biodegradation probability:	NH ₄ H ₂ PO ₄ Est: 0.398 (Slow); (NH ₄) ₂ SO ₄ : Est: 0.398 (Slow)
Bioaccumulation potential:	Low.
Bioconcentration factor:	NH ₄ H ₂ PO ₄ : 3.16 L/kg (wet weight) (Low BCF)
Bioaccumulation factor:	NH ₄ H ₂ PO ₄ : 63.04 L/kg (wet weight)
Mobility in soil:	Slow evaporation rate; water soluble, may leach to groundwater
Log Koc:	NH ₄ H ₂ PO ₄ Est: -1.25
Log Koa:	NH ₄ H ₂ PO ₄ Est: 16.72
Log Kaw:	NH ₄ H ₂ PO ₄ Est: -20.86
NOTE: NH ₄ H ₂ PO ₄ – Mono-ammonium Phosphate	

Other Adverse Ecological Effects: No other known effects at this time

Aquatic Toxicity Values – Environment – Research

Chemical Name	Acute (LC50)	Chronic (LC50)
Mono-ammonium phosphate	N/A	N/A
Mica	N/A	N/A
Attapulgite clay	N/A	N/A
Silicone oil	N/A	N/A
Calcium carbonate	N/A	N/A
Amorphous silica	N/A	N/A
Yellow 14 pigment	N/A	N/A

Aquatic Toxicity Values – Environment – Estimates

Chemical Name	Acute (LC50)	EC50
Mono-ammonium phosphate	2,91e+07 mg/L Fish 96 hr; 9.4e+06 mg/l Daphnid 48 hr;	6.70e+05 mg/L Gr. Algae 96 hr
Mica	N/A	N/A
Attapulgite clay	N/A	N/A
Silicone oil	N/A	N/A
Calcium carbonate	N/A	N/A
Amorphous silica	N/A	N/A
Yellow 14 pigment	N/A	N/A

Section 13. DISPOSAL CONSIDERATIONS

Safe Handling

Use appropriate PPE when handling, and wash thoroughly after handling (see Section 8).

Waste Disposal Considerations

Dispose in accordance with federal, state, and local regulations.

Contaminated Packaging

Dispose in accordance with federal, state, and local regulations.

NOTES:

This product is not a RCRA characteristically hazardous or listed hazardous waste. Dispose of according to state or local laws, which may be more restrictive than federal laws or regulations. Used product may be altered or contaminated, creating different disposal considerations.

Section 14. TRANSPORT INFORMATION

UN Number: NA
 UN Proper Shipping Name: NA
 Transport Hazard Class: NA
 Packing Group: NA
 Marine Pollutant?: NO

IATA Not regulated

DOT Not regulated

NOTES:

This product is not defined as a hazardous material under U.S. Department of Transportation (DOT) 49 CFR 172, or by Transport Canada “Transportation of Dangerous Goods” regulations.

Special Precautions for Shipping:

The transportation information above covers the ABC 555 dry chemical extinguisher agent as shipped in bulk containers and not when contained in fire extinguishers or fire extinguisher systems. If shipped in a stored pressure-type fire extinguisher, and pressurized with a non-flammable, non-toxic

inert expellant gas, the fire extinguisher is considered a hazardous material by the US Department of Transportation and Transport Canada. The proper shipping name shall be FIRE EXTINGUISHER and the UN designation is UN 1044. The DOT hazard class/division is LIMITED QUANTITY when pressurized to less than 241 psig and when shipped via highway or rail. UN Class 2.2. Non-Flammable Gas, when shipping via air. Packing Group – N/A

Section 15. REGULATORY INFORMATION

International Inventory Status: All ingredients are on the following inventories

Country(ies)	Agency	Status
United States of America	TSCA	Yes
Canada	DSL	Yes
Europe	EINECS/ELINCS	Yes
Australia	AICS	Yes
Japan	MITI	Yes
South Korea	KECL	Yes

REACH Title XVII Restrictions: No information available

Chemical Name	Dangerous Substances	Organic Solvents	Harmful Substances Whose Names Are to be Indicated on Label	Pollution Release and Transfer Registry (Class II)	Pollution Release and Transfer Registry (Class I)	Poison and Deleterious Substances Control Law
Monoammonium Phosphate	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Component	ISHA – Harmful Substances Prohibited for Manufacturing, Importing, Transferring, or Supplying	ISHA – Harmful Substances Requiring Permission	Toxic Chemical Classification Listing (TCCL) – Toxic Chemicals	Toxic Release Inventory (TRI) – Group I	Toxic Release Inventory (TRI) – Group II
Monoammonium Phosphate 7722-76-1	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Attapulgitte clay 12174-11-7 (>3)	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Mica-potassium aluminum silicate 120001-26-2 (>2)	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Calcium carbonate 471-34-1	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Amorphous silica 69012-64-2	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Yellow 14 pigment 5468-75-7	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

European Risk and Safety phrases:

EU Classification:	Xn - Irritant	
R Phrases:	20	Harmful by inhalation.
	36/37/38	Irritating to eyes, respiratory system and skin.
S Phrases:	22	Do not breath dust.
	24/25	Avoid contact with skin and eyes
	26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	36	Wear suitable protective clothing.

U.S. Federal Regulatory Information:

SARA 313:

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) - This product does not contain and chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

None of the chemicals in this product are under SARA reporting requirements or have SARA threshold planning quantities (TPQs) or CERCLA reportable quantities (RQs), or are regulated under TSCA 8(d).

SARA 311/312 Hazard Categories:

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
*-Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

* - Only applicable if material is in a pressurized extinguisher.

Clean Water/Clean Air Acts:

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42) or Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61) and Section 112 of the Clean Air Act Amendments of 1990.

U.S. State Regulatory Information:

Chemicals in this product are covered under specific State regulations, as denoted below:

Alaska - Designated Toxic and Hazardous Substances: None

California – Permissible Exposure Limits for Chemical Contaminants: None

Florida – Substance List: Mica Dust

Illinois – Toxic Substance List: None

Kansas – Section 302/303 List: None

Massachusetts – Substance List: Mica Dust

Minnesota – List of Hazardous Substances: None
Missouri – Employer Information/Toxic Substance List: None
New Jersey – Right to Know Hazardous Substance List: None
North Dakota – List of Hazardous Chemicals, Reportable Quantities: None
Pennsylvania – Hazardous Substance List: None
Rhode Island – Hazardous Substance List: Mica Dust
Texas – Hazardous Substance List: No
West Virginia – Hazardous Substance List: None
Wisconsin – Toxic and Hazardous Substances: None

California Proposition 65: No component is listed on the California Proposition 65 list.

Other:

Mexico – Grade	No component listed
Canada – WHMIS Hazard Class	No component listed

Section 16. OTHER INFORMATION

This SDS conforms to requirements under U.S., U.K., Canadian, Australian, and EU regulations or standards, and conforms to the proposed 2003 ANSI Z400.1 format.

Issuing Date	17-June-2012
Revision Date	13-March-2018
Revision Notes	None

The information herein is given in good faith but no warranty, expressed or implied, is made.
 Updated by William F. Garvin, CIH.

11/10/2020

AEROKROIL**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

Product Name:	AEROKROIL
Product Use:	Penetrant/Lubricant for Industrial Use
Manufacturer:	Kano Laboratories, Inc., 1000 E. Thompson Lane Nashville, TN 37211
Emergency Phone Number:	Chemtrec 1 (800) 424-9300
Manufacturer Phone Number:	615-833-4101
Website:	www.kroil.com
SDS Date of Preparation:	November 10, 2020

SECTION 2: HAZARDS IDENTIFICATION

GHS / HAZCOM 2012 Classification:

HEALTH	PHYSICAL
Skin Irritation Category 2 Eye Irritation Category 2A Aspiration Hazard Category 1 Skin Sensitization Category 1	Flammable Aerosol Category 2 Gas Under Pressure: Compressed Gas

Label Elements

DANGER!

Flammable aerosol.

Contains gas under pressure: may explode if heated. Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

Pressurized container. Do not pierce or burn, even after use.

Wash thoroughly after handling.

Contaminated clothing must not be allowed out of the workplace.

Wear protective gloves and eye protection.

IF SWALLOWED: Immediately call a POISON CENTER. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical attention.

In case of fire: Use carbon dioxide, dry chemical or foam to extinguish. Protect from sunlight.

Do not expose to temperatures exceeding 50°C/122°F.

Store locked up.

Dispose of contents and container in accordance with local and national regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS#	%
Severely Hydrotreated Petroleum Distillates	64742-52-5 64742-53-6	30-50
LVP Aliphatic Hydrocarbon	64742-47-8	20-40
Proprietary Additive	Proprietary	5-15
Diisobutyl Ketone	108-83-8	5-15
Aliphatic Alcohol #1	123-42-2	1 - <3
Aliphatic Alcohol #2	78-83-1	1 - <3
Carbon Dioxide Propellant	124-38-9	1-5

The exact percentage has been withheld as a trade secret or is a variation in formula.

SECTION 4: FIRST AID MEASURES

EYE: Rinse thoroughly with water for several holding the eye lids open to be sure the material is washed out. Get medical attention if irritation develops or persists.

SKIN: Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use.

INHALATION: Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention if symptoms develop.

INGESTION: DO NOT induce vomiting. Keep the victim calm and warm. Never give anything by mouth to an unconscious or drowsy person. Get immediate medical attention.

MOST IMPORTANT SYMPTOMS AND EFFECTS, ACUTE AND DELAYED: May cause eye and skin irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects such as headache, dizziness, nausea and vomiting. Harmful or fatal if swallowed. Aspiration into the lungs during ingestion or vomiting may cause lung damage. May cause an allergic skin reaction.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT, IF NEEDED: If swallowed, get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

SUITABLE (AND UNSUITABLE) EXTINGUISHING MEDIA: Use carbon dioxide, dry chemical or foam. Water may be ineffective but can be used to cool containers and structures.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL: Contents under pressure. Keep away from heat and open flames. Container may rupture or explode in the heat of a fire. Prolonged exposure to temperatures above 120oF may cause cans to burst. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

Never use welding or cutting torch on or near containers (even empty) because product can ignite explosively. Combustion products may be hazardous: Oxides of carbon, organic compounds, smoke and fumes.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water. Protect against bursting cans.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: Wear appropriate protective clothing to prevent eye and skin contact including impervious gloves, safety goggles and respirator if needed. Remove all ignition sources such as open flames, spark producing equipment, pilot lights, etc. Ventilate the area with explosion-proof equipment.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Report spills and releases as required to appropriate authorities.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP: Place leaking can in a pail or pan in a well-ventilated area until the pressure has been released. Cover liquid with an inert absorbent material and collect into an appropriate container for disposal.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Wash exposed skin thoroughly with soap and water after use. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Do not cut, braze, solder, grind or weld on or near containers. Contents under pressure. Do not puncture or incinerate container.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Store in a cool, well ventilated area at temperatures below 120°F. Do not store in direct sunlight. Store as a Level 3 aerosol.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CHEMICAL NAME	EXPOSURE LIMITS
Severely Hydrotreated Petroleum Distillates (as mineral oil)	5 mg/m ³ TWA OSHA PEL (as oil mist) 5 mg/m ³ TWA ACGIH TLV (inhalable fraction)
LVP Aliphatic Hydrocarbon	166 ppm TWA Manufacturer Recommended (vapor)
Proprietary Additive	None Established
Diisobutyl Ketone	50 ppm TWA OSHA PEL 25 ppm TWA ACGIH TLV
Aliphatic Alcohol #1	50 ppm OSHA TWA PEL 50 ppm TWA ACGIH TLV
Aliphatic Alcohol #2	100 ppm TWA OSHA PEL 50 ppm TWA ACGIH TLV
Carbon Dioxide Propellant	5000 ppm TWA OSHA PEL 5000 ppm TWA ACGIH TLV 30000 ppm STEL ACGIH TLV

APPROPRIATE ENGINEERING CONTROLS: Use with adequate general or local exhaust ventilation to maintain concentrations below the occupational exposure limits. Use explosion proof electrical equipment and wiring where required.

PERSONAL PROTECTIVE EQUIPMENT:

RESPIRATORY PROTECTION: If the exposure limits listed above are exceeded, a NIOSH approved respirator with organic vapor cartridges may be used. For higher exposures, a supplied air respirator may be required. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

HAND PROTECTION: Impervious gloves are recommended when needed to avoid skin contact.

EYE PROTECTION: Chemical safety goggles recommended.

SKIN PROTECTION: Impervious clothing as required to prevent skin contact and contamination of personal clothing.

HYGIENE MEASURES: Suitable eye wash and washing facilities should be available in the work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Slightly reddish liquid packaged as an aerosol	Odor:	Solvent
Odor Threshold:	Not available	pH:	Not available
Melting/Freezing Point:	Not available	Boiling Point/Range:	Not available
Flash Point:	132°F (55.5°C) TOC	Evaporation Rate:	Not available
Flammability: (Solid, Gas)	Not applicable	Flammability Limits:	10.9% (aliphatic alcohol #2) LEL: 0.7% (petroleum distillates)
Vapor Pressure:	Not available	Vapor Density:	Not available
Relative Density:	0.8596	Solubilities:	Negligible in Water
Partition Coefficient: (N-Octanol/Water)	Not available	Autoignition Temperature:	Not available
Decomposition Temperature:	Not available	Viscosity:	Not available

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: None known.

CHEMICAL STABILITY: Stable under normal conditions of storage or use.

POSSIBILITY OF HAZARDOUS REACTIONS: None known.

CONDITIONS TO AVOID: Avoid heat, sparks, flames and all other sources of ignition.

INCOMPATIBLE MATERIALS: Avoid strong oxidizing agents, reducing agents, acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion will produce oxides of carbon, acetone, acrid fumes and smoke.

SECTION 11: TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS:

EYE: May cause eye irritation with redness, tearing and stinging.

SKIN: May cause irritation with redness, rash, swelling. Prolonged or repeated contact may result in defatting and dermatitis. Repeated skin contact may cause sensitization (allergic skin reaction) in some individuals.

INHALATION: Inhalation of vapors or mists may cause mucous membrane and upper respiratory tract irritation and central nervous system depression. Symptoms may include coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea, fatigue and unconsciousness.

INGESTION: Ingestion is an unlikely route of exposure for aerosol products. Swallowing may cause gastrointestinal irritation with abdominal pain, nausea, vomiting and diarrhea and central nervous system depression with symptoms including headache, dizziness, intoxication, weakness, nausea, and vomiting. Aspiration into the lungs during ingestion or vomiting may cause lung damage.

CHRONIC HAZARDS: Aliphatic Alcohol #1 is suspected of damaging fertility or the unborn child.

CARCINOGEN STATUS: None of the components of this product at greater than 0.1% are listed as carcinogens by OSHA, IARC or NTP.

ACUTE TOXICITY: Toxicological testing has not been performed on this product as a mixture.

LVP Aliphatic Hydrocarbon: Oral rat LD50 > 5000 mg/kg; Dermal rat LD50 > 5000 mg/kg; Inhalation rat LC50 > 2.18 mg/L/4 hr.

Severely Hydrotreated Petroleum Distillates: Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 >5.28 mg/L/4 hr, Dermal rabbit LD50 >2000 mg/kg

Proprietary Additive: Oral rat LD50 3200 mg/kg; Dermal rabbit LD50 5000 mg/kg

Diisobutyl Ketone: Oral rat LD50 5233 mg/kg; Dermal rat LD50 > 2000 mg/kg; Inhalation rat LC50 14.5 mg/L/4 hr.

Aliphatic Alcohol #1: Oral rat LD50 3002 mg/kg; Dermal rat LD50 > 1875 mg/kg; Inhalation rat LC50 > 7.6 mg/L/4 hr.

Aliphatic Alcohol #2: Oral rat LD50 > 2830 mg/kg; Inhalation rat LC50 24.6 mg/L/4 hr; Dermal rabbit LD50 > 2000 mg/kg

Carbon Dioxide: Inhalation rat LC50 167857 ppm/4 hr

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: No toxicity data available for the product.

LVP Aliphatic Hydrocarbon: 96 hr. LC50 Pimephales promelas > 100 mg/L; 48 hr. EC50 daphnia magna > 1000 mg/L; 72 hr.

EC50 Pseudokirchnerella subcapitata > 100 mg/L

Severely Hydrotreated Petroleum Distillates: 96 hr LL50 Oncorhynchus mykiss 2.5 mg/kg, 48 hr EL50 daphnia magna 1.4 mg/L, 72 hr

EL50 Pseudokirchnerella subcapitata 1.3 mg/L

Proprietary Ingredient: 48 hr. LC50 daphnia magna 17-28 mg/L

Diisobutyl Ketone: 96 hr. LC50 Oncorhynchus mykiss 30 mg/L; 48 hr. EC50 daphnia magna 37.2 mg/L, 72 hr.

Aliphatic Alcohol #1: 96 hr. LC50 Oryzias latipes > 100 mg/L; 48 hr. EC50 daphnia magna > 1000 mg/L; 72 hr. EC50 Pseudokirchnerella subcapitata > 1000 mg/L

Aliphatic Alcohol #2: 96 hr LC50 Pimephales promelas 1430 mg/L; 48 hr EC50 daphnia pulex 1100 mg/L; 72 hr EC50 Pseudokirchnerella subcapitata 1799 mg/L

Carbon Dioxide: 96 hr LC50 Oncorhynchus mykiss 35 mg/L

PERSISTENCE AND DEGRADABILITY: Aliphatic Alcohol #1 and Aliphatic Alcohol #2 are readily biodegradable.

BIOACCUMULATIVE POTENTIAL: No data available.

MOBILITY IN SOIL: No data available

OTHER ADVERSE EFFECTS: None known

SECTION 13: DISPOSAL INFORMATION

DISPOSAL INSTRUCTIONS: Dispose of product in accordance with all local, state/provincial and federal regulations.

Do not puncture or incinerate.

CONTAMINATED PACKAGING: Offer empty packaging material to local recycling facilities.

SECTION 14: TRANSPORT INFORMATION

	UN NUMBER	PROPER SHIPPING NAME	HAZARD CLASS	PACKING GROUP	ENVIRONMENTAL HAZARD
DOT / 49 CFR GROUND		Limited Quantity			
DOT AIR	UN1950	Aerosols, Flammable, Limited Quantity	2.1	None	None
IMDG	UN1950	Aerosols, Limited Quantity	2.1	None	None
IATA	UN1950	Aerosols, Flammable, Limited Quantity	2.1	None	None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable - product is transported only in packaged form.

Special precautions: None known.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:


CERCLA 103 Reportable Quantity: This product has a Reportable Quantity (RQ) of 166,666 lbs. (based on the RQ for Aliphatic alcohol #2 of 5,000 lbs present at 3%) maximum. Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations

STATE REPORTING REGULATIONS:

Massachusetts Right To Know: Diacetone Alcohol 123-42-2, Isbutanol 78-83-1, Diisobutyl Ketone 108-83-8, Carbon Dioxide 124-38-9

New Jersey Right To Know: Isbutanol 78-83-1, Diisobutyl Ketone 108-83-8, Carbon Dioxide 124-38-9, Pine Oil 8002-09-3

Pennsylvania Right To Know: Diacetone Alcohol 123-42-2, Isbutanol 78-83-1, Diisobutyl Ketone 108-83-8, Carbon Dioxide 124-38-9

California Proposition 65:  **WARNING:** This product can expose you to chemicals including beta-myrcene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

SARA TITLE III:

Hazard Category for Section 311/312: Refer to Section 2 for the OSHA Hazard Classification

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None.

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

Canadian DSL: All of the components of this product are listed on the Canadian Domestic Substances List

SECTION 16: OTHER INFORMATION

HMIS RATINGS: Health - 2 Flammability - 4 Physical Hazard - 0

NFPA RATINGS: Health - 1 Flammability - 2 Instability - 0

SDS REVISION HISTORY: Updated formulation - Section 15

DATE OF PREPARATION: November 20, 2020

DATE OF LAST REVISION: July 01, 2020

The information contained herein has been developed based upon current available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or the consequences of its use or misuse.

11/10/2020

AEROKROIL

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	AEROKROIL
Product Use:	Penetrant/Lubricant for Industrial Use
Manufacturer:	Kano Laboratories, Inc., 1000 E. Thompson Lane Nashville, TN 37211
Emergency Phone Number:	Chemtrec 1 (800) 424-9300
Manufacturer Phone Number:	615-833-4101
Website:	www.kroil.com
SDS Date of Preparation:	November 10, 2020

SECTION 2: HAZARDS IDENTIFICATION

GHS / HAZCOM 2012 Classification:

HEALTH	PHYSICAL
Skin Irritation Category 2 Eye Irritation Category 2A Aspiration Hazard Category 1 Skin Sensitization Category 1	Flammable Aerosol Category 2 Gas Under Pressure: Compressed Gas

Label Elements

DANGER!

Flammable aerosol.

Contains gas under pressure: may explode if heated. Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

Pressurized container. Do not pierce or burn, even after use.

Wash thoroughly after handling.

Contaminated clothing must not be allowed out of the workplace.

Wear protective gloves and eye protection.

IF SWALLOWED: Immediately call a POISON CENTER. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical attention.

In case of fire: Use carbon dioxide, dry chemical or foam to extinguish. Protect from sunlight.

Do not expose to temperatures exceeding 50°C/122°F.

Store locked up.

Dispose of contents and container in accordance with local and national regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS#	%
Severely Hydrotreated Petroleum Distillates	64742-52-5 64742-53-6	30-50
LVP Aliphatic Hydrocarbon	64742-47-8	20-40
Proprietary Additive	Proprietary	5-15
Diisobutyl Ketone	108-83-8	5-15
Aliphatic Alcohol #1	123-42-2	1 - <3
Aliphatic Alcohol #2	78-83-1	1 - <3
Carbon Dioxide Propellant	124-38-9	1-5

The exact percentage has been withheld as a trade secret or is a variation in formula.

SECTION 4: FIRST AID MEASURES

EYE: Rinse thoroughly with water for several holding the eye lids open to be sure the material is washed out. Get medical attention if irritation develops or persists.

SKIN: Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use.

INHALATION: Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention if symptoms develop.

INGESTION: DO NOT induce vomiting. Keep the victim calm and warm. Never give anything by mouth to an unconscious or drowsy person. Get immediate medical attention.

MOST IMPORTANT SYMPTOMS AND EFFECTS, ACUTE AND DELAYED: May cause eye and skin irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects such as headache, dizziness, nausea and vomiting. Harmful or fatal if swallowed. Aspiration into the lungs during ingestion or vomiting may cause lung damage. May cause an allergic skin reaction.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT, IF NEEDED: If swallowed, get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

SUITABLE (AND UNSUITABLE) EXTINGUISHING MEDIA: Use carbon dioxide, dry chemical or foam. Water may be ineffective but can be used to cool containers and structures.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL: Contents under pressure. Keep away from heat and open flames. Container may rupture or explode in the heat of a fire. Prolonged exposure to temperatures above 120oF may cause cans to burst. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

Never use welding or cutting torch on or near containers (even empty) because product can ignite explosively. Combustion products may be hazardous: Oxides of carbon, organic compounds, smoke and fumes.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water. Protect against bursting cans.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: Wear appropriate protective clothing to prevent eye and skin contact including impervious gloves, safety goggles and respirator if needed. Remove all ignition sources such as open flames, spark producing equipment, pilot lights, etc. Ventilate the area with explosion-proof equipment.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Report spills and releases as required to appropriate authorities.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP: Place leaking can in a pail or pan in a well-ventilated area until the pressure has been released. Cover liquid with an inert absorbent material and collect into an appropriate container for disposal.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Wash exposed skin thoroughly with soap and water after use. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Do not cut, braze, solder, grind or weld on or near containers. Contents under pressure. Do not puncture or incinerate container.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Store in a cool, well ventilated area at temperatures below 120°F. Do not store in direct sunlight. Store as a Level 3 aerosol.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CHEMICAL NAME	EXPOSURE LIMITS
Severely Hydrotreated Petroleum Distillates (as mineral oil)	5 mg/m ³ TWA OSHA PEL (as oil mist) 5 mg/m ³ TWA ACGIH TLV (inhalable fraction)
LVP Aliphatic Hydrocarbon	166 ppm TWA Manufacturer Recommended (vapor)
Proprietary Additive	None Established
Diisobutyl Ketone	50 ppm TWA OSHA PEL 25 ppm TWA ACGIH TLV
Aliphatic Alcohol #1	50 ppm OSHA TWA PEL 50 ppm TWA ACGIH TLV
Aliphatic Alcohol #2	100 ppm TWA OSHA PEL 50 ppm TWA ACGIH TLV
Carbon Dioxide Propellant	5000 ppm TWA OSHA PEL 5000 ppm TWA ACGIH TLV 30000 ppm STEL ACGIH TLV

APPROPRIATE ENGINEERING CONTROLS: Use with adequate general or local exhaust ventilation to maintain concentrations below the occupational exposure limits. Use explosion proof electrical equipment and wiring where required.

PERSONAL PROTECTIVE EQUIPMENT:

RESPIRATORY PROTECTION: If the exposure limits listed above are exceeded, a NIOSH approved respirator with organic vapor cartridges may be used. For higher exposures, a supplied air respirator may be required. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

HAND PROTECTION: Impervious gloves are recommended when needed to avoid skin contact.

EYE PROTECTION: Chemical safety goggles recommended.

SKIN PROTECTION: Impervious clothing as required to prevent skin contact and contamination of personal clothing.

HYGIENE MEASURES: Suitable eye wash and washing facilities should be available in the work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Slightly reddish liquid packaged as an aerosol	Odor:	Solvent
Odor Threshold:	Not available	pH:	Not available
Melting/Freezing Point:	Not available	Boiling Point/Range:	Not available
Flash Point:	132°F (55.5°C) TOC	Evaporation Rate:	Not available
Flammability: (Solid, Gas)	Not applicable	Flammability Limits:	10.9% (aliphatic alcohol #2) LEL: 0.7% (petroleum distillates)
Vapor Pressure:	Not available	Vapor Density:	Not available
Relative Density:	0.8596	Solubilities:	Negligible in Water
Partition Coefficient: (N-Octanol/Water)	Not available	Autoignition Temperature:	Not available
Decomposition Temperature:	Not available	Viscosity:	Not available

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: None known.

CHEMICAL STABILITY: Stable under normal conditions of storage or use.

POSSIBILITY OF HAZARDOUS REACTIONS: None known.

CONDITIONS TO AVOID: Avoid heat, sparks, flames and all other sources of ignition.

INCOMPATIBLE MATERIALS: Avoid strong oxidizing agents, reducing agents, acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion will produce oxides of carbon, acetone, acrid fumes and smoke.

SECTION 11: TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS:

EYE: May cause eye irritation with redness, tearing and stinging.

SKIN: May cause irritation with redness, rash, swelling. Prolonged or repeated contact may result in defatting and dermatitis. Repeated skin contact may cause sensitization (allergic skin reaction) in some individuals.

INHALATION: Inhalation of vapors or mists may cause mucous membrane and upper respiratory tract irritation and central nervous system depression. Symptoms may include coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea, fatigue and unconsciousness.

INGESTION: Ingestion is an unlikely route of exposure for aerosol products. Swallowing may cause gastrointestinal irritation with abdominal pain, nausea, vomiting and diarrhea and central nervous system depression with symptoms including headache, dizziness, intoxication, weakness, nausea, and vomiting. Aspiration into the lungs during ingestion or vomiting may cause lung damage.

CHRONIC HAZARDS: Aliphatic Alcohol #1 is suspected of damaging fertility or the unborn child.

CARCINOGEN STATUS: None of the components of this product at greater than 0.1% are listed as carcinogens by OSHA, IARC or NTP.

ACUTE TOXICITY: Toxicological testing has not been performed on this product as a mixture.

LVP Aliphatic Hydrocarbon: Oral rat LD50 > 5000 mg/kg; Dermal rat LD50 > 5000 mg/kg; Inhalation rat LC50 > 2.18 mg/L/4 hr.

Severely Hydrotreated Petroleum Distillates: Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 >5.28 mg/L/4 hr, Dermal rabbit LD50 >2000 mg/kg

Proprietary Additive: Oral rat LD50 3200 mg/kg; Dermal rabbit LD50 5000 mg/kg

Diisobutyl Ketone: Oral rat LD50 5233 mg/kg; Dermal rat LD50 > 2000 mg/kg; Inhalation rat LC50 14.5 mg/L/4 hr.

Aliphatic Alcohol #1: Oral rat LD50 3002 mg/kg; Dermal rat LD50 > 1875 mg/kg; Inhalation rat LC50 > 7.6 mg/L/4 hr.

Aliphatic Alcohol #2: Oral rat LD50 > 2830 mg/kg; Inhalation rat LC50 24.6 mg/L/4 hr; Dermal rabbit LD50 > 2000 mg/kg

Carbon Dioxide: Inhalation rat LC50 167857 ppm/4 hr

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: No toxicity data available for the product.

LVP Aliphatic Hydrocarbon: 96 hr. LC50 Pimephales promelas > 100 mg/L; 48 hr. EC50 daphnia magna >1000 mg/L; 72 hr.

EC50 Pseudokirchnerella subcapitata > 100 mg/L

Severely Hydrotreated Petroleum Distillates: 96 hr LL50 Oncorhynchus mykiss 2.5 mg/kg, 48 hr EL50 daphnia magna 1.4 mg/L, 72 hr

EL50 Pseudokirchnerella subcapitata 1.3 mg/L

Proprietary Ingredient: 48 hr. LC50 daphnia magna 17-28 mg/L

Diisobutyl Ketone: 96 hr. LC50 Oncorhynchus mykiss 30 mg/L; 48 hr. EC50 daphnia magna 37.2 mg/L, 72 hr.

Aliphatic Alcohol #1: 96 hr. LC50 Oryzias latipes >100 mg/L; 48 hr. EC50 daphnia magna >1000 mg/L; 72 hr. EC50 Pseudokirchnerella subcapitata >1000 mg/L

Aliphatic Alcohol #2: 96 hr LC50 Pimephales promelas 1430 mg/L; 48 hr EC50 daphnia pulex 1100 mg/L; 72 hr EC50 Pseudokirchnerella subcapitata 1799 mg/L

Carbon Dioxide: 96 hr LC50 Oncorhynchus mykiss 35 mg/L

PERSISTENCE AND DEGRADABILITY: Aliphatic Alcohol #1 and Aliphatic Alcohol #2 are readily biodegradable.

BIOACCUMULATIVE POTENTIAL: No data available.

MOBILITY IN SOIL: No data available

OTHER ADVERSE EFFECTS: None known

SECTION 13: DISPOSAL INFORMATION

DISPOSAL INSTRUCTIONS: Dispose of product in accordance with all local, state/provincial and federal regulations.

Do not puncture or incinerate.

CONTAMINATED PACKAGING: Offer empty packaging material to local recycling facilities.

SECTION 14: TRANSPORT INFORMATION

	UN NUMBER	PROPER SHIPPING NAME	HAZARD CLASS	PACKING GROUP	ENVIRONMENTAL HAZARD
DOT / 49 CFR GROUND		Limited Quantity			
DOT AIR	UN1950	Aerosols, Flammable, Limited Quantity	2.1	None	None
IMDG	UN1950	Aerosols, Limited Quantity	2.1	None	None
IATA	UN1950	Aerosols, Flammable, Limited Quantity	2.1	None	None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable - product is transported only in packaged form.

Special precautions: None known.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:


CERCLA 103 Reportable Quantity: This product has a Reportable Quantity (RQ) of 166,666 lbs. (based on the RQ for Aliphatic alcohol #2 of 5,000 lbs present at 3%) maximum. Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations

STATE REPORTING REGULATIONS:

Massachusetts Right To Know: Diacetone Alcohol 123-42-2, Isbutanol 78-83-1, Diisobutyl Ketone 108-83-8, Carbon Dioxide 124-38-9

New Jersey Right To Know: Isbutanol 78-83-1, Diisobutyl Ketone 108-83-8, Carbon Dioxide 124-38-9, Pine Oil 8002-09-3

Pennsylvania Right To Know: Diacetone Alcohol 123-42-2, Isbutanol 78-83-1, Diisobutyl Ketone 108-83-8, Carbon Dioxide 124-38-9

California Proposition 65:  **WARNING:** This product can expose you to chemicals including beta-myrcene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

SARA TITLE III:

Hazard Category for Section 311/312: Refer to Section 2 for the OSHA Hazard Classification

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None.

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

Canadian DSL: All of the components of this product are listed on the Canadian Domestic Substances List

SECTION 16: OTHER INFORMATION

HMIS RATINGS: Health - 2 Flammability - 4 Physical Hazard - 0

NFPA RATINGS: Health - 1 Flammability - 2 Instability - 0

SDS REVISION HISTORY: Updated formulation - Section 15

DATE OF PREPARATION: November 20, 2020

DATE OF LAST REVISION: July 01, 2020

The information contained herein has been developed based upon current available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or the consequences of its use or misuse.



Safety Data Sheet

This safety data sheet complies with the requirements of: 2012 OSHA Hazard Communication Standard (29CFR 1910.1200)

Product name ANSUL ABC Multipurpose Dry Chemical Agent - Stored Pressure System

1. Identification

1.1. Product Identifier

Product name ANSUL ABC Multipurpose Dry Chemical Agent - Stored Pressure System

1.2. Other means of identification

Product code 435028
UN/ID no UN1044
Synonyms None
Chemical Family No information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use No information available.
Uses advised against Consumer use.

1.4. Details of the Supplier of the Safety Data Sheet

Company Name Tyco Fire Protection Products
One Stanton Street
Marinette, WI 54143-2542
Telephone: 715-735-7411
Contact point Product Stewardship at 1-715-735-7411
E-mail address psra@tycofp.com

1.5. Emergency Telephone Number

Emergency telephone CHEMTREC 001-800-424-9300 or 001-703-527-3887

2. Hazards Identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Simple asphyxiants
Gases Under Pressure - Compressed Gas

2.2. Label Elements

Signal Word

WARNING

Hazard Statements

May displace oxygen and cause rapid suffocation
Contains gas under pressure; may explode if heated





Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 2 / 9

Precautionary Statements

Storage

Protect from sunlight. Store in a well-ventilated place.

2.3. Hazards Not Otherwise Classified (HNOC)

Not Applicable.

2.4. Other Information

3. Composition/information on Ingredients

3.1. Mixture

The following component(s) in this product are considered hazardous under applicable OSHA(USA)

Chemical name	CAS No.	weight-%
Attapulgate	12174-11-7	1 - 5
Calcium carbonate	471-34-1	1 - 5

4. First aid measures

4.1. Description of first aid measures

General Advice

Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical advice/attention.

Skin contact

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Inhalation

Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.

Ingestion

If swallowed: Call a POISON CENTER or doctor/physician if you feel unwell.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms

None known.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

Note to physicians

Keep victim warm and quiet.

5. Fire-fighting measures

5.1. Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire. Dry chemical or CO2. Water spray, fog or regular foam.



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 3 / 9

5.2. Unsuitable Extinguishing Media

None.

5.3. Specific Hazards Arising from the Chemical

Ruptured cylinders may rocket. Some may burn but none ignite readily.

5.4. Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

5.5. Protective Equipment and Precautions for Firefighters

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions Do not touch or walk through spilled material. Stop leak if you can do it without risk.

OTHER INFORMATION Ventilate the area.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental Precautions

Environmental Precautions Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for Containment If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

Methods for Cleaning Up Use personal protective equipment as required. Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Take up mechanically, placing in appropriate containers for disposal. Avoid creating dust. Clean contaminated surface thoroughly.

7. Handling and Storage

7.1. Precautions for Safe Handling

Advice on safe handling Avoid generation of dust. Do not breathe dust/fume/gas/mist/vapors/spray. Use with local exhaust ventilation. Use personal protective equipment as required. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a well-ventilated place. Keep cool. Keep container tightly closed. Guard against dust accumulation of material. Use care in handling/storage. Pressurized extinguishers



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 4 / 9

should be properly stored and secured to prevent falling or being knocked over.

Incompatible Materials Strong acids.

8. Exposure Controls/Personal Protection

8.1. Control Parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL
Attapulgit 12174-11-7	TWA: 1 mg/m ³ respirable particulate matter	-	-	-
Calcium carbonate 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	-

ACGIH (American Conference of Governmental Industrial Hygienists) OSHA (Occupational Safety and Health Administration of the US Department of Labor): NIOSH IDLH Immediately Dangerous to Life or Health

8.2. Appropriate Engineering Controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

8.3. Individual protection measures, such as personal protective equipment

Eye/Face Protection Avoid contact with eyes. Tight sealing safety goggles.

Skin and Body Protection No special precautions are needed in handling this material.

Respiratory Protection In case of insufficient ventilation, wear suitable respiratory equipment.

Ventilation Use local exhaust or general dilution ventilation to control exposure with applicable limits

8.4. General hygiene considerations

Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical State	powder	Color	Yellow
Odor	odorless		
Odor Threshold	No data available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point/freezing point	No data available	
Boiling point / boiling range	No data available	
Flash Point	No data available	
Evaporation Rate	No data available	
Flammability (solid, gas)	No data available	
Flammability limit in air		
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 5 / 9

Vapor Pressure	No data available
Vapor Density	No data available
Specific gravity	No data available
Water Solubility	No data available
Solubility in Other Solvents	No data available
Partition coefficient	No data available
Autoignition Temperature	No data available
Decomposition Temperature	No data available
Kinematic viscosity	No data available

10. Stability and Reactivity

10.1. Chemical Stability

Stable under recommended storage conditions.

10.2. Reactivity

No data available

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

Hazardous Polymerization Hazardous polymerization does not occur.

10.4. Conditions to Avoid

None known based on information supplied.

10.5. Incompatible Materials

Strong acids.

10.6. Hazardous decomposition products

Carbon oxides. Nitrogen oxides (NO_x).

11. Toxicological Information

11.1. Information on Likely Routes of Exposure

Product information

Inhalation	May cause irritation of respiratory tract.
Eye Contact	May cause irritation.
Skin contact	May cause irritation.
Ingestion	Ingestion may cause irritation to mucous membranes.

Component Information

Acute Toxicity



Product code 435028

/ Product name ANSUL ABC /
 Multipurpose Dry Chemical Agent -
 Stored Pressure System

PAGE 6 / 9

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Calcium carbonate 471-34-1	= 6450 mg/kg (Rat)	-	-

11.2. Information on Toxicological Effects

Symptoms No information available.

11.3. Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Attapulgite (palygorskite fibers) is a hydrated magnesium aluminum silicate. Long palygorskite (attapulgite) fibers (>5 micrometers) are possibly carcinogenic to humans (Group 2B). Short palygorskite (attapulgite) fibers (<5 micrometers) cannot be classified as to their carcinogenicity to humans (Group 3). The attapulgite present in this product contains fibers 0.5-2.5 um range, so would be considered by IARC as Group 3. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product.

Chemical name	ACGIH	IARC	NTP	OSHA
Attapulgite 12174-11-7	-	Group 3	-	X

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity No information available.
STOT - Single Exposure No information available.
STOT - Repeated Exposure No information available.
Target organ effects Eyes, Respiratory System, Skin.
Aspiration Hazard No information available.

11.4. Numerical Measures of Toxicity - Product information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 8156 mg/kg

12. Ecological Information

12.1. Ecotoxicity

Not classified.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Ammonium sulfate, technical 7783-20-2	-	LC50 96 h 460 - 1000 mg/L Leuciscus idus static; LC50 96 h 123 - 128 mg/L Poecilia reticulata semi-static; LC50 96 h = 126 mg/L Poecilia reticulata; LC50 96 h > 100 mg/L Pimephales promelas; LC50 96 h 32.2 - 41.9 mg/L Oncorhynchus mykiss flow-through; LC50 96 h 5.2 - 8.2 mg/L Oncorhynchus mykiss static; LC50 96 h = 18 mg/L Cyprinus carpio; LC50 96 h = 480 mg/L Brachydanio rerio flow-through; LC50 96 h = 420 mg/L Brachydanio rerio semi-static; LC50 96 h = 250 mg/L Brachydanio rerio	LC50 48 h = 14 mg/L Daphnia magna; EC50 24 h = 423 mg/L Daphnia magna
Silicic Acid/silica gel, Amorphous	EC50 (72h) = 440 mg/L	LC50 (96h) static = 5000 mg/L	EC50 (48h) = 7600 mg/L



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 7 / 9

7631-86-9	Pseudokirchneriella subcapitata	Brachydanio rerio	Ceriodaphnia dubia
-----------	---------------------------------	-------------------	--------------------

12.2. Persistence and Degradability

No information available.

12.3. Bioaccumulation

No information available.

12.4. Other Adverse Effects

No information available

13. Disposal Considerations

13.1. Waste Treatment Methods

Disposal of wastes

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Do not reuse container. Pressurized container: Do not pierce or burn, even after use.

14. Transport Information

DOT

UN/ID no	UN1044
Proper Shipping Name	Fire extinguishers
Description	UN1044, Fire extinguishers, 2.2
Hazard class	2.2
Special Provisions	18, 110
Emergency Response Guide Number	126

TDG

UN/ID no	UN1044
Description	UN1044, Fire extinguishers, 2.2
Proper Shipping Name	Fire extinguishers
Hazard class	2.2

MEX

UN/ID no	UN1044
Description	UN1044, Fire extinguishers, 2.2
Proper Shipping Name	Fire extinguishers
Hazard class	2.2

ICAO (air)

UN/ID no	UN1044
Description	UN1044, Fire extinguishers, 2.2



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 8 / 9

Proper Shipping Name Fire extinguishers
Hazard class 2.2
Special Provisions A19

IATA

UN/ID no UN1044
Description UN1044, Fire extinguishers, 2.2
Proper Shipping Name Fire extinguishers
Hazard class 2.2
ERG Code 2L
Special Provisions A19

IMDG

UN/ID no UN1044
Description UN1044, Fire extinguishers, 2.2
Proper Shipping Name Fire extinguishers
Hazard class 2.2
EmS-No F-C, S-V
Special Provisions 225

15. Regulatory Information

15.1. International Inventories

TSCA Complies
DSL/NDSL Complies
ENCS Does not comply
IECSC Complies
KECL Does not comply
PICCS Complies
AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

15.2. US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Ammonium dihydrogen phosphate - 7722-76-1	1.0
Ammonium sulfate, technical - 7783-20-2	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard No
Chronic health hazard No
Fire Hazard No
Sudden Release of Pressure Hazard Yes
Reactive Hazard No



Product code 435028

/ Product name ANSUL ABC /
Multipurpose Dry Chemical Agent -
Stored Pressure System

PAGE 9 / 9

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

15.3. US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Attapulgite - 12174-11-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Silicic Acid/silica gel, Amorphous 7631-86-9	-	X	X
Magnesium carbonate 546-93-0	X	X	-

16. Other information, including date of preparation of the last revision

NFPA	Health Hazards 0	Flammability 0	Instability 0	Physical and chemical properties -
HMIS	Health Hazards 0	Flammability 0	Physical Hazards 3	Personal Protection X

Revision date 13-Feb-2019

Revision note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

SAFETY DATA SHEET

Section 1. IDENTIFICATION

Product Identifier

Product Name General Purpose Thred Gard.

Other means of Identification

Product Code TG04, TG08, TG16.

Recommended Use Anti Seize Compound.

Recommended Restrictions None Known.

Manufacturer

Company Name Federal Process Corporation

Address 4520 Richmond Road

Cleveland OH 44128

Telephone 1-800-846-7325

Emergency Telephone Number: Call Chemtrec at 1-800-424-9300

Section 2. HAZARDS IDENTIFICATION

PHYSICAL STATE: Grease Like

Classification:

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

Signal Word:

Warning



Hazard Statements:

H319 – Causes serious eye irritation.

H317 – May cause an allergic skin reaction

Precautionary Statements:

Prevention: Not expected to be present a hazard during normal use.

Response: P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313–If eye irritation persists: Get medical advice/attention.
 P332 + P313 – If skin irritation or rash occurs: Get medical advice/attention.

Disposal: P501 - Dispose of contents/container to an approved waste disposal plant.

Other Hazards: Toxic to aquatic life with long lasting effects.

Unknown Acute Toxicity: 2% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight %
Petroleum oil	64741-96-4	60-80
Red iron oxide	1309-37-1	5-10

Section 4. FIRST AID MEASURES

First Aid Measures:

Eye Contact Rinse thoroughly with plenty of water, for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

Skin Contact If skin irritation occurs, rinse affected area with water. If skin irritation or rash occurs: Get medical advice/attention.

Inhalation Remove to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.

Ingestion Do NOT induce vomiting Get medical attention immediately. Rinse mouth with water. Never give anything by mouth to an unconscious individual.

Most Important Symptoms and effects:

Symptoms Direct contact with eyes may cause temporary irritation.
Do NOT ingest.

Section 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Use foam, dry chemical, carbon dioxide or water fog.

Unsuitable Extinguishing Media: Avoid solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the Chemical:

Carbon oxides expected to be the primary hazardous combustion product.

Protective Equipment and Precautions for Firefighters:

As in any fire, wear self-contained breathing apparatus and other protective clothing (approved or equivalent) and full protective gear.

Section 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Personal Precautions: Use personal protective equipment as required. Keep unnecessary personnel away.

Methods and Material for Containment and Cleaning Up:

Methods for Containment: Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up: Keep in suitable, closed containers for disposal.

Section 7. HANDLING AND STORAGE

Precautions for Safe Handling:

Advice on Safe Handling: Avoid breathing vapors or mists. Contaminated work-clothing should not be allowed out of the workplace.

Conditions for Safe Storage, including

Any Incompatibilities:

Storage Conditions: Keep containers tightly closed in a dry, cool and well-ventilated place.
Do not store near heat, sparks, or open flames.
KEEP OUT OF REACH OF CHILDREN.

Incompatible Materials: None known based on information supplied.

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines:

Chemical Name	ACGIH TWA	ACGIH STEL	OSHA TWA
Petroleum oil (CAS 64741-96-4)	5 mg/m ³	N/A	5 mg/m ³
Red iron oxide (CAS 1309-37-1)	NO DATA	NO DATA	NO DATA

Appropriate Engineering Controls:

Engineering Controls: Apply technical measures to comply with the occupational exposure limits.

Individual Protection Measures, such as
Personal Protective Equipment:

Eye/Face Protection: Avoid contact with eyes.

Skin and Body Protection: No protective equipment is needed under normal use conditions.

Respiratory Protection: Ensure adequate ventilation, especially in confined areas. If confined in poorly ventilated areas use NIOSH/MSHA

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice. Wash exposed areas thoroughly before eating, drinking, smoking or leaving work area. Launder contaminated clothing before reusing.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State:	Grease like.	Odor:	Mild.
Appearance:	Viscous.	Odor Threshold:	Not available.
Color:	Red		

<u>Property</u>	<u>Values</u>
pH	N/A

Melting Point/Freezing Point	Not determined.
Boiling Point/Boiling Range	Not determined.
Flash Point	>430F (>221C) Closed Cup.
Evaporation Rate	Not determined.
Flammability (Solid, Gas)	n/a-liquid
Upper Flammability Limit	Not determined.
Lower Flammability Limit	Not determined.
Vapor Pressure	Not determined.
Vapor Density	Not determined.
Specific Gravity	Not determined.
Water Solubility	None.
Solubility in other Solvents	Not determined.
Partition Coefficient (n-octanol/water)	Not determined.
Auto-ignition Temperature	Not determined.
Decomposition Temperature	Not determined.
Kinematic Viscosity	Not determined.
Explosive Properties	Not determined.
Oxidizing Properties	Not determined.

Section 10. STABILITY AND REACTIVITY

<u>Reactivity:</u>	Not reactive under normal conditions.
<u>Chemical Stability:</u>	Stable under recommended storage conditions.
<u>Possibility of Hazardous Reactions:</u>	None under normal processing.
<u>Conditions to Avoid:</u>	Keep out of reach of children.
<u>Incompatible Materials:</u>	None known.
<u>Hazardous Decomposition Products:</u>	Oxides of carbon.

Section 11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure:

Eye Contact: Causes serious eye irritation.

Skin Contact: May cause an allergic skin reaction.

Inhalation: Avoid breathing vapors or mists.

Ingestion: Do not taste or swallow.

Component Information:

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum oil (CAS 64741-96-4)	N/A	N/A	N/A
Red iron oxide (CAS 1309-37-1)	>10 g/kg (Rat)	N/A	N/A

Information on physical, chemical and toxicological effects:

Symptoms: Please section 4 of this SDS for symptoms.

Delayed and Immediate Effects as Well as Chronic Effects From Short and Long Term Exposure:

Sensitization: May cause an allergic skin reaction.

Carcinogenicity: Not classifiable as a human carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum oil (CAS 64741-96-4)	NO DATA	NO DATA	NO DATA	NO DATA
Red iron oxide (CAS1309-37-1)	NO DATA	NO DATA	NO DATA	NO DATA

Legend

IARC (International Agency for Research on Cancer).

Group3 IARC components are “not classifiable as human carcinogens”.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical Measures of Toxicity:

Not Determined.

Section 12. ECOLOGICAL INFORMATION

Ecotoxicity:

Toxic to aquatic life with lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Petroleum oil (64741-96-4)	N/D	N/D	N/D	N/A
Red iron oxide (1309-37-1)	N/D	>10,000 mg/kg	N/D	N/D

Persistence/Degradability: Not determined.

Bioaccumulation: Not determined.

Mobility: Not determined.

Other Adverse Effects: Not determined.

Section 13. DISPOSAL CONSIDERATIONS

Waste Treatment Method:

Disposal of Wastes: Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging: Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. TRANSPORT INFORMATION

DOT: Not Regulated

PROPER SHIPPING NAME: N/A.

IDENTIFICATION NUMBER: N/A

IATA: Not regulated

IMDG: Not regulated..

Section 15. REGULATORY INFORMATION

<u>International Inventories:</u>	Not determined.
<u>U.S. Federal Regulations:</u>	Not determined.
Petroleum oil <u>SARA 313:</u>	No.
Copper flakes SARA 313	Yes
TSCA Inventory:	Yes.
<u>U.S Right-to-Know Regulations:</u>	Not determined.

Section 16. OTHER INFORMATION

NFPA:	Health Hazards 1	Flammability 1	Instability 0	Special Hazards Not determined
HMIS	Health Hazards 1	Flammability 1	Instability 0	Special Hazards Not determined

Issue Date: 1st March 2014

Revision Date: 1^{23rd} March 2018

DISCLAIMER:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

SAFETY DATA SHEET

Section 1. IDENTIFICATION

Product Identifier

Product Name General Purpose Thred Gard.

Other means of Identification

Product Code TG04, TG08, TG16.

Recommended Use Anti Seize Compound.

Recommended Restrictions None Known.

Manufacturer

Company Name Federal Process Corporation
Address 4520 Richmond Road
 Cleveland OH 44128
Telephone 1-800-846-7325

Emergency Telephone Number: Call Chemtrec at 1-800-424-9300

Section 2. HAZARDS IDENTIFICATION

PHYSICAL STATE: Grease Like

Classification:

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

Signal Word: Warning



Hazard Statements: H319 – Causes serious eye irritation.

 H317 – May cause an allergic skin reaction

Precautionary Statements:

Prevention: Not expected to be present a hazard during normal use.

Response: P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313–If eye irritation persists: Get medical advice/attention.
 P332 + P313 – If skin irritation or rash occurs: Get medical advice/attention.

Disposal: P501 - Dispose of contents/container to an approved waste disposal plant.

Other Hazards: Toxic to aquatic life with long lasting effects.

Unknown Acute Toxicity: 2% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight %
Petroleum oil	64741-96-4	60-80
Red iron oxide	1309-37-1	5-10

Section 4. FIRST AID MEASURES

First Aid Measures:

Eye Contact Rinse thoroughly with plenty of water, for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

Skin Contact If skin irritation occurs, rinse affected area with water. If skin irritation or rash occurs: Get medical advice/attention.

Inhalation Remove to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.

Ingestion Do NOT induce vomiting Get medical attention immediately. Rinse mouth with water. Never give anything by mouth to an unconscious individual.

Most Important Symptoms and effects:

Symptoms Direct contact with eyes may cause temporary irritation.
Do NOT ingest.

Section 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Use foam, dry chemical, carbon dioxide or water fog.

Unsuitable Extinguishing Media: Avoid solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the Chemical:

Carbon oxides expected to be the primary hazardous combustion product.

Protective Equipment and Precautions for Firefighters:

As in any fire, wear self-contained breathing apparatus and other protective clothing (approved or equivalent) and full protective gear.

Section 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Personal Precautions: Use personal protective equipment as required. Keep unnecessary personnel away.

Methods and Material for Containment and Cleaning Up:

Methods for Containment: Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up: Keep in suitable, closed containers for disposal.

Section 7. HANDLING AND STORAGE

Precautions for Safe Handling:

Advice on Safe Handling: Avoid breathing vapors or mists. Contaminated work-clothing should not be allowed out of the workplace.

Conditions for Safe Storage, including

Any Incompatibilities:

Storage Conditions: Keep containers tightly closed in a dry, cool and well-ventilated place.
Do not store near heat, sparks, or open flames.
KEEP OUT OF REACH OF CHILDREN.

Incompatible Materials: None known based on information supplied.

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines:

Chemical Name	ACGIH TWA	ACGIH STEL	OSHA TWA
Petroleum oil (CAS 64741-96-4)	5 mg/m ³	N/A	5 mg/m ³
Red iron oxide (CAS 1309-37-1)	NO DATA	NO DATA	NO DATA

Appropriate Engineering Controls:

Engineering Controls: Apply technical measures to comply with the occupational exposure limits.

Individual Protection Measures, such as
Personal Protective Equipment:

Eye/Face Protection: Avoid contact with eyes.

Skin and Body Protection: No protective equipment is needed under normal use conditions.

Respiratory Protection: Ensure adequate ventilation, especially in confined areas. If confined in poorly ventilated areas use NIOSH/MSHA

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice. Wash exposed areas thoroughly before eating, drinking, smoking or leaving work area. Launder contaminated clothing before reusing.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State: Grease like. Odor: Mild.
Appearance: Viscous. Odor Threshold: Not available.
Color: Red

Property Values
pH N/A

Melting Point/Freezing Point	Not determined.
Boiling Point/Boiling Range	Not determined.
Flash Point	>430F (>221C) Closed Cup.
Evaporation Rate	Not determined.
Flammability (Solid, Gas)	n/a-liquid
Upper Flammability Limit	Not determined.
Lower Flammability Limit	Not determined.
Vapor Pressure	Not determined.
Vapor Density	Not determined.
Specific Gravity	Not determined.
Water Solubility	None.
Solubility in other Solvents	Not determined.
Partition Coefficient (n-octanol/water)	Not determined.
Auto-ignition Temperature	Not determined.
Decomposition Temperature	Not determined.
Kinematic Viscosity	Not determined.
Explosive Properties	Not determined.
Oxidizing Properties	Not determined.

Section 10. STABILITY AND REACTIVITY

<u>Reactivity:</u>	Not reactive under normal conditions.
<u>Chemical Stability:</u>	Stable under recommended storage conditions.
<u>Possibility of Hazardous Reactions:</u>	None under normal processing.
<u>Conditions to Avoid:</u>	Keep out of reach of children.
<u>Incompatible Materials:</u>	None known.
<u>Hazardous Decomposition Products:</u>	Oxides of carbon.

Section 11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure:

Eye Contact: Causes serious eye irritation.

Skin Contact: May cause an allergic skin reaction.

Inhalation: Avoid breathing vapors or mists.

Ingestion: Do not taste or swallow.

Component Information:

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum oil (CAS 64741-96-4)	N/A	N/A	N/A
Red iron oxide (CAS 1309-37-1)	>10 g/kg (Rat)	N/A	N/A

Information on physical, chemical and toxicological effects:

Symptoms: Please section 4 of this SDS for symptoms.

Delayed and Immediate Effects as Well as Chronic Effects From Short and Long Term Exposure:

Sensitization: May cause an allergic skin reaction.

Carcinogenicity: Not classifiable as a human carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum oil (CAS 64741-96-4)	NO DATA	NO DATA	NO DATA	NO DATA
Red iron oxide (CAS1309-37-1)	NO DATA	NO DATA	NO DATA	NO DATA

Legend

IARC (International Agency for Research on Cancer).

Group3 IARC components are “not classifiable as human carcinogens”.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical Measures of Toxicity:

Not Determined.

Section 12. ECOLOGICAL INFORMATION

Ecotoxicity:

Toxic to aquatic life with lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Petroleum oil (64741-96-4)	N/D	N/D	N/D	N/A
Red iron oxide (1309-37-1)	N/D	>10,000 mg/kg	N/D	N/D

Persistence/Degradability: Not determined.

Bioaccumulation: Not determined.

Mobility: Not determined.

Other Adverse Effects: Not determined.

Section 13. DISPOSAL CONSIDERATIONS

Waste Treatment Method:

Disposal of Wastes: Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging: Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. TRANSPORT INFORMATION

DOT: Not Regulated

PROPER SHIPPING NAME: N/A.

IDENTIFICATION NUMBER: N/A

IATA: Not regulated

IMDG: Not regulated..

Section 15. REGULATORY INFORMATION

International Inventories: Not determined.

U.S. Federal Regulations: Not determined.

Petroleum oil
SARA 313: No.

Copper flakes
SARA 313 Yes

TSCA Inventory: Yes.
U.S Right-to-Know Regulations: Not determined.

Section 16. OTHER INFORMATION

NFPA:	Health Hazards 1	Flammability 1	Instability 0	Special Hazards Not determined
HMIS	Health Hazards 1	Flammability 1	Instability 0	Special Hazards Not determined

Issue Date: 1st March 2014

Revision Date: 1^{23rd} March 2018

DISCLAIMER:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

SAFETY DATA SHEET

A04422007

Section 1. Identification

Product name : Industrial WORK DAY™ Enamel Spray Paint
Flat White

Product code : A04422007

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : Krylon Products Group
101 Prospect Avenue NW
Cleveland, OH 44115

Emergency telephone number of the company : US/Canada: (800) 424-9300
Mexico: CHEMTREC Mexico 01-800-681-9531. Available 24 hours and 365 days per year

Product Information Telephone Number : US/Canada: (800) 247-3266
Mexico: Not Available

Regulatory Information Telephone Number : US/Canada: (216) 566-2902
Mexico: Not Available

Transportation Emergency Telephone Number : US/Canada: (800) 424-9300
Mexico: SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 hours / 365 days a year

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION (Unborn child) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (lungs) - Category 1
ASPIRATION HAZARD - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 14.3%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 21.8%


Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 22.7%

GHS label elements

Date of issue/Date of revision : 11/27/2019	Date of previous issue : 9/14/2019	Version : 13	1/18
A04422007	Industrial WORK DAY™ Enamel Spray Paint Flat White	SHW-85-NA-GHS-US	84

Section 2. Hazards identification

Hazard pictograms



Signal word

: Danger

Hazard statements

- : Extremely flammable aerosol.
- Contains gas under pressure; may explode if heated.
- Causes serious eye irritation.
- Causes skin irritation.
- Suspected of damaging the unborn child.
- Suspected of causing cancer.
- May be fatal if swallowed and enters airways.
- May cause respiratory irritation.
- May cause drowsiness or dizziness.
- Causes damage to organs through prolonged or repeated exposure. (lungs)

Precautionary statements

Prevention

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.

Response

- : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage

- : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

Disposal

- : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.

Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

Hazards not otherwise classified

- : DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of identification : Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Acetone	≥25 - ≤50	67-64-1
Propane	≥10 - ≤25	74-98-6
Butane	≥10 - ≤25	106-97-8
Isobutyl Acetate	≤10	110-19-0
Talc	≤10	14807-96-6
Toluene	≤10	108-88-3
Titanium Dioxide	≤5	13463-67-7
Ethyl 3-Ethoxypropionate	≤1.6	763-69-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.

Section 4. First aid measures

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Section 5. Fire-fighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
 - carbon dioxide
 - carbon monoxide
 - metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Section 7. Handling and storage

Protective measures : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Acetone	67-64-1	ACGIH TLV (United States, 3/2019). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. NIOSH REL (United States, 10/2016). TWA: 250 ppm 10 hours. TWA: 590 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 2400 mg/m ³ 8 hours.
Propane	74-98-6	NIOSH REL (United States, 10/2016). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2019). Oxygen Depletion [Asphyxiant]. Explosive potential.
Butane	106-97-8	NIOSH REL (United States, 10/2016). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 3/2019). Explosive potential. STEL: 1000 ppm 15 minutes.
Isobutyl Acetate	110-19-0	NIOSH REL (United States, 10/2016). TWA: 150 ppm 10 hours. TWA: 700 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 150 ppm 8 hours.

Section 8. Exposure controls/personal protection

Talc	14807-96-6	<p>TWA: 700 mg/m³ 8 hours. ACGIH TLV (United States, 3/2019). STEL: 150 ppm 15 minutes. TWA: 50 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 2 mg/m³ 10 hours. Form: Respirable fraction ACGIH TLV (United States, 3/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable fraction</p>
Toluene	108-88-3	<p>OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 375 mg/m³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m³ 15 minutes. ACGIH TLV (United States, 3/2019). TWA: 20 ppm 8 hours.</p>
Titanium Dioxide	13463-67-7	<p>ACGIH TLV (United States, 3/2019). TWA: 10 mg/m³ 8 hours. OSHA PEL (United States, 5/2018). TWA: 15 mg/m³ 8 hours. Form: Total dust</p>
Ethyl 3-Ethoxypropionate	763-69-9	<p>None.</p>

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Acetone	67-64-1	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1200 mg/m³ 8 hours. 15 min OEL: 1800 mg/m³ 15 minutes. 8 hrs OEL: 500 ppm 8 hours. 15 min OEL: 750 ppm 15 minutes. CA British Columbia Provincial (Canada, 5/2019). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. CA Ontario Provincial (Canada, 1/2018). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. CA Quebec Provincial (Canada, 1/2014). TWAEV: 500 ppm 8 hours. TWAEV: 1190 mg/m³ 8 hours. STEV: 1000 ppm 15 minutes. STEV: 2380 mg/m³ 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 750 ppm 15 minutes. TWA: 500 ppm 8 hours.</p>
Normal propane	74-98-6	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 1000 ppm 8 hours. TWAEV: 1800 mg/m³ 8 hours. CA Ontario Provincial (Canada, 1/2018).</p>

Section 8. Exposure controls/personal protection

Butane	106-97-8	<p>TWA: 1000 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 5/2019). Oxygen Depletion [Asphyxiant]. Explosive potential. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 800 ppm 8 hours. TWAEV: 1900 mg/m³ 8 hours. CA Ontario Provincial (Canada, 1/2018). TWA: 800 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 5/2019). Explosive potential. STEL: 1000 ppm 15 minutes.</p>
Isobutyl acetate	110-19-0	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 150 ppm 8 hours. 8 hrs OEL: 713 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 5/2019). TWA: 150 ppm 8 hours. CA Ontario Provincial (Canada, 1/2018). TWA: 150 ppm 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 150 ppm 8 hours. TWAEV: 713 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 188 ppm 15 minutes. TWA: 150 ppm 8 hours.</p>
talc (none asbestiform)	14807-96-6	<p>CA British Columbia Provincial (Canada, 5/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable TWA: 0.1 f/cc 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 3 mg/m³ 8 hours. Form: Respirable dust. CA Ontario Provincial (Canada, 1/2018). TWA: 2 mg/m³ 8 hours. Form: Respirable fraction. TWA: 2 f/cc 8 hours. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m³ 8 hours. Form: Respirable particulate CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable fraction</p>
Toluene	108-88-3	<p>CA Alberta Provincial (Canada, 6/2018). Absorbed through skin.</p>

Section 8. Exposure controls/personal protection

Titanium dioxide	13463-67-7	<p>8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 188 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 5/2019). TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 1/2018). TWA: 20 ppm 8 hours. CA Quebec Provincial (Canada, 1/2014). Absorbed through skin. TWAEV: 50 ppm 8 hours. TWAEV: 188 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.</p> <p>CA British Columbia Provincial (Canada, 5/2019). TWA: 3 mg/m³ 8 hours. Form: Respirable dust TWA: 10 mg/m³ 8 hours. Form: Total dust CA Quebec Provincial (Canada, 1/2014). TWAEV: 10 mg/m³ 8 hours. Form: Total dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m³ 8 hours. CA Ontario Provincial (Canada, 1/2018). TWA: 10 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours.</p>
------------------	------------	---

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
Acetone	67-64-1	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 500 ppm 8 hours. STEL: 750 ppm 15 minutes.
Propane	74-98-6	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
Butane	106-97-8	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
Isobutyl Acetate	110-19-0	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 150 ppm 8 hours.
Toluene	108-88-3	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

- Appearance**
- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point/boiling range** : Not available.
- Flash point** : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 5.6 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 1%
Upper: 12.8%
- Vapor pressure** : 101.3 kPa (760 mm Hg) [at 20°C]
- Vapor density** : 1.55 [Air = 1]
- Relative density** : 0.77
- Solubility** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.

Section 9. Physical and chemical properties

Decomposition temperature : Not available.
Viscosity : Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
Molecular weight : Not applicable.
Aerosol product
Type of aerosol : Spray
Heat of combustion : 27.659 kJ/g

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.
Chemical stability : The product is stable.
Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid : Avoid all possible sources of ignition (spark or flame).
Incompatible materials : No specific data.
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Acetone	LD50 Oral	Rat	5800 mg/kg	-
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours
Isobutyl Acetate	LD50 Dermal	Rabbit	>17400 mg/kg	-
	LD50 Oral	Rat	13400 mg/kg	-
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Ethyl 3-Ethoxypropionate	LD50 Oral	Rat	3200 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Acetone	Eyes - Mild irritant	Human	-	186300 ppm	-
	Eyes - Mild irritant	Rabbit	-	10 UI	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
Isobutyl Acetate	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	395 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Talc	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Human	-	72 hours 300 ug l	-

Section 11. Toxicological information

Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes	-
	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Severe irritant	Rabbit	-	870 ug	-
				24 hours 2	-
	Skin - Mild irritant	Pig	-	mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 250	-
	Skin - Moderate irritant	Rabbit	-	UI	-
			-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
Titanium Dioxide	Skin - Mild irritant	Human	-	mg	-
			-	500 mg	-
			-	72 hours 300	-
Ethyl 3-Ethoxypropionate	Skin - Mild irritant	Rabbit	-	ug l	-
			-	24 hours 500	-
			-	mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Talc	-	3	-
Toluene	-	3	-
Titanium Dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Acetone	Category 3	Not applicable.	Narcotic effects
	Category 3	Not applicable.	Respiratory tract irritation
Propane	Category 3	Not applicable.	Narcotic effects
	Category 3	Not applicable.	Respiratory tract irritation
Butane	Category 3	Not applicable.	Narcotic effects
	Category 3	Not applicable.	Respiratory tract irritation
Isobutyl Acetate	Category 3	Not applicable.	Narcotic effects
Toluene	Category 3	Not applicable.	Narcotic effects
	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
Acetone	Category 2	Not determined	Not determined
Propane	Category 2	Not determined	Not determined
Butane	Category 2	Not determined	Not determined
Talc	Category 1	Inhalation	lungs
Toluene	Category 2	Not determined	Not determined

Aspiration hazard

Name	Result
Propane	ASPIRATION HAZARD - Category 1
Butane	ASPIRATION HAZARD - Category 1
Toluene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
- Inhalation** : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 unconsciousness
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
 irritation
 redness
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 nausea or vomiting
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Section 11. Toxicological information

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Causes damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	8085.01 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Acetone	Acute EC50 7200000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute LC50 6000000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 6900 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 5600 ppm Fresh water	Fish - Poecilia reticulata	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Toluene	Chronic NOEC 0.1 mg/l Fresh water	Fish - Fundulus heteroclitus
Acute EC50 12500 µg/l Fresh water		Algae - Pseudokirchneriella subcapitata	72 hours
Acute EC50 11600 µg/l Fresh water		Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
Acute EC50 6000 µg/l Fresh water		Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
Titanium Dioxide	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Acetone	-	-	Readily
Toluene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Toluene	-	90	low

Mobility in soil






Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class	-	-	Emergency schedules F-D, S-U

Section 14. Transport information

	<u>ERG No.</u> 126	2). <u>ERG No.</u> 126	<u>ERG No.</u> 126	
--	-----------------------	------------------------------	-----------------------	--

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

Proper shipping name : Not available.
Ship type : Not available.
Pollution category : Not available.

Section 15. Regulatory information

SARA 313
 SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65
 WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations
International lists :

- Australia inventory (AICS)**: Not determined.
- China inventory (IECSC)**: Not determined.
- Japan inventory (ENCS)**: Not determined.
- Japan inventory (ISHL)**: Not determined.
- Korea inventory (KECI)**: Not determined.
- New Zealand Inventory of Chemicals (NZIoC)**: Not determined.
- Philippines inventory (PICCS)**: Not determined.
- Taiwan Chemical Substances Inventory (TCSI)**: Not determined.
- Thailand inventory**: Not determined.
- Turkey inventory**: Not determined.
- Vietnam inventory**: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		4
Physical hazards		3

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	Calculation method
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (lungs) - Category 1	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

History

Date of printing : 11/27/2019

Date of issue/Date of revision : 11/27/2019

Date of previous issue : 9/14/2019

Version : 13

Key to abbreviations : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group
 UN = United Nations

📌 Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of

Date of issue/Date of revision : 11/27/2019	Date of previous issue : 9/14/2019	Version : 13	17/18
A04422007	Industrial WORK DAY™ Enamel Spray Paint Flat White	SHW-85-NA-GHS-US	

Section 16. Other information

sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

A03700004

Section 1. Identification

Product name : KRYLON® Industrial QUIK-MARK™ Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Orange

Product code : A03700004

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : Krylon Products Group
101 Prospect Avenue NW
Cleveland, OH 44115

Emergency telephone number of the company : US/Canada: (800) 424-9300
Mexico: CHEMTREC Mexico 800-681-9531. Available 24 hours and 365 days per year

Product Information Telephone Number : US/Canada: (800) 247-3266
Mexico: Not Available

Regulatory Information Telephone Number : US/Canada: (216) 566-2902
Mexico: Not Available

Transportation Emergency Telephone Number : US/Canada: (800) 424-9300
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year


Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 18.5% (oral), 28.4% (dermal), 18.5% (inhalation)

GHS label elements

Hazard pictograms



Signal word : Danger

Date of issue/Date of revision : 6/4/2021

Date of previous issue : 4/19/2021

Version : 17

1/17

A03700004

KRYLON® Industrial QUIK-MARK™ Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Orange

SHW-85-NA-GHS-US

Section 2. Hazards identification

Hazard statements : Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May be fatal if swallowed and enters airways.
 May cause respiratory irritation.
 May cause drowsiness or dizziness.
 Suspected of causing cancer.
 Suspected of damaging fertility or the unborn child.
 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Pressurized container: Do not pierce or burn, even after use.

Response : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Storage : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
 Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

Hazards not otherwise classified : DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Toluene	<10	108-88-3
Propane	≤10	74-98-6
Light Aliphatic Hydrocarbon	≤10	64742-47-8
Butane	≤5	106-97-8
Lt. Aliphatic Hydrocarbon Solvent	≤3	64742-89-8
Titanium Dioxide	≤0.3	13463-67-7
Xylene, mixed isomers	≤0.3	1330-20-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
 - irritation
 - redness
- Inhalation** : Adverse symptoms may include the following:
 - respiratory tract irritation
 - coughing
 - nausea or vomiting
 - headache
 - drowsiness/fatigue
 - dizziness/vertigo
 - unconsciousness
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations

Section 4. First aid measures

- Skin contact** : Adverse symptoms may include the following:
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 - nausea or vomiting
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous thermal decomposition products : Decomposition products may include the following materials:

- carbon dioxide
- carbon monoxide
- nitrogen oxides
- sulfur oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Toluene	108-88-3	OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 375 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m ³ 15 minutes. ACGIH TLV (United States, 3/2020). TWA: 20 ppm 8 hours.
Propane	74-98-6	NIOSH REL (United States, 10/2016). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2020). Oxygen Depletion [Asphyxiant]. Explosive potential. ACGIH TLV (United States, 3/2020). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.
Light Aliphatic Hydrocarbon	64742-47-8	NIOSH REL (United States, 10/2016). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 3/2020). Explosive potential. STEL: 1000 ppm 15 minutes.
Butane	106-97-8	None. ACGIH TLV (United States, 3/2020). TWA: 10 mg/m ³ 8 hours. OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 3/2020). TWA: 100 ppm 8 hours. TWA: 434 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m ³ 15 minutes. OSHA PEL (United States, 5/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Lt. Aliphatic Hydrocarbon Solvent	64742-89-8	
Titanium Dioxide	13463-67-7	
Xylene, mixed isomers	1330-20-7	

Occupational exposure limits (Canada)

Section 8. Exposure controls/personal protection

Ingredient name	CAS #	Exposure limits
Toluene	108-88-3	<p>CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 188 mg/m³ 8 hours.</p> <p>CA British Columbia Provincial (Canada, 1/2020). TWA: 20 ppm 8 hours.</p> <p>CA Ontario Provincial (Canada, 6/2019). TWA: 20 ppm 8 hours.</p> <p>CA Quebec Provincial (Canada, 7/2019). Absorbed through skin. TWAEV: 50 ppm 8 hours. TWAEV: 188 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.</p>
Normal propane	74-98-6	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours.</p> <p>CA Quebec Provincial (Canada, 7/2019). TWAEV: 1000 ppm 8 hours. TWAEV: 1800 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.</p> <p>CA British Columbia Provincial (Canada, 1/2020). Oxygen Depletion [Asphyxiant]. Explosive potential.</p> <p>CA Ontario Provincial (Canada, 6/2019). Oxygen Depletion [Asphyxiant]. Explosive potential.</p>
Petroleum refining, hydrotreated light distillate	64742-47-8	<p>CA British Columbia Provincial (Canada, 1/2020). Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.</p> <p>CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.</p> <p>CA Ontario Provincial (Canada, 6/2019). Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.</p>
Butane	106-97-8	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours.</p> <p>CA Quebec Provincial (Canada, 7/2019). TWAEV: 800 ppm 8 hours. TWAEV: 1900 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.</p> <p>CA British Columbia Provincial (Canada,</p>

Section 8. Exposure controls/personal protection

Titanium dioxide	13463-67-7	<p>1/2020). Explosive potential. STEL: 1000 ppm 15 minutes. CA Ontario Provincial (Canada, 6/2019). Explosive potential. STEL: 1000 ppm 15 minutes. CA British Columbia Provincial (Canada, 1/2020). TWA: 10 mg/m³ 8 hours. Form: Total dust TWA: 3 mg/m³ 8 hours. Form: respirable fraction CA Quebec Provincial (Canada, 7/2019). TWAEV: 10 mg/m³ 8 hours. Form: Total dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m³ 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours.</p>
Xylene	1330-20-7	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 100 ppm 8 hours. 15 min OEL: 651 mg/m³ 15 minutes. 15 min OEL: 150 ppm 15 minutes. 8 hrs OEL: 434 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 1/2020). TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes. CA Quebec Provincial (Canada, 7/2019). TWAEV: 100 ppm 8 hours. TWAEV: 434 mg/m³ 8 hours. STEV: 150 ppm 15 minutes. STEV: 651 mg/m³ 15 minutes. CA Ontario Provincial (Canada, 6/2019). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.</p>

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
Toluene	108-88-3	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
Propane	74-98-6	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
Light Aliphatic Hydrocarbon	64742-47-8	ACGIH TLV (United States, 3/2020). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.
Butane	106-97-8	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.

Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : 7
- Melting point/freezing point** : Not available.
- Boiling point/boiling range** : Not available.
- Flash point** : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 2 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.

Section 9. Physical and chemical properties

- Lower and upper explosive (flammable) limits** : Lower: 0.9%
Upper: 9.5%
- Vapor pressure** : 101.3 kPa (760 mm Hg) [at 20°C]
- Vapor density** : 1 [Air = 1]
- Relative density** : 0.86
- Solubility** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
- Molecular weight** : Not applicable.
- Aerosol product**
- Type of aerosol** : Spray
- Heat of combustion** : 13.154 kJ/g

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours
	LC50 Inhalation Gas.	Rat	6700 ppm	4 hours
Xylene, mixed isomers	LD50 Oral	Rat	4300 mg/kg	-

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Eyes - Mild irritant	Rabbit	-	870 ug	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Pig	-	24 hours 250 uL	-
	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
Titanium Dioxide	Skin - Moderate irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
Xylene, mixed isomers	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 uL	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	100 %	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-
Titanium Dioxide	-	2B	-
Xylene, mixed isomers	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 3	-	Respiratory tract irritation
Propane	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
Light Aliphatic Hydrocarbon	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
Butane	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation

Section 11. Toxicological information

Lt. Aliphatic Hydrocarbon Solvent	Category 3	-	Narcotic effects
Xylene, mixed isomers	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects
	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 2	-	-
Propane	Category 2	-	-
Light Aliphatic Hydrocarbon	Category 2	-	-
Butane	Category 2	-	-
Lt. Aliphatic Hydrocarbon Solvent	Category 2	-	-
Xylene, mixed isomers	Category 2	-	-

Aspiration hazard

Name	Result
Toluene	ASPIRATION HAZARD - Category 1
Propane	ASPIRATION HAZARD - Category 1
Light Aliphatic Hydrocarbon	ASPIRATION HAZARD - Category 1
Butane	ASPIRATION HAZARD - Category 1
Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
Xylene, mixed isomers	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : No known significant effects or critical hazards.

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
irritation
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 11. Toxicological information

Ingestion : Adverse symptoms may include the following:
 nausea or vomiting
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	5261.79 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Toluene	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
Light Aliphatic Hydrocarbon Lt. Aliphatic Hydrocarbon Solvent	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days
	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
Xylene, mixed isomers	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes	48 hours

Section 12. Ecological information

	Acute LC50 13400 µg/l Fresh water	pugio Fish - Pimephales promelas	96 hours
--	-----------------------------------	-------------------------------------	----------

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily
Xylene, mixed isomers	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Toluene	-	90	low
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	high
Xylene, mixed isomers	-	8.1 to 25.9	low

Mobility in soil






Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

Section 14. Transport information

Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).	-	-	Emergency schedules F-D, S-U
	ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to IMO instruments : Not available.

Proper shipping name : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

International lists

- Australia inventory (AIIIC):** Not determined.
- China inventory (IECSC):** Not determined.
- Japan inventory (CSCL):** Not determined.
- Japan inventory (ISHL):** Not determined.
- Korea inventory (KECI):** Not determined.
- New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- Philippines inventory (PICCS):** Not determined.
- Taiwan Chemical Substances Inventory (TCSI):** Not determined.
- Thailand inventory:** Not determined.
- Turkey inventory:** Not determined.
- Vietnam inventory:** Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		2
Physical hazards		3

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

History

Date of printing : 6/4/2021

Date of issue/Date of revision : 6/4/2021

Date of previous issue : 4/19/2021

Version : 17

Key to abbreviations :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- SGG = Segregation Group
- UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer,

Section 16. Other information

or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

A03700004

Section 1. Identification

Product name : KRYLON® Industrial QUIK-MARK™ Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Orange

Product code : A03700004

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : Krylon Products Group
101 Prospect Avenue NW
Cleveland, OH 44115

Emergency telephone number of the company : US/Canada: (800) 424-9300
Mexico: CHEMTREC Mexico 800-681-9531. Available 24 hours and 365 days per year

Product Information Telephone Number : US/Canada: (800) 247-3266
Mexico: Not Available

Regulatory Information Telephone Number : US/Canada: (216) 566-2902
Mexico: Not Available

Transportation Emergency Telephone Number : US/Canada: (800) 424-9300
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year


Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 18.5% (oral), 28.4% (dermal), 18.5% (inhalation)

GHS label elements

Hazard pictograms



Signal word : Danger

Date of issue/Date of revision : 6/4/2021

Date of previous issue : 4/19/2021

Version : 17

1/17

A03700004

KRYLON® Industrial QUIK-MARK™ Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Orange

SHW-85-NA-GHS-US

Section 2. Hazards identification

Hazard statements : Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May be fatal if swallowed and enters airways.
 May cause respiratory irritation.
 May cause drowsiness or dizziness.
 Suspected of causing cancer.
 Suspected of damaging fertility or the unborn child.
 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Pressurized container: Do not pierce or burn, even after use.

Response : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Storage : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
 Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

Hazards not otherwise classified : DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Toluene	<10	108-88-3
Propane	≤10	74-98-6
Light Aliphatic Hydrocarbon	≤10	64742-47-8
Butane	≤5	106-97-8
Lt. Aliphatic Hydrocarbon Solvent	≤3	64742-89-8
Titanium Dioxide	≤0.3	13463-67-7
Xylene, mixed isomers	≤0.3	1330-20-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 4. First aid measures

- Skin contact** : Adverse symptoms may include the following:
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 - nausea or vomiting
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous thermal decomposition products : Decomposition products may include the following materials:

- carbon dioxide
- carbon monoxide
- nitrogen oxides
- sulfur oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Toluene	108-88-3	OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 375 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m ³ 15 minutes. ACGIH TLV (United States, 3/2020). TWA: 20 ppm 8 hours.
Propane	74-98-6	NIOSH REL (United States, 10/2016). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2020). Oxygen Depletion [Asphyxiant]. Explosive potential. ACGIH TLV (United States, 3/2020). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.
Light Aliphatic Hydrocarbon	64742-47-8	NIOSH REL (United States, 10/2016). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 3/2020). Explosive potential. STEL: 1000 ppm 15 minutes.
Butane	106-97-8	None. ACGIH TLV (United States, 3/2020). TWA: 10 mg/m ³ 8 hours. OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 3/2020). TWA: 100 ppm 8 hours. TWA: 434 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m ³ 15 minutes. OSHA PEL (United States, 5/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Lt. Aliphatic Hydrocarbon Solvent	64742-89-8	
Titanium Dioxide	13463-67-7	
Xylene, mixed isomers	1330-20-7	

Occupational exposure limits (Canada)

Section 8. Exposure controls/personal protection

Ingredient name	CAS #	Exposure limits
Toluene	108-88-3	<p>CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 188 mg/m³ 8 hours.</p> <p>CA British Columbia Provincial (Canada, 1/2020). TWA: 20 ppm 8 hours.</p> <p>CA Ontario Provincial (Canada, 6/2019). TWA: 20 ppm 8 hours.</p> <p>CA Quebec Provincial (Canada, 7/2019). Absorbed through skin. TWAEV: 50 ppm 8 hours. TWAEV: 188 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.</p>
Normal propane	74-98-6	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours.</p> <p>CA Quebec Provincial (Canada, 7/2019). TWAEV: 1000 ppm 8 hours. TWAEV: 1800 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.</p> <p>CA British Columbia Provincial (Canada, 1/2020). Oxygen Depletion [Asphyxiant]. Explosive potential.</p> <p>CA Ontario Provincial (Canada, 6/2019). Oxygen Depletion [Asphyxiant]. Explosive potential.</p>
Petroleum refining, hydrotreated light distillate	64742-47-8	<p>CA British Columbia Provincial (Canada, 1/2020). Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.</p> <p>CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.</p> <p>CA Ontario Provincial (Canada, 6/2019). Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.</p>
Butane	106-97-8	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours.</p> <p>CA Quebec Provincial (Canada, 7/2019). TWAEV: 800 ppm 8 hours. TWAEV: 1900 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.</p> <p>CA British Columbia Provincial (Canada,</p>

Section 8. Exposure controls/personal protection

Titanium dioxide	13463-67-7	<p>1/2020). Explosive potential. STEL: 1000 ppm 15 minutes. CA Ontario Provincial (Canada, 6/2019). Explosive potential. STEL: 1000 ppm 15 minutes. CA British Columbia Provincial (Canada, 1/2020). TWA: 10 mg/m³ 8 hours. Form: Total dust TWA: 3 mg/m³ 8 hours. Form: respirable fraction CA Quebec Provincial (Canada, 7/2019). TWAEV: 10 mg/m³ 8 hours. Form: Total dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m³ 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours.</p>
Xylene	1330-20-7	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 100 ppm 8 hours. 15 min OEL: 651 mg/m³ 15 minutes. 15 min OEL: 150 ppm 15 minutes. 8 hrs OEL: 434 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 1/2020). TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes. CA Quebec Provincial (Canada, 7/2019). TWAEV: 100 ppm 8 hours. TWAEV: 434 mg/m³ 8 hours. STEV: 150 ppm 15 minutes. STEV: 651 mg/m³ 15 minutes. CA Ontario Provincial (Canada, 6/2019). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.</p>

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
Toluene	108-88-3	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
Propane	74-98-6	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
Light Aliphatic Hydrocarbon	64742-47-8	ACGIH TLV (United States, 3/2020). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.
Butane	106-97-8	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.

Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : 7
- Melting point/freezing point** : Not available.
- Boiling point/boiling range** : Not available.
- Flash point** : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 2 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.

Section 9. Physical and chemical properties

- Lower and upper explosive (flammable) limits** : Lower: 0.9%
Upper: 9.5%
- Vapor pressure** : 101.3 kPa (760 mm Hg) [at 20°C]
- Vapor density** : 1 [Air = 1]
- Relative density** : 0.86
- Solubility** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
- Molecular weight** : Not applicable.
- Aerosol product**
- Type of aerosol** : Spray
- Heat of combustion** : 13.154 kJ/g

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours
	LC50 Inhalation Gas.	Rat	6700 ppm	4 hours
Xylene, mixed isomers	LD50 Oral	Rat	4300 mg/kg	-

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Eyes - Mild irritant	Rabbit	-	870 ug	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Pig	-	24 hours 250 uL	-
	Skin - Mild irritant Skin - Moderate irritant	Rabbit Rabbit	- -	435 mg 24 hours 20 mg	- -
Titanium Dioxide	Skin - Moderate irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
Xylene, mixed isomers	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 uL	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	100 %	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-
Titanium Dioxide	-	2B	-
Xylene, mixed isomers	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 3	-	Respiratory tract irritation
Propane	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
Light Aliphatic Hydrocarbon	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
Butane	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation

Section 11. Toxicological information

Lt. Aliphatic Hydrocarbon Solvent	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
Xylene, mixed isomers	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 2	-	-
Propane	Category 2	-	-
Light Aliphatic Hydrocarbon	Category 2	-	-
Butane	Category 2	-	-
Lt. Aliphatic Hydrocarbon Solvent	Category 2	-	-
Xylene, mixed isomers	Category 2	-	-

Aspiration hazard

Name	Result
Toluene	ASPIRATION HAZARD - Category 1
Propane	ASPIRATION HAZARD - Category 1
Light Aliphatic Hydrocarbon	ASPIRATION HAZARD - Category 1
Butane	ASPIRATION HAZARD - Category 1
Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
Xylene, mixed isomers	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 11. Toxicological information

Ingestion : Adverse symptoms may include the following:
 nausea or vomiting
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	5261.79 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Toluene	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
Light Aliphatic Hydrocarbon Lt. Aliphatic Hydrocarbon Solvent	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days
	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
Titanium Dioxide Xylene, mixed isomers	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes	48 hours

Section 12. Ecological information

	Acute LC50 13400 µg/l Fresh water	pugio Fish - Pimephales promelas	96 hours
--	-----------------------------------	-------------------------------------	----------

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily
Xylene, mixed isomers	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Toluene	-	90	low
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	high
Xylene, mixed isomers	-	8.1 to 25.9	low

Mobility in soil






Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

Section 14. Transport information

Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).	-	-	Emergency schedules F-D, S-U
	ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to IMO instruments : Not available.

Proper shipping name : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

International lists

- Australia inventory (AIIIC):** Not determined.
- China inventory (IECSC):** Not determined.
- Japan inventory (CSCL):** Not determined.
- Japan inventory (ISHL):** Not determined.
- Korea inventory (KECI):** Not determined.
- New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- Philippines inventory (PICCS):** Not determined.
- Taiwan Chemical Substances Inventory (TCSI):** Not determined.
- Thailand inventory:** Not determined.
- Turkey inventory:** Not determined.
- Vietnam inventory:** Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		2
Physical hazards		3

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

History

Date of printing : 6/4/2021

Date of issue/Date of revision : 6/4/2021

Date of previous issue : 4/19/2021

Version : 17

Key to abbreviations : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group
 UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer,

Section 16. Other information

or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

A03700004

Section 1. Identification

Product name : KRYLON® Industrial QUIK-MARK™ Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Orange

Product code : A03700004

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : Krylon Products Group
101 Prospect Avenue NW
Cleveland, OH 44115

Emergency telephone number of the company : US/Canada: (800) 424-9300
Mexico: CHEMTREC Mexico 01-800-681-9531. Available 24 hours and 365 days per year

Product Information Telephone Number : US/Canada: (800) 247-3266
Mexico: Not Available

Regulatory Information Telephone Number : US/Canada: (216) 566-2902
Mexico: Not Available

Transportation Emergency Telephone Number : US/Canada: (800) 424-9300
Mexico: SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 hours / 365 days a year

Section 2. Hazards identification


OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
TOXIC TO REPRODUCTION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 18.7% (oral), 28.5% (dermal), 18.7% (inhalation)

GHS label elements

Hazard pictograms



Signal word : Danger

Date of issue/Date of revision : 10/13/2020 **Date of previous issue** : 5/13/2020

Version : 15

1/16

A03700004

KRYLON® Industrial QUIK-MARK™ Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Orange

SHW-85-NA-GHS-US

Section 2. Hazards identification

Hazard statements : Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May be fatal if swallowed and enters airways.
 May cause respiratory irritation.
 May cause drowsiness or dizziness.
 Suspected of damaging fertility or the unborn child.
 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Pressurized container: Do not pierce or burn, even after use.

Response : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Storage : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
 Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

Hazards not otherwise classified : DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of identification : Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Toluene	<10	108-88-3
Propane	≤10	74-98-6
Light Aliphatic Hydrocarbon	≤10	64742-47-8
Butane	≤5	106-97-8
Lt. Aliphatic Hydrocarbon Solvent	≤3	64742-89-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 4. First aid measures

- Skin contact** : Adverse symptoms may include the following:
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 - nausea or vomiting
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous thermal decomposition products : Decomposition products may include the following materials:

- carbon dioxide
- carbon monoxide
- nitrogen oxides
- sulfur oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Toluene	108-88-3	OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 375 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m ³ 15 minutes. ACGIH TLV (United States, 3/2020). TWA: 20 ppm 8 hours.
Propane	74-98-6	NIOSH REL (United States, 10/2016). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2020). Oxygen Depletion [Asphyxiant]. Explosive potential.
Light Aliphatic Hydrocarbon	64742-47-8	ACGIH TLV (United States, 3/2020). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.
Butane	106-97-8	NIOSH REL (United States, 10/2016). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 3/2020). Explosive potential. STEL: 1000 ppm 15 minutes.
Lt. Aliphatic Hydrocarbon Solvent	64742-89-8	None.

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Toluene	108-88-3	CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 188 mg/m ³ 8 hours. CA British Columbia Provincial (Canada, 1/2020). TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 20 ppm 8 hours. CA Quebec Provincial (Canada, 7/2019). Absorbed through skin. TWAEV: 50 ppm 8 hours.

Section 8. Exposure controls/personal protection

Normal propane	74-98-6	<p>TWAEV: 188 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.</p> <p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 1000 ppm 8 hours. TWAEV: 1800 mg/m³ 8 hours.</p> <p>CA Ontario Provincial (Canada, 6/2019). TWA: 1000 ppm 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.</p> <p>CA British Columbia Provincial (Canada, 1/2020). Oxygen Depletion [Asphyxiant]. Explosive potential.</p>
Petroleum refining, hydrotreated light distillate	64742-47-8	<p>CA British Columbia Provincial (Canada, 1/2020). Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.</p> <p>CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.</p> <p>CA Ontario Provincial (Canada, 6/2019). Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.</p>
Butane	106-97-8	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 800 ppm 8 hours. TWAEV: 1900 mg/m³ 8 hours.</p> <p>CA Ontario Provincial (Canada, 6/2019). TWA: 800 ppm 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.</p> <p>CA British Columbia Provincial (Canada, 1/2020). Explosive potential. STEL: 1000 ppm 15 minutes.</p>

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
Toluene	108-88-3	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
Propane	74-98-6	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
Light Aliphatic Hydrocarbon	64742-47-8	ACGIH TLV (United States, 3/2020). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.

Section 8. Exposure controls/personal protection

Butane	106-97-8	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
--------	----------	--

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
 - Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
 - Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
 - Skin protection**
 - Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
 - Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
 - Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
 - Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

- Appearance**
- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : 7
- Melting point/freezing point** : Not available.
- Boiling point/boiling range** : Not available.

Section 9. Physical and chemical properties

- Flash point** : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 2 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 0.9%
Upper: 9.5%
- Vapor pressure** : 101.3 kPa (760 mm Hg) [at 20°C]
- Vapor density** : 1 [Air = 1]
- Relative density** : 0.86
- Solubility** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
- Molecular weight** : Not applicable.
- Aerosol product**
- Type of aerosol** : Spray
- Heat of combustion** : 13.191 kJ/g

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
Butane	LD50 Oral	Rat	636 mg/kg	-
	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Eyes - Mild irritant	Rabbit	-	870 ug	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Pig	-	24 hours 250 UJ	-
	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 3	-	Respiratory tract irritation
Propane	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
Light Aliphatic Hydrocarbon	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
Butane	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
Lt. Aliphatic Hydrocarbon Solvent	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
	Category 3		Narcotic effects

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
Toluene	Category 2	-	-
Propane	Category 2	-	-
Light Aliphatic Hydrocarbon	Category 2	-	-
Butane	Category 2	-	-
Lt. Aliphatic Hydrocarbon Solvent	Category 2	-	-

Aspiration hazard

Name	Result
Toluene	ASPIRATION HAZARD - Category 1
Propane	ASPIRATION HAZARD - Category 1
Light Aliphatic Hydrocarbon	ASPIRATION HAZARD - Category 1
Butane	ASPIRATION HAZARD - Category 1
Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Section 11. Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	5286.78 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Toluene	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
Light Aliphatic Hydrocarbon Lt. Aliphatic Hydrocarbon Solvent	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days
	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily

Bioaccumulative potential

Section 12. Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Toluene Lt. Aliphatic Hydrocarbon Solvent	- -	90 10 to 2500	low high

Mobility in soil






Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	- ERG No. 126	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2). ERG No. 126	- ERG No. 126	-	Emergency schedules F-D, S-U

Section 14. Transport information

	Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Dependent upon container size, this product may ship under the Limited Quantity shipping exception.
--	---	---	---	---	---

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to IMO instruments : Not available.

Proper shipping name : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

International lists

- : **Australia inventory (AICS):** Not determined.
- : **China inventory (IECSC):** Not determined.
- : **Japan inventory (ENCS):** Not determined.
- : **Japan inventory (ISHL):** Not determined.
- : **Korea inventory (KECI):** Not determined.
- : **New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- : **Philippines inventory (PICCS):** Not determined.
- : **Taiwan Chemical Substances Inventory (TCSI):** Not determined.
- : **Thailand inventory:** Not determined.
- : **Turkey inventory:** Not determined.
- : **Vietnam inventory:** Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		2
Physical hazards		3

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Section 16. Other information

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

History

Date of printing : 10/13/2020

Date of issue/Date of revision : 10/13/2020

Date of previous issue : 5/13/2020

Version : 15

Key to abbreviations : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group
 UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.



Revision Number: 004.1

Issue date: 04/02/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE LB 8504 SYNTHETIC PETROLEUM ANTI-SEIZE known as Loctite(R) Graphite-50 Synthet
Product type: Lubricant
Restriction of Use: None identified
Company address: Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 234244

Item number: 51084
Region: United States

Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)

None

Precautionary Statements

Prevention: Not prescribed
Response: Not prescribed
Storage: Not prescribed
Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Graphite	7782-42-5	40 - 50
Petrolatum	8009-03-8	40 - 50
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	5 - 10
Petroleum distillates, hydrotreated, light naphthenic	64742-53-6	5 - 10

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

IDH number: 234244

Product name: LOCTITE LB 8504 SYNTHETIC PETROLEUM ANTI-SEIZE known as Loctite(R) Graphite-50 Synthet

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	If high pressure forces the product under the skin get immediate medical attention. If hot material contacts the skin, immediately cool before attempting removal. Wash with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms develop and persist, get medical attention.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide. Do not use high volume water jet.
Special firefighting procedures:	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode. Oil will float on water and can spread fire.
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray. Closed containers may explode when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Acrid smoke and fumes.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up as much material as possible. Clean residue with soap and water. Contaminated surfaces will be extremely slippery.

7. HANDLING AND STORAGE

Handling:	Keep container closed. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.
Storage:	Keep in a cool, well ventilated area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA	None	None
Petrolatum	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist.	None	None
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA Inhalable fraction.	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Petroleum distillates, hydrotreated, light naphthenic	5 mg/m3 TWA Inhalable fraction.	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None

Engineering controls:

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Black
Odor:	Mild, Petroleum
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	650 °F (343.3 °C)None
Melting point/ range:	Not available.
Specific gravity:	1.2
Vapor density:	Not available.
Flash point:	236 °C (456.8 °F) HST-US D09F; Flash/Fire Point By Cleveland Open Cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not determined
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Negligible
Partition coefficient (n-octanol/water):	Not determined
VOC content:	0 %; 0 g/l Essentially Zero
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Acrid smoke and fumes.
Incompatible materials:	Strong acids. Oxidizing agents. Alkalis.
Reactivity:	Not available.
Conditions to avoid:	Excessive heat. Direct sunlight. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Graphite dust may be irritating
Skin contact:	May cause skin irritation.
Eye contact:	May cause eye irritation.
Ingestion:	May cause gastrointestinal disturbances.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Graphite	None	Lung
Petrolatum	None	Irritant
Distillates (petroleum), hydrotreated heavy naphthenic	None	Irritant
Petroleum distillates, hydrotreated, light naphthenic	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Graphite	No	No	No
Petrolatum	No	No	No
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Petroleum distillates, hydrotreated, light naphthenic	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.
Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health
CERCLA/SARA Section 313: None above reporting de minimis.
California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 8

Prepared by: Product Safety and Regulatory Affairs
Issue date: 04/02/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.



SAFETY DATA SHEET

1. Identification

Product identifier	SCRUBS® Hand Cleaner Towels
Other means of identification	
Part Number	42201, 42210, 42225, 42230, 42232, 42256, 42260, 42272, 42274, 42280
Recommended use	A deep cleaning hand cleaner towel designed for removing heavy dirt, oil and greases from hands.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Company name	ITW Pro Brands
Address	805 E. Old 56 Highway Olathe, KS 66061
Country	(U.S.A.) Tel: +1 800-443-9536
In Case of Emergency	1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Alcohols, C12-15, ethoxylated		68131-39-5	1 - 3
Distillates Petroleum Hydrotreated Light		64742-47-8	1 - 3
d-limonene		5989-27-5	1 - 3
Neopentyl Glycol		126-30-7	0.1 - 1
Phenoxyethanol		122-99-6	0.1 - 1
Sodium Dodecanol Sulfosuccinate		577-11-7	0.1 - 1

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Mechanically pick up material and place in a proper container for disposal. Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid prolonged exposure. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S. - OSHA Components

	Type	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	PEL	5 mg/m ³	Oil mist

ACGIH Components

	Type	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m ³	Oil mist

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

Color Colorless-blue / white

Odor Citrus

Odor threshold Not available.

pH 6

Melting point/freezing point Not available.

Initial boiling point and boiling range 212 °F (100 °C)

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density > 1

Relative density Not available.

Solubility(ies)

Solubility (water) Miscible.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.995

VOC 0 % per US State and Federal Consumer Product Regulations

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Alcohols, C12-15, ethoxylated (CAS 68131-39-5)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 0.1 mg/l, 8 Hours
Oral		
LD50	Rat	> 5000 mg/kg
d-limonene (CAS 5989-27-5)		
Acute		
Oral		
LD50	Rat	> 2000 mg/kg
Neopentyl Glycol (CAS 126-30-7)		
Acute		
Oral		
LD50	Rat	> 6400 mg/kg
Phenoxyethanol (CAS 122-99-6)		
Acute		
Dermal		
LD50	Rabbit	> 2200 mg/kg, 24 Hours
Oral		
LD50	Rat	1400 mg/kg
Sodium Dodecanol Sulfosuccinate (CAS 577-11-7)		
Acute		
Dermal		
LD50	Rabbit	> 10000 mg/kg, 24 Hours

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
d-limonene (CAS 5989-27-5)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	
Not listed.	
US. National Toxicology Program (NTP) Report on Carcinogens	
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.
Further information	This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species		Test Results
Alcohols, C12-15, ethoxylated (CAS 68131-39-5)			
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	0.37 - 0.43 mg/l, 48 hours
Fish	LC50	Channel catfish (Ictalurus punctatus)	1.04 - 1.39 mg/l, 96 hours
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
d-limonene (CAS 5989-27-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	0.619 - 0.796 mg/l, 96 hours
Phenoxyethanol (CAS 122-99-6)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	337 - 352 mg/l, 96 hours
Sodium Dodecanol Sulfosuccinate (CAS 577-11-7)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	20 - 40 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

d-limonene	4.232
Phenoxyethanol	1.16

Mobility in soil Not established.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT
Not regulated as dangerous goods.

IATA
Not regulated as dangerous goods.

IMDG
Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

General information This material is not regulated by any mode of transportation.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance
Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List
Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-11-2019

Revision date 06-03-2019

Version # 02

Disclaimer

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

Accidental release measures: Methods and materials for containment and cleaning up
Physical & Chemical Properties: Multiple Properties
Transport Information: Proper Shipping Name/Packing Group
HazReg Data: International Inventories
GHS: Classification



SAFETY DATA SHEET

1. Identification

Product identifier SCRUBS® Hand Cleaner Towels

Other means of identification

Part Number 42201, 42210, 42225, 42230, 42232, 42256, 42260, 42272, 42274, 42280

Recommended use A deep cleaning hand cleaner towel designed for removing heavy dirt, oil and greases from hands.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

Address 805 E. Old 56 Highway
Olathe, KS 66061

Country (U.S.A.)

In Case of Emergency Tel: +1 800-443-9536
1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Alcohols, C12-15, ethoxylated		68131-39-5	1 - 3
Distillates Petroleum Hydrotreated Light		64742-47-8	1 - 3
d-limonene		5989-27-5	1 - 3
Neopentyl Glycol		126-30-7	0.1 - 1
Phenoxyethanol		122-99-6	0.1 - 1
Sodium Dodecanol Sulfosuccinate		577-11-7	0.1 - 1

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Mechanically pick up material and place in a proper container for disposal. Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid prolonged exposure. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S. - OSHA

Components	Type	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	PEL	5 mg/m ³	Oil mist

ACGIH

Components	Type	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m ³	Oil mist

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

Color Colorless-blue / white

Odor Citrus

Odor threshold Not available.

pH 6

Melting point/freezing point Not available.

Initial boiling point and boiling range 212 °F (100 °C)

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density > 1

Relative density Not available.

Solubility(ies)

Solubility (water) Miscible.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.995

VOC 0 % per US State and Federal Consumer Product Regulations

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Alcohols, C12-15, ethoxylated (CAS 68131-39-5)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 0.1 mg/l, 8 Hours
Oral		
LD50	Rat	> 5000 mg/kg
d-limonene (CAS 5989-27-5)		
Acute		
Oral		
LD50	Rat	> 2000 mg/kg
Neopentyl Glycol (CAS 126-30-7)		
Acute		
Oral		
LD50	Rat	> 6400 mg/kg
Phenoxyethanol (CAS 122-99-6)		
Acute		
Dermal		
LD50	Rabbit	> 2200 mg/kg, 24 Hours
Oral		
LD50	Rat	1400 mg/kg
Sodium Dodecanol Sulfosuccinate (CAS 577-11-7)		
Acute		
Dermal		
LD50	Rabbit	> 10000 mg/kg, 24 Hours

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
d-limonene (CAS 5989-27-5)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	
Not listed.	
US. National Toxicology Program (NTP) Report on Carcinogens	
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.
Further information	This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species		Test Results
Alcohols, C12-15, ethoxylated (CAS 68131-39-5)			
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	0.37 - 0.43 mg/l, 48 hours
Fish	LC50	Channel catfish (Ictalurus punctatus)	1.04 - 1.39 mg/l, 96 hours
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
d-limonene (CAS 5989-27-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	0.619 - 0.796 mg/l, 96 hours
Phenoxyethanol (CAS 122-99-6)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	337 - 352 mg/l, 96 hours
Sodium Dodecanol Sulfosuccinate (CAS 577-11-7)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	20 - 40 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

d-limonene	4.232
Phenoxyethanol	1.16

Mobility in soil Not established.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT
Not regulated as dangerous goods.

IATA
Not regulated as dangerous goods.

IMDG
Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

General information This material is not regulated by any mode of transportation.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance
Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List
Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-11-2019

Revision date 06-03-2019

Version # 02

Disclaimer

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

Accidental release measures: Methods and materials for containment and cleaning up
Physical & Chemical Properties: Multiple Properties
Transport Information: Proper Shipping Name/Packing Group
HazReg Data: International Inventories
GHS: Classification



SAFETY DATA SHEET

1. Identification

Product identifier SCRUBS® In-A-Bucket Hand Cleaner Towels

Other means of identification

Part Number 42201, 42210, 42230, 42232, 42256, 42260, 42272, 42274, 42280

Recommended use A cleaner wipe designed for removing dirt and grease from hands.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

Address 805 E. Old 56 Highway
Olathe, KS 66061

Country (U.S.A.)

Tel: +1 800-443-9536

In Case of Emergency 1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Not available.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates Petroleum Hydrotreated Light		64742-47-8	1 - 3
Sodium Dodecanol Sulfosuccinate		577-11-7	0.5 - 1
Dimethyl Glutarate		1119-40-0	< 0.5
D-limonene		5989-27-5	< 0.5
Phenoxyethanol		122-99-6	< 0.5

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	<p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.</p> <p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Mechanically pick up material and place in a proper container for disposal.</p>
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid prolonged exposure. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S. - OSHA Components

Components	Type	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	PEL	5 mg/m3	Oil mist

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Glycerin (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

ACGIH Components	Type	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m3	Oil mist

US. Workplace Environmental Exposure Level (WEEL) Guides Components	Type	Value	Form
Propylene Glycol (CAS 57-55-6)	TWA	10 mg/m3	Aerosol.

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Colorless-blue / white

Odor Citrus

Odor threshold Not available.

pH 6

Melting point/freezing point Not available.

Initial boiling point and boiling range 212 °F (100 °C)

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density > 1

Relative density Not available.

Solubility(ies)

Solubility (water) Miscible.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.995
VOC	0 % per US State and Federal Consumer Product Regulations

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the decomposition temperature. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Not available.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
3-iodo-2-propynyl-butylcarbamate (CAS 55406-53-6)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	1.1 g/kg
Alcohols, C12-15, ethoxylated (CAS 68131-39-5)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 100 mg/m ³ , 6 Hours
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 0.1 mg/l, 8 Hours

Components	Species	Test Results
Oral LD50	Rat	> 5000 mg/kg
D-limonene (CAS 5989-27-5)		
Acute Oral LD50	Rat	> 2000 mg/kg
Glycerin (CAS 56-81-5)		
Acute Oral LD50	Rat	18000 mg/kg
Phenoxyethanol (CAS 122-99-6)		
Acute Dermal LD50	Rabbit	> 2200 mg/kg, 24 Hours
Oral LD50	Rat	1400 mg/kg
Propylene Glycol (CAS 57-55-6)		
Acute Dermal LD50	Rabbit	> 2000 mg/kg, 24 Hours
Oral LD50	Rat	22000 mg/kg
Sodium Dodecanol Sulfosuccinate (CAS 577-11-7)		
Acute Dermal LD50	Rabbit	> 10000 mg/kg, 24 Hours
Oral LD50	Rat	> 1300 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
D-limonene (CAS 5989-27-5)	3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not available.	
Chronic effects	Prolonged inhalation may be harmful.	

Further information

This product has no known adverse effect on human health.

12. Ecological information**Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
3-iodo-2-propynyl-butylcarbamate (CAS 55406-53-6)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 0.05 - 0.089 mg/l, 96 hours
Alcohols, C12-15, ethoxylated (CAS 68131-39-5)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Ceriodaphnia dubia) 0.37 - 0.43 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 0.96 - 1.4 mg/l, 96 hours
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Bluegill (Lepomis macrochirus) 2.2 mg/l, 4 days
D-limonene (CAS 5989-27-5)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia pulex) 69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 0.619 - 0.796 mg/l, 96 hours
Glycerin (CAS 56-81-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 51000 - 57000 mg/l, 96 hours
Phenoxyethanol (CAS 122-99-6)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (Pimephales promelas) 337 - 352 mg/l, 96 hours
Propylene Glycol (CAS 57-55-6)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) > 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 710 mg/l, 96 hours
Sodium Dodecanol Sulfosuccinate (CAS 577-11-7)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 20 - 40 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential**Partition coefficient n-octanol / water (log Kow)**

D-limonene	4.57
Glycerin	-1.76
Phenoxyethanol	1.16
Propylene Glycol	-0.92

Mobility in soil

Not established.

Other adverse effects

None known.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

General information This material is not regulated by any mode of transportation.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Glycerin (CAS 56-81-5)

Other Flavoring Substances with OSHA PEL's

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

3-iodo-2-propynyl-butylcarbamate (CAS 55406-53-6)

Glycerin (CAS 56-81-5)
Propylene Glycol (CAS 57-55-6)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-05-2021

Version # 01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.



Safety Data Sheet California CARB Compliant

1 - Identification

<p>Product Name: WD-40 Multi-Use Product Aerosol</p> <p>Product Use: Lubricant, Penetrant, Drives Out Moisture, Removes and Protects Surfaces From Corrosion</p> <p>Restrictions on Use: None identified</p> <p>SDS Date Of Preparation: March 5, 2019</p>	<p>Manufacturer: WD-40 Company</p> <p>Address: 9715 Businesspark Avenue San Diego, California, USA 92131</p> <p>Telephone:</p> <p>Emergency: 1-888-324-7596</p> <p>Information: 1-888-324-7596</p> <p>Chemical Spills: 1-800-424-9300 (Chemtrec) 1-703-527-3887 (International Calls)</p>
--	---

2 – Hazards Identification

Hazcom 2012/GHS Classification:

Flammable Aerosol Category 1

Gas Under Pressure: Compressed Gas

Aspiration Toxicity Category 1

Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)

Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Label Elements:



DANGER!

Extremely Flammable Aerosol.

Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Prevention

Keep away from heat, sparks, open flames, hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing vapors or mists.

Use only outdoors or in a well-ventilated area.

Response

IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

Storage

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

Disposal

Dispose of contents and container in accordance with local and national regulations.

3 - Composition/Information on Ingredients

Ingredient	CAS #	Weight Percent	US Hazcom 2012/ GHS Classification
LVP Aliphatic Hydrocarbon	64742-47-8	45-50%	Aspiration Toxicity Category 1
Petroleum Base Oil	64742-56-9 64742-65-0 64742-53-6 64742-54-7 64742-71-8	<35%	Not Hazardous
Aliphatic Hydrocarbon	64742-47-8	<25%	Flammable Liquid Category 3 Aspiration Toxicity Category 1 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)
Carbon Dioxide	124-38-9	2-3%	Simple Asphyxiant Gas Under Pressure, Compressed Gas

Note: The specific chemical identity and exact percentages are a trade secret.

4 – First Aid Measures

Ingestion (Swallowed): Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

Eye Contact: Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists.

Skin Contact: Wash with soap and water. If irritation develops and persists, get medical attention.

Inhalation (Breathing): If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

Signs and Symptoms of Exposure: Harmful or fatal if swallowed. Aspiration of liquid into the lungs during swallowing or vomiting may cause lung damage. May cause eye and respiratory irritation. Inhalation of mists or vapors may cause drowsiness, dizziness and other nervous system effects. Skin contact may cause drying of the skin.

Indication of Immediate Medical Attention/Special Treatment Needed: Immediate medical attention is needed for ingestion.

5 – Fire Fighting Measures

Suitable (and unsuitable) Extinguishing Media: Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

Specific Hazards Arising from the Chemical: Extremely flammable aerosol. Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Combustion will produce oxides of carbon and hydrocarbons.

Special Protective Equipment and Precautions for Fire-Fighters: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting containers.

6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area.

Methods and Materials for Containment/Cleanup: Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty.

Conditions for Safe Storage: Store in a cool, well-ventilated area, away from incompatible materials. Do not store above 120°F or in direct sunlight. U.F.C (NFPA 30B) Level 3 Aerosol. Store away from oxidizers.

8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure Limits
LVP Aliphatic Hydrocarbon	1200 mg/m ³ TWA (manufacturer recommended)
Petroleum Base Oil	5 mg/m ³ TWA (Inhalable) ACGIH TLV (as Mineral oil) 5 mg/m ³ TWA OSHA PEL (as Oil mist, mineral)
Aliphatic Hydrocarbon	1200 mg/m ³ TWA (manufacturer recommended)
Carbon Dioxide	5000 ppm TWA, 30,000 ppm STEL ACGIH TLV 5000 ppm TWA OSHA PEL

The Following Controls are Recommended for Normal Consumer Use of this Product

Appropriate Engineering Controls: Use in a well-ventilated area.

Personal Protection:

Eye Protection: Avoid eye contact. Always spray away from your face.

Skin Protection: Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where skin contact is likely.

Respiratory Protection: None needed for normal use with adequate ventilation.

For Bulk Processing or Workplace Use the Following Controls are Recommended

Appropriate Engineering Controls: Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

Personal Protection:

Eye Protection: Safety goggles recommended where eye contact is possible.

Skin Protection: Wear chemical resistant gloves.

Respiratory Protection: None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

Work/Hygiene Practices: Wash with soap and water after handling.

9 – Physical and Chemical Properties

Appearance:	Light amber liquid	Flammable Limits: (Solvent Portion)	LEL: 0.6% UEL: 8%
Odor:	Mild petroleum odor	Vapor Pressure:	95-115 PSI @ 70°F
Odor Threshold:	Not established	Vapor Density:	Greater than 1 (air=1)
pH:	Not Applicable	Relative Density:	0.8 – 0.82 @ 60°F
Melting/Freezing Point:	Not established	Solubilities:	Insoluble in water
Boiling Point/Range:	361 - 369°F (183 - 187°C)	Partition Coefficient; n-octanol/water:	Not established
Flash Point:	138°F (59°C) Tag Closed Cup (liquid)	Autoignition Temperature:	Not established

Evaporation Rate:	Not established	Decomposition Temperature:	Not established
Flammability (solid, gas):	Flammable Aerosol	Viscosity:	2.79-2.96 cSt @ 100°F
VOC:	24.1% MIR=0.43gO3/gVOC	Pour Point:	-63°C (-81.4°F) ASTM D-97

10 – Stability and Reactivity

Reactivity: Not reactive under normal conditions

Chemical Stability: Stable

Possibility of Hazardous Reactions: May react with strong oxidizers generating heat.

Conditions to Avoid: Avoid heat, sparks, flames and other sources of ignition. Do not puncture or incinerate containers.

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide and carbon dioxide.

11 – Toxicological Information

Symptoms of Overexposure:

Inhalation: High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

Skin Contact: Prolonged and/or repeated contact may produce mild irritation and defatting with possible dermatitis.

Eye Contact: Contact may be irritating to eyes. May cause redness and tearing.

Ingestion: This product has low oral toxicity. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

Chronic Effects: None expected.

Carcinogen Status: None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA.

Reproductive Toxicity: None of the components is considered a reproductive hazard.

Numerical Measures of Toxicity:

Acute Toxicity Estimates: Oral > 5,000 mg/kg; Dermal >2,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

12 – Ecological Information

Ecotoxicity: No specific aquatic toxicity data is currently available; however components of this product are not expected to be harmful to aquatic organisms

Persistence and Degradability: Components are readily biodegradable.

Bioaccumulative Potential: Bioaccumulation is not expected based on an assessment of the ingredients.

Mobility in Soil: No data available

Other Adverse Effects: None known

13 - Disposal Considerations

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Do not puncture or incinerate containers, even empty. Dispose in accordance with federal, state, and local regulations.

14 – Transportation Information

DOT Surface Shipping Description: UN1950, Aerosols, 2.1 Ltd. Qty
(Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)
IMDG Shipping Description: UN1950, Aerosols, 2.1, LTD QTY
ICAO Shipping Description: UN1950, Aerosols, flammable, 2.1

NOTE: WD-40 Company does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

15 – Regulatory Information

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Acute Health, Fire Hazard, Sudden Release of Pressure

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product does not require a California Proposition 65 warning.

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification

16 – Other Information

HMIS Hazard Rating:

Health – 1 (slight hazard), Fire Hazard – 4 (severe hazard), Physical Hazard – 0 (minimal hazard)

Revision Date: March 5, 2019

Supersedes: July 19, 2018

Revision Summary: Section 9 update VOC data

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA

Reviewed by: I. Kowalski

Regulatory Affairs Dept.

1012200/No.0084704